

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

14

Township Corner:

Found - 15" Fir, now 36"; Corner Tree, had been opened, scribing.
18" Fir, now stump, S. 70° W. 18.5 ft., shows good scar.
15" Fir, now stump, N. 66° W. 79.9 ft., shows scar.
48" Fir, now 49", N. 48° E. 19.8 ft., very old bark scribe.
15" Fir, now 34", S. 40° E. 13.2 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T30S R
(N-W Side of Office 2 S 36 | S 31 1
Corner Tree) 1966 W S 1 | S 6 W
T31S

New BT's: 12" D. Fir N. 19° W. 81.3 ft. scribed T30S R2W S36 CS BT.
11" D. Fir S. 12° W. 109.3 ft. scribed T31S R2W S 1 CS BT.
Distances to center of corner tree. - Corner lies on top
of main ridge, running East & West.

15

Sec. Cor. to Sections 5 - 6 - 7 - 8.

Found - 10" D. Fir, now stump, N. 71° W. 27.1 ft., had been opened for scribe
24" D. Fir, now stump, S. 69° W. 38.9 ft., shows good scar.
10" Fir, now burnt stub, S. 56° E. 17.2 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S RLW
Office, 1966 S 6 | S 5
S 7 | S 8

New BT's: 9" Maple S. 16° W. 62.8 ft. scribed T31S RLW S7 CS BT.
10" Maple N. 86° W. 68.0 ft. scribed T31S RLW S6 CS BT.
8" Hemlock S. 84° E. 106.5 ft. scribed T31S RLW S8 CS BT.
8" Hemlock N. 1° E. 109.3 ft. scribed T31S RLW S5 CS BT.

16

1/4 Corner to Sections 17 and 16.

Found - 12" W. Oak, now 19", N. 15° E. 23.1 ft., had been opened for scribe "S".
No trace of other Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S RLW
Office, 1966 1/4 S 17 / S 16

New BT: 8" D. Fir N. 27° W. 22.1 ft. scribed 1/4 S17 CS BT.
Reblazed & Rescribed: 19" W. Oak N. 15° E. 23.1 ft. scribed 1/4 S16 CS BT.
Note - Logging Road bears East 60.0 ft.

17

1/4 Corner to Sections 6 and 5.

Found - 12" Pine, now 18", S. 80° W. 40.4 ft. scribe, "S" visible, had
been opened. Opened tree for BT.
6" Pine S. 55° W. 25.4 ft., no trace.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S RLW
Office, 1966 1/4 S 6 / S 5

New BT's: 14" D. Fir N. 43° W. 13.2 ft. scribed 1/4 S 6 CS BT.
8" D. Fir N. 48° E. 13.0 ft. scribed 1/4 S 5 CS BT.
note - This corner lies on top of small ridge, running E. & W.

18

1/4 Corner to Sec. 6, T31-1W. & Sec. 1, T31-2W.

Found - 18" Oak, now 24", N. 60° W. 15.2 ft., rotten face.
20" Oak, now 22", S. 80° E. 9.9 ft.; Dead Snag. Tree had been
opened for scribe "BT".

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's T31S
Office, 1966 R2W 1/4 S 1 / S 6 RLW

New BT's: 12" D. Fir S. 55 1/2° W. 10.8 ft. scribed 1/4 S1 CS BT.
10" D. Fir N. 55 1/2° E. 19.6 ft. scribed 1/4 S 6 CS BT.

19

Sec. Cor. to Secs. 7 & 18, T31-1W. & Sec. 12 & 13, T31-2W.

Found - Corner Tree & Sandstone at Cor. See Ren. #12, T31-2W
Orig. 20" W. Oak, now 18" S. 57° E. 57.4 ft., scribe visible #199
8", now 7" W. Oak, S. 42° W. 8.6 ft., shows good scar.
10", now 14" Pine N. 55° W. 41.6 ft. Opened for scribe, pitched over
scribing visible.

Set - Brass Cap on N. Side of 6" Cor. Tree: R T31S R
County Surveyor's 2 S 12 | S 7 1
Office, 1966 W S 13 | S 18 W
July, 1966

John M. Powell
Frank Jones & Joe Brady
June 1966
C. S. File No. 54/28

RE-RENEWED, SEE CORNER NO. #164
RE-RENEWED, SEE CORNER NO. #300
RE-RENEWED, SEE CORNER NO. #194
RE-RENEWED, SEE CORNER NO. #199