

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

20

Sec. Corner to Secs. 18 & 19, T31-1W. & Secs. 13 & 24, T31-2W.
Found - Stone at Sec. Cor. 16x10x8. See Ren. #11, T31-2W.
No trace of N. E. nor S. W. Bearing Trees.
20" B. Oak N. 65 $\frac{1}{2}$ ° W. 44.2 ft. Opened for scribe "3BT" (Rotten)
(Find bearing to be N. 75 $\frac{1}{2}$ ° W.)
20" Laurel, now 24", S. 56° W. 17.8 ft. No scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
2	S 13	S 18 1
W	S 24	S 19 W

New BT's: 24" Cedar N. 45 $\frac{1}{2}$ ° W. 11.9 ft. scribed T31SR2W S13 CS BT.
14" D. Fir N. 2 $\frac{1}{2}$ ° W. 22.9 ft. scribed T31S R2W.
10" D. Fir S. 45° E. 39.4 ft. scribed T31S R1W S19 CS BT.
Reblazed & Rescribed: 24" Laurel S. 56° W. 17.8' Mkd: T31SR2W S24 CS BT.

21

$\frac{1}{4}$ Corner to Sec. 19, T31-1W. & Sec. 24, T31-2W.
Found - 30" Corner Tree, now dead snag.
18" D. Fir Stump N. 74° W. 20.5 ft., bark scribed $\frac{1}{4}$ S. # 209.
30" D. Fir, now dead snag, N. 10° E. 39.4 ft., shows good scar,
opened tree for scribe. (find dist. to be 34.0 ft.)
Set - Brass Cap for Cor. alongside South Side of Corner Tree mkd:

R	T 31 S	R	County Surveyor's
$\frac{1}{4}$	SW S 24 / S 19	1W	Office, 1966

New BT's: 9" W. Fir N. 29° W. 34.6 ft. scribed $\frac{1}{4}$ S24 CS BT.
12" W. Fir S. 59° E. 13.0 ft. scribed $\frac{1}{4}$ S19 CS BT.

RE-
CORNER

John M. Powell
Frank Jones & Terry Connell
July 1966
C. S. File No. 54/28

22

Sec. Cor. to Secs. 30 & 19, 31-1W & Secs. 24 & 25, T31-2W.
Found - 1922 GLO Brass Cap, mkd. (This cap 1 mi. too
T31S S 25 | S 30 R1W far North, more likely
R2W S 36 | S 31 marked wrong.)
Found - Orig. Trees for Sec. Cor.

S24		S 19
S 25		S 30

18" D. Fir, now snag, N. 5° E. 13.2 ft. Opened for scribe "BT".
20" D. Fir, now down, N. 60° W. 4.0 ft. Opened for scribe "BT".
18" D. Fir, now 27", S. 89 $\frac{1}{2}$ ° E. 91.1 ft., shows scar-rescribed.
18" D. Fir, now stump S. 50° W. 17.3 ft. (not 21.8') no scribing
on stump, but part of old burned face.
1922 BT's: 11" D. Fir N. 79° W. 9.4 ft., opened for scribe "R2W".
13" D. Fir S. 49° W. 30.3 ft., shows good scar.
27" D. Fir S. 89 $\frac{1}{2}$ ° E. 91.1 ft., rescribed on bark.
By ring count trees were scribed in 1922.
Set - Brass Cap alongside 1922 Cap mkd: County Surveyor's Office, 1966

R	T 31 S	R R
2	S 24	S 19 1
W	S 25	S 30 W

New BT's: 12" D. Fir S. 76° E. 9.5 ft. scribed T31S R1W S 30 CS BT.
11" D. Fir N. 19° E. 27.9 ft. scribed T31S R1W S19 CS BT.
10" D. Fir N. 67° W. 23.4 ft. scribed T31S R2W S24 CS BT.
11" D. Fir S. 42° W. 18.7 ft. scribed T31S R2W S25 CS BT.

FD OK 7/7/81
L. HERRINGTON
CS 61/87

23

$\frac{1}{4}$ Corner to Sec. 18, T31-1W. & Sec. 13, T31-2W.
Found - Sandstone at $\frac{1}{4}$ Corner, no marks visible. See Ren. #13, T31-2W.
10" Fir, now 17" N. 32° E. 60.1 ft., bark scribed "S".
14" Fir, now 23", N. 32° W. 48.8 ft., bark scribed $\frac{1}{4}$ S13 CS BT.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
2W	S 13	S 18 1W

Reblazed & Rescribed: 17" D. Fir N. 32° E. 60.1 ft. scribed $\frac{1}{4}$ S18 CS BT.
23" D. Fir N. 32° W. 48.8 ft. scribed $\frac{1}{4}$ S13 CS BT.
Note - This corner lies about 150.0 ft. south of high rock bluffs
that drop off to the west and north.

24

$\frac{1}{4}$ Corner to Sec. 7, T31-1W. & Sec. 12, T31-2W.
Found - 6" Maple Corner Tree. See Ren. #3.
4" Maple, now 6", N. 51 $\frac{1}{2}$ ° W. 15.0 ft., scribe marks visible.
12" D. Fir, now 12" N. 2 $\frac{1}{2}$ ° W. 19.0 ft., shows good scar.
Set - Brass Cap alongside 6" Maple mkd: County Surveyor's Office, 1966

R	T 31 S	R
$\frac{1}{4}$	2W S 12 / S 7	1W

Note - This corner lies 30' west of 60' high, vertical bluff.
New BT: 21" D. Fir N. 5° W. 26.7 ft. scribed $\frac{1}{4}$ S12 CS BT.

RE-
CORNER
SEE CORNER NO #191