

Douglas County Surveyor's Record of
Government Corners Renewed

M.W.W. T. 31 S. T.S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Sec. Cor. to Secs. 30 & 31, T31-1W. & Secs. 25 & 36, T31-2W. 25

Found - Stone at Corner, no marks visible.

- Orig. 28" Cedar N. 5° E. 5.9 ft., scribe visible "31S RLW S30".
- Orig. 16" Pine, now snag, N. 22° W. 22.4 ft. scribe visible.
- Orig. 30" Pine S. 66° E. 87.1 ft., scribe visible, pitched over.
- Orig. 14" Laurel, now 19", S. 74½° W. 97.7 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
2	S 25 S 30	1
W	S 36 S 31	W

New BT's: 6" D. Fir S. 41° W. 7.5 ft. scribed T31SR2W S36 CS BT.
7" Laurel N. 66° W. 22.6 ft. mkd; T31S R2W S25 CS BT.

Note - This corner lies west of trail. Tag on Pine Tree N. 66° W. 87.1 ft. to section corner.

¼ Corner to Sec. 30, T31-1W. & Sec. 25, T31-2W. 26

Found - 12" Laurel, now 24", N. 70° E. 18.5 ft. Opened for "BT" scribe.
No. trace of N. W. BT.

1922 GLO Brass Cap, out of ground.

Reset - 1922 GLO Brass Cap mkd. U.S. Gen. Land Office, 1922

¼	S 25 / S 30
---	-------------

Reblazed & Resrbd: 20" Laurel N. 70° E. 18.5 ft. mkd. ¼ S30 CS BT.
New BT: 24" D. Fir S. 81° W. 20.0 ft. mkd. ¼ S25 CS BT.

¼ Cor. to Sec. 31, T31-1W. & Sec. 36, T31-2W. 27

Found - Stone at ¼ Corner, marked "¼".
18" Cedar, down & rotten, N. 10° E. 9.9 ft., fd. scribing "B".
28" Cedar, burned stump, S. 47° W. 14.5 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T31S	R
2	W S 36 / S 31	W

New BT's: 6" D. Fir N. 15° E. 17.9 ft. mkd. ¼ S31 CS BT.
8" D. Fir S. 60° W. 17.0 ft. mkd. ¼ S36 CS BT.

Note - This corner lies 50.0 ft. north of trail, location tag on trail.

Corner to Sec. 36, T31-2W. & Sec. 31, T31-1W only. 28

Found - Orig. 30", now 30" Fir N. 30° E. 38.3 ft., shows good scar.
Orig. 14" Fir, now down, N. 33° W. 19.1 ft. scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T31S	R
2	S 36 / S 31	1
W	S 1	W
T 32 S		

New BT's: 24" D. Fir N. 19° W. 34.6 ft. scribed T31S R2W S36 CS BT.

Section Corner to Sections 7 - 8 - 17 - 18. #211 29

Found - 12" B.Oak, now 26", S. 55° W. 65.3 ft., shows scar. *Fd. ok. by L. Herzstein, U.S.F.S. 1/17/84 see CS-62/15*
15" Oak, now down, S. 45° E. 99.0 ft., scribe found "BT".
15" Oak, now down, N. 38° E. 58.1 ft.
12" Oak, now down, N. 12° W. 73.9 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R 1 W
S 7	S 8
S 18	S 17

New BT's: 13" D. Fir N. 47° E. 26.3 ft. mkd. T31S RLW S 8 CS BT.
14" Laurel N. 62° W. 17.0 ft. mkd. T31S RLW S 7 CS BT.
12" D. Fir S. 37° W. 28.1 ft. mkd. T31S RLW S18 CS BT.
13" D. Fir S. 50° E. 52.0 ft. mkd. T31S RLW S17 CS BT.

Sept. 9, 1966

Sec. Corner to Sections 8 - 9 - 16 - 17 30

Found - Orig. 18" Oak, now dead, S. 22° W. 17.8 ft.
Orig. 20" Oak, now 24", N. 5° W. 25.1 ft. Tree opened, scribe visible
Orig. 24", Pine, now Stump, S. 47° E. 28.4 ft., shows scar, stump has been moved.

GLO Brass Cap mkd. in 1923.

New BT's: 12" D. Fir N. 27° W. 29.4 ft. mkd. T31S RLW S 8 CS BT.
11" D. Fir S. 65° W. 110.0 ft. mkd. T31S RLW S17 CS BT.
9" D. Fir N. 70° E. 2.9 ft. mkd. T31S RLW S9 CS BT.

No tree in S. E. Quad. This corner is at end of spur road on north edge of landing.

Sept. 2, 1966

John M. Powell
Frank Jones & Terry Connell
July 1966
C. S. File No. 54/28

RE-NEWED

See BLK
Dependent
V 54
Pg 20783

RE-NEWED SEE CORNER NO #162