

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

55

Section Corner to Sections 4 and 3. T32-1
Found - No trace of Stone or S.W. BT.
10", now 14" Laurel, S. 35° E. 13.2 ft., shows scar.
5", now 8" D.Fir, N. 47° E. 5.9 ft., rotten face, scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W
Office S 34
1968 S 4 | S 3
T 32 S
New BT's: 6" Live Oak S. 74° W. 35.4 ft. mkd. T32S R1W S4 CS BT.
8" Live Oak N. 51° W. 26.2 ft. mkd. T31S R1W S34 CS BT.
S. E. BT. O. K. and Tagged.

56

1/4 Corner to Section 34 only, T31-1W.
Found - No trace of Stone or S. E. Bearing Tree.
30", now 30" D.Fir, N. 70° E. 19.8 ft., opened for scribe "4 S".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W
Office 1/4 S 34
1968 T 32 S
New BT: 13" D.Fir N. 42° W. 20.6 ft. mkd. 1/4 S34 CS BT.
N. E. Bearing Tree O.K. and Tagged.

57

1/4 Corner to Section 33 only, T31-1W. *FO. OK 12/92 M 116-30 BY KAISER*
Found - 14x10x8 Corner Stone mkd. with "1/4" on the North Face.
40", now 46" Cedar S. 25° W. 39.0 ft. (Rec. S15W 34.3) shows scribing.
36" Fir, now 38" Stump, N. 3° E. 19.1', opened & found scribing "1/4 BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R1W 1/4 S 33
Office, 1968 T32S
New BT's: 14" Cedar N. 54° W. 41.0 ft. mkd. "1/4 S33 CS BT".
12" Fir N. 42° E. 46.6 ft. mkd. "1/4 S33 CS BT".
This cor. lies in S-W fence corner, 150.1' E. of the Sec. Cor. to 4 & 5,
T.32-1W., see below, and 300' north of a road.

58

Sec. Corner to Sections 4 and 5, T32-1W. *FO. OK 12/92 M 116-30 BY KAISER*
Found - Stone at Corner, 18x11x8 with 4 grooves on it.
10" Fir, now a stob, N. 40° W. 4.6 ft., opened & found scribing of "BT".
8" Fir, now pieces of wood & a hole, S. 65° E. 5.3 ft., shows scribing.
8" Laurel, now a stump, hole, S. 18° W. 18.5 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R1W S 33
Office, 1968 T32S S 5 | S 4
New BT's: 15" D.Fir S. 21° E. 26.3 ft. mkd. T32S R1W S4 CS BT.
10" Y.Pine S. 65° W. 25.1 ft. mkd. T32S R1W S5 CS BT.
This cor. lies N-W fence, 150.1 ft. W. of 1/4 Cor. Sec. 33 only, see above,
and 300 ft. north of a road. 8/1/68

59

Section Corner to Section 1 and 2, T32-1W.
Found - Stone mkd. with 5 notches & C. C.
20", now 37" D.Fir, N. 3° W. 29.7 ft., tree opened, scribe visible.
10", now 10" D.Fir, S. 10° E. 68.0 ft. (slope dist.), shows good scar.
15", now 20" D.Fir, 65.4 ft. (Rec. 73.3, slope dist. -77.6'). Doug. Co.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R1W CC S 36
Office, 1968 T32S S 2 | S 1
Bearing Trees O. K. and Tagged. Jack. Co.
Record Dist. from Angle Point 195.4 ft. I find Dist. to be 187.0'.

60

Angle Point - This corner lies 61.4 ft. W. of 1/4 Cor. Sec. 36, T31-1W,
which is a Brass Cap, 1923, in good condition.
Found - No trace of Stone at corner. (Tagged BT's)
Orig. 12" D.Fir, now dead, S. 25° E. 13.0 ft. (Rec. S. 32E 14.5') scribe
visible "AP BT".
Orig. 16", now 16" D. Fir N. 71° E. 36.3 ft. Doug. Co.
Set - Brass Cap at Angle Point Mkd: County Surveyor's T31S R1W A P
Office 1968 T32S
Jack. Co.
New BT: 38" D.Fir S. 49° E. 22.0 ft. mkd. A.P. CS BT.

John M. Powell
Frank Jones & W. Penley
July and August, 1968
C. S. File No. 54/71