

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R.W.W.M.

KOKK-CHAPMAN CO., EUGENE, ORE. 21801

61

Township Corner.

Found - 30x15x6 Stone, 6 notches on N-S-E-W Sides.

36" D.Fir, now snag, N.10°E. 38.3 ft., bark scribe, good face.

15" D.Fir, now down, N.32°W. 15.2 ft.

35" D.Fir, now down, S.81°W. 51.5 ft., shows good scar.

35" D.Fir, now stump, S.45°E. 41.6 ft.

Set - Brass Cap at Twp. Cor. Mkd: County Surveyor's Office 1968

T 31 S	Doug. Co.
RLW S 1	RLE
S 1	S 31
	S 6

T 32 S Jack. Co.

New BT's: 8" Maple N. 8° W. 48.0 ft. mkd. T32S RLW S1 CS BT.

9" D.Fir N. 75° E. 49.6 ft. mkd. T31S RLE S31 CS BT.

6" Yew S. 23° E. 25.3 ft. mkd. T32S RLE S6 CSBT.

This corner 20.0 ft. west of ravine.

62

Township Corner. - Closing Corner.

Found - 35x15x5 Stone Mkd. CC and 6 notches

60", now 64" D.Fir, S.30°W. 1.3 ft., shows good scar.

30" D.Fir, now rotten stob, N.41°E. 18.5 ft.

40" D.Fir, now rotten stob, N.74°W. 27.7 ft.

Set - Brass Cap at Twp. Cor. Mkd: County Surveyor Office 1968

T. 31 S.	Doug. Co.
R	S 36
1	S 1
W	S 31
Jack. Co.	R
E	C.C. 1

New BT's: 9" D.Fir N. 2 1/2° E. 11.5 ft. mkd. T31S RLE S31 CC CS BT.

9" D.Fir N. 26° W. 17.2 ft. mkd. T31S RLW S36 GC CS BT.

8/9/68

63

Section Corner for Secs. 35 & 36, T31-1W.

Found - 36", now 39" D.Fir, N.20°W. 2.6 ft., shows good scar.

28", now 32" D.Fir, N.72°E. 11.9 ft., shows good scar.

GLO Brass Cap at Corner, properly marked in 1922.

New BT: 25" D.Fir S. 60° W. 24.5 ft. mkd: T32S RLW S 2 CS BT.

Note - This corner lies 50.5 ft. East of Angle Point, See Ren. #64, below.

64

Angle Point on line, 50.5 ft. West of Section Corner To Secs. 35 & 36 only, T31-1W.

Found - 6x12x6 Stone mkd. with notches and AP on north face.

16" D.Fir, now down, N.40°E. 4.6 ft. mcribe visible, AP BT.

24", now 26" D.Fir, N. 36° W. 21.8 ft., shows good scar.

Set - Brass Cap at Angle Point Mkd: County Surveyor's Office 1968

T 31 S	R 1 W
	A P
	T 32 S

New BT: 22" D.Fir N. 41° E. 19.1 ft. scribed A P CS BT.

Note - This corner lies 50.5 ft. west of Sec. Cor. above, Ren. #63.

65

1/4 Corner to Section 3 only, T32-1W.

Found - Mound of Stone & Stake at Corner, See Ren. #1, T32-1.

30", now 24" D.Fir, S.46°W. 8.0 ft., bark scribed "S3 1581 BT".

14", now 14" D.Fir, S.48°E. 37.2 ft., shows good scar.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office 1968

T 31 S	R 1 W
	S 3
	T 32 S

Reblazed & Rescribed:

24" D.Fir S. 46° W. 8.9 ft. mkd. 1/4 S 3 CS BT.

66

1/4 Corner to Section 35 only, T31-1W.

Found - GLO Brass Cap at 1/4 Cor., properly marked in 1922.

10", now 12" Maple, N. 42° E. 7.9 ft., shows good scar.

14" D.Fir, now stob, N. 72° W. 23.1 ft., shows good scar.

New BT: 26" D. Fir N. 22° W. 20.0 ft. mkd. 1/4 S35 CS BT.

Note - This corner lies 37.0 ft. E. of A.P. Corner & about 10' E. of draw.

John M. Powell  
 Frank Jones & W. Penley  
 August, 1968  
 C. S. File No. 54/71