

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
August, 1968
C. S. File No. 54/71

67
Angle Point 37.0 ft. West of $\frac{1}{4}$ Corner to Sec. 35, T31-LW., Ren. #66.
Found - Stone, 6x12x8 at Angle Point.
14" D.Fir, now stob, N.67°E. 15.8 ft., shows good scar.s.
14" D.Fir, now stob, S.80°E. 24.4 ft., scribe visible, "AP BT".
Set - Brass Cap at A.P. Cor. Mkd: County Surveyor's T 31 S R 1 W
Office A P
1968 T 32 S

New BT's: 14" D.Fir S.20°W. 33.7 ft. mkd: A P CS BT.
16" D.Fir S.30°E. 22.6 ft. mkd: A P CS BT.

Note - This corner lies 37.0 ft. West of $\frac{1}{4}$ Corner Sec. 35, T31-LW.

68
Section Corner to Sections 34 & 35, T31-LW.
Found - Mound of Stone at Corner, See Ren. #1, T31-LW.
12", now Maple, N.46 $\frac{1}{2}$ °W. 16.5 ft., scribe visible "34 BT".
6", now 10" Maple, N.64°E. 34.6 ft., rotten face, "BT" visible.
6", now 6" Maple, opened & rotten, N.34°W. 26.4 ft.
S.W. BT, 20" Fir, not found.
Set - Brass Cap at Cor. Mkd: T 31 S R 1 W County Surveyor's
S 34 | S 35 Office
S 3 1968

Reblazed & Rescribed: T 32 S
10" Maple N. 64° E. 34.6 ft. mkd. T31S R1W S35 CS BT.
New BT: 24" D.Fir S. 79° W. 36.5 ft. mkd. T32S R1W S3 CS BT.

69
Section Corner to Sections 3 and 2, T32-LW.
Found - GLO Brass Cap at Corner, properly marked 1922.
20", now 36" D.Fir, S. 45° W. 7.3 ft., shows scar.
12", now 14" D.Fir, S. 55° E. 31.0 ft., shows good scar.
6" D.Fir, now down, N. 5° W. 19.1 ft. (Old BT's. tagged & O.K.)
New BT: 17" D.Fir N. 15° E. 50.7 ft. mkd. T31S R1W S35 CS BT.
Note - This corner lies 187.4 ft. W. of Angle Point Corner, See Ren. #67.

70
Section Corner to Sections 20 - 21 - 28 - 29.
Found - 15", now 21" W.Oak, N.34°E. 52.1 ft., shows good scar.
6", now 13" B.Oak, N.15°W. 38.3 ft., shows good scar.
12", now 16" W.Oak, S.45°E. 31.7 ft., not healed, rotten face.
12" Pine, now 30" Stump, S.87°W. 38.9 ft., faint burnt scribe
marks visible on Pine Log from stump.
Set - Brass Cap at Cor. Mkd: County Surveyor's T. 31 S R 1 W
Office S 20 | S 21
1968 S 29 | S 28

Reblzd. & Rescrbd: 16" W.Oak S.45°W. 31.7 ft. mkd. T31S R1W S28 CS BT.
New BT: 9" W.Oak S. 53° W. 56.8 ft. mkd. T31S R1W S29 CS BT.

71
 $\frac{1}{4}$ Corner to Sections 29 and 28.
Found - 10", now 17" W.Oak, S.56°W. 49.5 ft., opened for scribe "BT".
15" Oak, now down & rotten, N.68°E. 26.4 ft. #181
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W
Office, 1968 $\frac{1}{4}$ S 29 | S 28

New BT's: 16" D.Fir S. 72° W. 44.0 ft. mkd. $\frac{1}{4}$ S 29 CS BT.
21" S. Pine S. 89° E. 20.5 ft. mkd. $\frac{1}{4}$ S 28 CS BT.

Note - This corner lies about 5.0 ft. E. of old picket fence running N-S.

72
 $\frac{1}{4}$ Corner to Sections 21 and 28.
Found - 10" B.Oak, now cut stump, S.88°W. 20.5 ft., opened stump for scribe.
30" Pine, now down, N. 24° W. 37.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W
Office $\frac{1}{4}$ S 21
1968 S 28

New BT's: 8" Fir West 11.3 ft. mkd: $\frac{1}{4}$ S 28 CS BT.
10" Fir N. 20° W. 9.0 ft. mkd: $\frac{1}{4}$ S 21 CS BT.

Note - This corner lies west of old picket fence about 20', fence runs N-S.