

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

87  
Section Corner to Sections 17 - 18 - 19 - 20.  
Found - 12" D.Fir, now 28" Double Fir, S. 8° W. 21.8 ft., opened  
for scribe "19". (Tried to count rings but too close)  
18", now 30" D.Fir, S. 5° E. 37.0 ft., shows good scar.  
20" D.Fir, now snag, N. 35° E. 19.8 ft. (Rec. 17.2), shows good scar.  
No trace of N. W. Bearing Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968  
T 31 S R 1 W  
S 18 | S 17  
S 19 | S 20  
New BT's: 28" D.Fir N. 83° W. 31.3 ft. mkd: T31S R1W S18 CS BT.  
6" Maple N. 26° E. 30.0 ft. mkd. T31S R1W S17 CS BT.  
Note - Call on creek 33.0 ft. north of corner is good.

88  
1/4 Corner to Sections 18 and 17.  
Found - 12" Oak, now rotten stump, N. 45° W. 33.7 ft., opened  
stump for scribe "BT".  
10" Oake, now stump hole, N. 40° E. 27.1 ft.  
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1968  
T 31 S R 1 W  
1/4 S 18 | S 17  
New BT's: 10" Cedar N. 40° W. 22.0 ft. scribed 1/4 S18 CS BT.  
16" D.Fir N. 67° E. 28.3 ft. scribed 1/4 S17 CS BT.  
This corner lies west of draw about 80 ft.

89  
Section Corner to Sections 16 - 17 - 20 - 21.  
Found - Orig. 24", now 34" Fir Snag, N. 20° W. 21.1 ft., scribe marks  
visible on open blaze.  
Orig. 30", now 38" Fir Snag, N. 40° E. 21.1 ft., shows scar.  
We do not open.  
No trace other bearing trees.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968  
T 31 S R 1 W  
S 17 | S 16  
S 20 | S 21  
New BT's: 9" Yew S. 88° E. 1.2 ft. mkd: "T31S R1W S21 CS BT.  
12" Maple N. 5° E. 68.5 ft. mkd: "T31S R1W S16 CS BT.  
18" D.Fir S. 48 1/2° W. 40.0 ft. mkd: " T31S R1W S20 CS BT.  
18" D.Fir N. 54° W. 36.2 ft. mkd: "T31S R1W S17 CS BT.  
This corner lies about 75 ft. north of logging road.

90  
Section Corner to Sections 19 - 20 - 29 - 30.  
Found - GLO Brass Cap, properly marked in 1922.  
6" D.Fir, now stump, S. 4° E. 47.5 ft., opened for scribe "BT".  
10" D.Fir, now stump, S. 2 1/2° W. 50.2 ft., shows good scar.  
10" D.Fir, now stump, N. 15° E. 23.8 ft., shows good scar.  
No trace of N. W. Bearing Tree.  
New BT's: 14" D.Fir S. 60° W. 15.2 ft. scribed T31S R1W S30 CS BT.  
10" D.Fir N. 75° W. 13.3 ft. scribed T31S R1W S19 CS BT.  
22" D.Fir S. 31° E. 15.2 ft. scribed T31S R1W S29 CS BT.  
8" Maple N. 46° E. 37.6 ft. scribed T31S R1W S20 CS BT.

91  
Section Corner to Sections 26 - 27 - 34 - 35.  
Found - 1922, GLO Brass Cap, properly marked.  
12" D.Fir, now rotten stump, N. 30° E. 23.8 ft., found scribe.  
36" D.Fir, now snag, S. 10° E. 25.1 ft., shows good scar.  
20", now 36" D.Fir, N. 47° W. (Rec. N50W) 37.0 ft., shows good scar.  
24" D.Fir, now down & rotten, S. 38° W. 7.3 ft.  
New BT's: 34" D.Fir N. 66° E. 40.6 ft. scribed T31S R1W S26 CS BT.  
12" R.Fir S. 24 1/2° E. 18.0 ft. scribed T31S R1W S35 CS BT.  
No trees available in S. W. Quad, old unit.

92  
1/4 Corner to Sections 26 and 27.  
Found - 1922 GLO Brass Cap, out of ground on steep west slope.  
8", now 15" D.Fir, N. 11° E. 18.5 ft., shows good scar.  
6", now 9" D.Fir, N. 36° W. 8.6 ft., opened for scribe "B".  
Reset - Brass Cap at 1/4 corner in Mound of Stone.  
New BT: 7" D.Fir N. 64° E. 4.6 ft. scribed 1/4 S27 CS BT.

John M. Powell  
Frank Jones & W. Penley  
August, 1968  
C. S. File No. 54/71

RE-RENEWED, CORNER NO. #172