Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

100

Section Corner to Sections 14 - 15 - 22 - 23.
Found - GLO Brass Cap, properly marked in 1922.
8",now 14" D.Fir, N. 36* E. 19.1 ft., shows good scar.
18",now 24" R.Fir, N. 65* W. 21.8 ft., scribe visible.
10",now 14" R.Fir, S. 51* E. 22.4 ft., scribe marks partially visible.
22" R.Fir, now stump, S. 17* W. 22.4 ft., scribe visible.
New BT: 30" D. Fir South 26.8 ft. scribed T31S R1W S22 CS BT.

\- - - - - -

101

¼ Corner Section 19 only, T31 - 1 E.
Found - GLO Brass Cap at ¼ Corner properly marked in 1922.
25" D.Fir,now 27", S.26*E.(Rec.S46E) 20.5 ft., shows good scar.
30" D.Fir, now down, N. 51* E. 15.8 ft.
New BT: 14" D.Fir S. 60* E. 39.4 ft. scribed "¼ S19 CS BT".

\- - - - - -

102

Section Corner to Sections 24 and 25 only, T31 - 1 W.
Found - Stone at Section Corner, no marks found.
30" D.Fir, now 6' Stob, S.75*W. 22.4 ft., scribe visible.
12",now 15" D.Fir, N.48*W.(Rec.N50W) 31.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

R	T 31 S		R
1 W	S 24 | S 25	S19	1 E

New BT's: 9" D.Fir S. 67* W. 36.6 ft. scribed T31S R1W S25 CS BT.
11" R.Fir S.,15* E. 17.3 ft. scribed T31S R1E S19 CS BT.

\= - - - - -

103

Section Corner to Sections 18 and 19, T31S - 1 E.
Found - GLO Brass Cap at Sec. Cor. properly marked in 1922.
12" Hemlock, now burnt stob, N. 21* E. 42.9 ft.
26" D.Fir, now burnt stump, S.43* E. 32.3 ft., shows good scar.
No Trees in area. Tagged All Stumps.
New Bearing Stumps: 28" Hemlock Stump N.71*E. 53.6 ft. scribe T31S R1E S18 CS BT.
55" D.Fir Stump S.60*W. 45.9 ft. scribed S24 CS BT.
Note - This corner lies in clear cut unit in bottom of draw under burnt-out 5' log on east edge. North of rocky point about 200 ft.

\- - - - - -

104

¼ Corner to Section 24 only, T31S - R1W.
Found - No trace of corner stone.
30" D.Fir, now stump, S. 69* W. 48.2 ft., opened for scribe.
6",now 13" R.Fir, N. 82* W. 15.2 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

R	T 31 S		R
1 W	¼ S 24 |		1 E

New BT: 30" D. Fir S. 71½*E. 33.6 ft. scribed S19 CS BT.
No trees to the West.

\- - - - - -

105

¼ Corner to Section 18 only, T31S -R1E.
Found - GLO Brass Cap, properly marked in 1922.
5" Hemlock, now down, N. 43* E. 17.9 ft.
5",now 8" Chinquapin, S.51*E.(Rec.71) 24.4 ft., scrb. visible on rotten face.
New BT's: 6" Hemlock N. 39* E. 10.0 ft. scribed ¼ S18 CS BT.
5" Maple S. 72* E. 13.8 ft. scribed ¼ S18 CS BT.
This corner lies on tip of ridge running about S72E & 42' S. of creek.

\- - - - - -

106

¼ Corner to Section 7 only, T31S - R1E.
Found - Stone at ¼ Corner marked "¼".
28",now 36" D.Fir, N.23*E. 42.9 ft., shows good scar.
36",now 37" D.Fir, S.26*E. 28.4 ft.,shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

R	T 31 S		R
1 W	S 7 | ¼		1 E

All Bearing Trees O. K. and Tagged.

\- - - - - -

John M. Powell
Frank Jones & W. Penley
September, 1968
C. S. File No. 54/71