

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S.      T. S.      R. 1 W.      R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 31881

John M. Powell  
Frank Jones & W. Penley  
September, 1968  
C. S. File No. 54/71

107

Section Corner to Sections 12 & 13 only, T31S - R1W.  
Found - Stone at Sec. Cor. marked with 4 notches.  
12", now 16" D. Fir, N. 71\*W. 13.9 ft., shows good scar.  
18", now 24" Cedar, S. 30\*W. 24.4 ft., shows scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R  
Office 1 S 12 S 7 1  
1968 W S 13 E

Reblzd. & Resrbd: 16" D. Fir N. 71\*W. 13.9 ft. mkd: T31S R1W S12 CS BT.  
24" Cedar S. 30\*W. 24.4 ft. mkd: T31S R1W S13 CS BT.  
New BT: 14" Cedar N. 6\* E. 12.8 ft. scribed T31S R1E S 7 CS BT.

108

$\frac{1}{4}$  Corner Section 13 only, T31S - R1W.  
Found - 5x10x5 Stone at  $\frac{1}{4}$  Corner, marked " $\frac{1}{4}$ " on West face.  
48" D. Fir, now snag, N. 2\* W. 116.8 ft., shows good scar.  
40" D. Fir, now snag, S. 22\* W. 111.5 ft., shows good scar.  
Remains of Cedar S. 70\*E. 15.2 ft. which was destroyed.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R  
Office 1 S 13 1  
1968 W  $\frac{1}{4}$  E

New BT's: 9" D. Fir N. 1\* W. 13.9 ft. mkd:  $\frac{1}{4}$  S13 CS BT.  
8" D. Fir S. 83\* W. 9.7 ft. mkd:  $\frac{1}{4}$  S13 CS BT.

109

Section Corner to Sections 7 and 18, T31S - R1E.  
Found - GLO Brass Cap, properly marked in 1923.  
40" D. Fir, now snag, S. 66\* E. 55.4 ft., shows good scar.  
40" D. Fir, now down, N. 53\* E. 7.3 ft.  
New BT's: 10" D. Fir N. 66\* E. 28.5 ft. scribed T31S R1E S7 CS BT.  
6" D. Fir S. 45\* E. 20.9 ft. scribed T31S R1E S18 CS BT.  
13" D. Fir N. 41\* W. 40.4 ft. scribed T31S R1W S13 CS BT.

110

$\frac{1}{4}$  Corner to Section 25 only, T31-1W.  
Found - No trace of corner stone.  
40" D. Fir, now stump, S. 75\* W. 9.9 ft., scribe visible.  
18", now 20" D. Fir, N. 59\* W. 24.4 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R  
Office 1  $\frac{1}{4}$  T 31 S 1  
1968 W S 25 E

New BT: 30" D. Fir S. 20\* W. 17.4 ft. scribed " $\frac{1}{4}$  S25 CS BT".

111

Section Corner to Sections 19 and 30 only, T31 - 1 E.  
Found - G. L. O. Brass Cap, properly marked in 1923.  
12" Yew, now 12", S. 58\* E. 13.2 ft. scribe visible.  
24", now 27" Hemlock, N. 35\* E. 27.1 ft., shows good scar.  
New BT: 9" Yew N. 44\* W. 28.0 ft. scribed T31S R1W S25 CS BT.

112

Section Corner to Sections 25 and 36 only, T31 - 1 W.  
found - Stone at Corner, no marks visible.  
30" D. Fir, now snag, S. 25\* W. 13.9 ft., shows good scar.  
24", now 27" R. Fir, N. 24\* W. 24.4 ft., scribe visible "R" & other marks  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R  
Office 1 S 25 S 30 1  
1968 W S 36 E

New BT's: 14" Hemlock S. 84\* W. 18.5 ft. mkd: T31S R1W S36 CS BT.  
14" D. Fir S. 47\* E. 24.5 ft. mkd: T31S R1E S30 CS BT.

113

$\frac{1}{4}$  Corner to Section 31 only, T31 - 1 E.  
Found - G.L.O. Brass Cap at Cor, properly marked in 1923.  
18", now 20" Fir, S. 56\* E. 35.6 ft., shows good scar.  
No trace of N. E. BT.  
New BT: 8" D. Fir N. 26\* E. 40.8 ft. scribed " $\frac{1}{4}$  S31 CS BT.