

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T.S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Ja hn M. Powell
 Frank Jones & W. Penley
 September, 1968
 C. S. File No. 54/71

$\frac{1}{4}$ Corner to Sections 23 and 24. 121
 Found - G.L.O. Brass Cap, properly marked in 1923, out of ground.
 7", now 14" D.Fir, N. 12* E. 7.3 ft., opened for scribe.
 8", now 20" D.Fir, S. 14* W. 17.8 ft., shows good scar.
 Reset - G.L.O. Brass Cap for $\frac{1}{4}$ corner.
 New BT: 20" D.Fir N. 54* W. 8.7 ft. scribed " $\frac{1}{4}$ S23 CS BT".
 All trees tagged.

Section Corner to Sections 23 - 24 - 25 - 26. 122
 Found - G.L.O. Brass Cap at Sec. Cor., properly marked in 1923.
 16", now 19" D.Fir, S. 40* E. 22.4 ft., shows good scar.
 40", now 36" D.Fir, S. 63* W. 12.5 ft., shows good scar.
 32", now 38" D.Fir, N. 23* W. 24.4 ft., pitched over, scribe visible.
 20" D.Fir, now snag, N. 80* E. 70.6 ft. scribe visible.
 New BT: 6" D. Fir N. 52* E. 24.5 ft. scribed S24 CS BT.
 Note - No other trees in reasonable distance.
 This corner lies on small spur running about S.50*W. top of spur rocky.

$\frac{1}{4}$ Corner to Sections 19 and 20. 123
 Found - Orig. 40" S.Pine, now 44" Windfall, N. 47* E. 26.4 ft., shows scbng.
 Orig. 18" Oak, now 26" Snag, S.28*W. 11.9 ft., shows poor face.
 16", now 18" D.Fir, N.19*40'W. 17.3 ft., shows good scribing. *REN.#6*
 18", now 18" D.Fir, S.48*10'E. 14.9 ft., shows good scribing.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W.
 Office, 1968 $\frac{1}{4}$ S 19 | S 20
 Note - This $\frac{1}{4}$ corner lies on general east slope.

$\frac{1}{4}$ Corner to Sections 28 and 33. 124
 Found - 15", now 23" Fir, S. 30* W. 6.6 ft., bark scribe visible, " $\frac{1}{4}$ S".
 Tree also opened for "BT" scribe.
 18", now 19" D.Fir, N. 56* W. 11.9 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 1 W
 Office 1968 $\frac{1}{4}$ S 28
 S 33
 Reblzd. & Rescrbd: 23" D.Fir S. 30* W. 6.6 ft. mkd: $\frac{1}{4}$ S33 CS BT.

Section Corner to Sections 27 - 28 - 33 - 34. 125
 Found - G.L.O. Brass Cap, properly marked in 1922, out of ground.
 28", now 38" D. Fir, N. 81* E. 35.6 ft., shows good scar.
 14", now 16" Maple, S. 31* E. 31.7 ft., shows scar. *#161*
 30", now D. Fir Stump, N. 44* W. 20.5 ft. shows good scar.
 No trace of S. W. Bearing Tree.
 Reset Brass Cap at Section Corner, cap was out of ground.
 New BT's: 16" D.Fir N. 68* W. 17.3 ft. mkd: T31S R1W S28 CS BT.
 13" Hemlock S. 15* W. 51.0 ft. mkd: T31S R1W S33 CS BT.

$\frac{1}{4}$ Corner to Sections 27 and 28. 126
 Found - 10", now 14" Fir Corner Tree, shows 2 good faces. *#206*
 18", now 22" Fir Windfall, S. 15* E. 11.2 ft., shows good faces.
 22" Fir, now 22" Windfall, S. 65* W. 11.2 ft., shows scribing.
 Set - Brass Cap on S. Side of Corner Tree Mkd: County Surveyor's T31S R1W
 Office, 1968 $\frac{1}{4}$ S 28 | S 27
 New BT's: 6" D. Fir S. 30*W. 6.1 ft. mkd: $\frac{1}{4}$ S28 CS BT.
 10" W. Fir S. 5*E 35.6 ft. mkd: $\frac{1}{4}$ S27 CS BT.
 Note - This $\frac{1}{4}$ corner lies in a N. - E. cutting corner.

$\frac{1}{4}$ Corner to Sections 24 and 25. 127
 Found - No trace of Brass Cap, bladed out in old skid road.
 30" D.Fir, now stump, S. 15* W. 9.9 ft., shows good scar.
 22" D.Fir, now stump, N. 17* W. 8.6 ft., opened for scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R1 W
 Office 1968 $\frac{1}{4}$ S 24
 S 25
 New BT's: 10" D.Fir S. 88* W. 36.3 ft. mkd: $\frac{1}{4}$ S25 CS BT.
 9" D.Fir N. 24* E. 42.3 ft. mkd: $\frac{1}{4}$ S24 CS BT.