

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Township Corner: T31S S 1 $\frac{1}{4}$ S 31 T30S R1E 143
RLW S 6 T31S

Found - After deligent search, we find 3" I.P. & Brass Cap approx. Gov't
40 ft. down hillside, out of ground.
Reset - Brass Cap in Mound of Stone at Corner Point.
Found - Orig. 7", now 8" B.Oak, N.84°E. 39.6 ft., now 7' high snag,
We open & find scribing.
Orig. 16", now 17" Madrona, down & out of position, S.72°E. 22.4 ft.
Scribe visible on underside.
New BT: 8" D. Fir S.83 $\frac{1}{2}$ °W. 64.6 ft. mkd: T31S R1W S1 CS BT.
No other live trees or stumps close for Bearing Trees.
Set - 5/8" Iron Rod 20 ft. North & 5/8" I.Rod 25 ft. North of corner.
This corner lies on steep westerly slope approx. 635 ft. north of
the East $\frac{1}{4}$ corner to Section 1, T31-1W, see Ren. #140.

John M. Powell
Frank Jones & W. Penley
October, 1968
C. S. File No. 54/71

Section Corner to Sections 1 and 12 only, T31-1W. 144

Found - 5x12x8 Stone at section corner marked with notches.
30" D. Fir, now snag, N.40°W. 27.1 ft., shows good scar.
12", now 14" D.Fir, S.19°W. 21.1 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
Office 1 S 1 S 6 1
1968 W S 12 S 6 E
New BT's: 10" D.Fir N. 53° W. 59.0 ft. mkd: T31S R1W S1 CS BT.
14" D.Fir N. 22° E. 5.9 ft. mkd: T31S R1E S 6 CS BT.

10/16/68

North $\frac{1}{4}$ Corner to Section 6 only, T32-1W. 145

Set - Brass Cap Mkd: T 31 S, T 32 S, R 1 W MAY 2004 M 144-50
N $\frac{1}{4}$ S 6
1970 O.P.E. 4906
Mkd: 28" Cedar BT bears S. 6 $\frac{1}{2}$ ° W. 82.3 ft.
10" Doug. Fir BT. bears S. 85° W. 23.6 ft.
See Map for tie to Sec. Cor. to Sections 31 and 32, T31-1W. (RM 2-21)

FO. OK BY R. WITCHERLEY
MAY 2004 M 144-50

Bruce A. Shaner
Ump. Nat'l. Forest
Oct. 31, 1970 RM 2 - 21

North $\frac{1}{4}$ Corner to Section 1 only, T 32-2W. 146

Set - Brass Cap Mkd: T32S, R2W, W M
N $\frac{1}{4}$ S 1
1970 O.P.E. 4906
Mkd: 28" Doug. Fir BT. bears S. 66° W. 27.0 ft.
28" Doug. Fir BT. bears S. 40 $\frac{1}{2}$ °E. 25.2 ft.
This cor. bears N.89°50'E. 72.11 ft. from 36/31, T31S, R's. 2 & 1W.

MARCH 71

Sec. Cor. To Secs. 31 & 32, only, T.31-1W. 147

Found-Brass Cap, properly marked, U.S. G.L.O., See Ren. #9.
12" White Fir BT bears N.38°E. 51.5 ft.
48" Cedar BT, down, scribe not visible bears
N. 4° W. 16.0 ft.
Mkd: 26" D.Fir BT. bears N. 25° W. 89.0 ft.
10/31/70

1/4 Corner to Sections 20 and 29. 148

Found Stone Mound.
Set 2" x 18" galv. iron pipe with 3" Brass Cap in concrete & stamped:
T 31 S R 1 W
 $\frac{1}{4}$ S 20
S 29
Ore. Lic. 222
1972
Found stump hole with Oak sucker shoots N.52°W. 14.5 ft.
Found stump hole with Oak sucker shoots S.73°W. 11.9 ft.
16" P. Pine BT. bears N.17 $\frac{1}{4}$ °W. 40.0 ft. scribed 1/4 S20 RS222 B.T.
12" D.Fir BT. bears S.6 $\frac{1}{2}$ °E. 24.8 ft. scribed 1/4 S29 RS222 B.T.
8/28/72

J. A. Hoffbahr
For: Umpqua Nat'l. Forest
Aug. 8, 1972 Map M 42 - 70