

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

149

1/4 Corner to Sections 29 and 32.  
Set - 2"x30" Galv. Iron pipe with 3" Brass Cap Witness Corner Stamped:  
T 31 S R 1 W Witness Corner

1/4 Cor. S 29  
S 32

South 20 ft. to True Cor.

Ore. Lic. 222

1972

from which:

12" W.Fir bears S.24 3/4°W. 180.5 ft. scribed W.C. 1/4 S32 T31S R1W RS222 BT.

10" D.Fir bears N.36 1/2°E. 81.4 ft. scribed W.C. 1/4 S29 T31S R1W RS 222 BT.

8/28/72

150

Section Corner to Sections 28 - 29 - 32 - 33.

Set - 2"x30" Galv. Iron pipe with 3" Brass Cap stamped:

T 31 S R 1 W

S 29 | S 28

S 32 | S 33

Ore.Lic.222

1972

from which:

15" W.Fir bears N.41 1/2°E. 27.9 ft. scribed T31S R1W S28 RS222 BT.

8" P.Pine bears S.50°E. 79.4 ft. scribed T31S R1W S33 RS 222 BT.

12" P.Pine bears S.16 1/2°W. 45.5 ft. scribed T31S R1W S32 RS 222 BT.

8" D.Fir bears N.55 1/4°W. 28.3 ft. scribed T31S R1W S29 RS 222 BT.

8/28/72

151

Center 1/4 Corner Section 29.

Set - 2"x30" Galv. Iron pipe with 3" Brass Cap stamped:

T 31 S R 1 W

C 1/4 S29

Ore.Lic. 222

1972

from which:

12" D.Fir bears S.75 1/4°W. 6.9 ft. scribed C 1/4 S29 RS222 BT.

12" D.Fir bears N.57°E. 20.5 ft. scribed C 1/4 S29 RS222 BT.

8/28/72

152

Center of Section 30

Set - 2" Iron Pipe with 3" Brass Cap stamped:

T 31 S R 1 W

C 1/4 S 30

PE 2128

From Which bears:

A 14" D.Fir N.49 1/2°W. 22.7 ft. scribed C 1/4 S30 BT PE 2128

A 14" D.Fir S.10°W. 63.4 ft. scribed C 1/4 S30 BT PE 2128

10/72

RE-RENEWED, SEE CORNER NO. #197

1/4 Corner between Sections 17 and 20.

Corner set by proportionate measurement.

Set - 2 1/2" Brass Cap on 1" Galv. iron pipe stamped as shown:

T 31 S R 1 W

1/4 Cor S 17  
S 20

Ore Lic 222

1972

from which bears:

9" D. Fir B. T. bears N. 5 1/2°E. 20.7 ft. scribed 1/4 S17

RS 222 BT.

11"D. Fir B.T. bears S.3 1/2°W. 7.8 ft. scribed 1/4 S20 RS222 BT.

10/9/72

154

Center 1/4 Section Corner Section 17.

Set-2 1/2" x 30" Galv. iron pipe with 3" Brass Cap stamped as shown:

T 31 S R 1 W

Sec 17

C 1/4

Ore.Lic.222

1972

from which bears:

12"D.Fir BT bears S.70 1/2°E. 26.0 ft. scribed C1/4 S17 RS222 BT.

13"B.Oak BT bears S.54°W. 17.5 ft. scribed C1/4 S17 RS222 BT.

Umpqua National Forest  
By: J. A. Hoffbuhr  
Map File M 42 - 70

Umpqua Nat'l Forest  
By: Wm. S. Barnes  
Map File M 46 - 75

Umpqua National Forest  
By: Jack A. Hoffbuhr  
Map File M 42 - 75