

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 T. S. R. 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

161

Don E. Garrett
For: U.S. Forest Serv.
August, 1975
58 - 7

Section corner for Secs. 28, 27, 33 and 34.
Found - 1922 USGLO brass cap properly marked.
16" Maple, bears S.31°E., 31.7 ft. (9.662 meters) Ren. #125
16" Fir, bears N.68°W., 17.3 ft. (5.273 meters)
13" Hemlock, bears S.15°W., 51.0 ft. (15.545 meters)
NE tree down.
New BT - 14" Fir, bears N.31°E., 42.0 ft. (12.802 meters). Scribed
S27, T31S, R1W, BT.

8/75

Section corner for Secs. 8, 9, 17 and 16. 162

Found - 1923 U.S.G.L.O. Brass cap properly stamped.
Orig. 18" now 24" Oak snag, bears S.12°W., 17.8 ft. Tree
has well healed blaze.
A 12" now 16" D.Fir, bears N.34°W., 29.4 ft. (Rec. N.27°W.) #168
to root crown. Tree leaning to the Northwest, has good blaze
scribed "T31S R1W S8 CS BT" REN. #30
All other bearing trees are uprooted or gone.
New BT's - A 12" D. Fir, bears N.11°E., 119.7 ft. Tree double blazed and
scribed "T31S R1W S9 CS BT"
A 3" Pine, bears S.22°W., 74.4 ft. Scribed "X" 2 inches high and
3 inches wide. (Approximately)
Set witness sign and post beside brass cap.
There are no trees suitable for marking in the southeast quadrant.

9/1/76

Closing corner for SEcs. 15 and 22. 163

Found - 1923 GLO brass cap properly stamped, pipe loose in ground &
leaning badly.
3/4" Iron rod in top of orig. 34" BT stump bears N.35°E., 22.7 ft.
Stump has well healed scar. Ren. #96
3/4" I.R. in top of orig. 38" BT stump bears S.55°E., 4.1 ft.
Stump has a well healed scar.
Set - Using the 3/4" I. Rods set by Powell for reference, I re-set the
brass cap & placed a mound of stone around the monument.
No new accessories available.

12/8/77

Section Corner for Secs. 5, 6, 7 and 8. 164

Found - 1966 County Surveyors brass cap on a 1" I.P., properly marked.
23" D.Fir stump N.70°W., 27.7 ft. scribe visible. Ren. #15
41" D.Fir stump S.71°W., 40.4 ft. good scar.
Rotted stump, S.59°E., 17.1 ft. no scribe visible.
14" Maple, S.17°W., 61.7 ft. scribe visible
12" Hemlock, S.83°E., 105.9 ft. scribe visible.
8" fallen Hemlock, N.03°E., 106.2 ft. scribe visible.
10" Maple snag, N.84°W., 67.6 ft. scribe visible.
Scribed: 12" Hemlock, N.31°11'E., 187.2 ft. "T31S R1W S5 BT".
26" D.Fir, N.09°34'W., 155.5 ft. "T31S R1W S6 BT".

1/4 Corner for Secs. 7 and 8. 165

Found - Burned snag, N.34°42'E., 39.0 ft. (old BT)
30" Pond. Pine, S.43°53'E., 46.7 ft. scribe visible.
15" D.Fir, S.55°28'W., 21.5 ft. good scar.
18" D.Fir, N.87°33'W., 32.9 ft. good scar.
12" B.Oak, N.07°09'W., 71.3 ft. good scar.
Set - 2" x 30" steel pipe with s 1/2" Brass cap marked: T31S R1W
1/4 S7 S8 PLS 866 1977, alongside a 1 1/2" steel shaft found
per C.S. 51/142. Ren. #7

11/77 166

1/4 Corner for Secs. 5 and 8.

Set - Brass cap marked: T31S R1W 1/4 S5 S8 PLS 866 1977.
Scribed - 14" D. Fir, N.66°19'W., 91.8 ft. "1/4 S5 BT". 210
36" D.Fir, N.29°19'E., 97.9 ft. "1/4 S5 BT".

(Added 1/27/78) -- 6" D. Fir S.32°55'E., 66.4 ft. scribed "1/4 S8 BT". 11/77

Center 1/4 Corner for Sec. 8 167

Set - Brass cap marked: T.31S R1W C 1/4 S8 PLS 866 1977.
Scribed: 12" D.Fir, N.82°38'W., 36.2 ft. "C 1/4 S8 BT".
8" D.Fir, S.04°15'E., 13.9 ft. "C 1/4 S8 BT".

L.E. Monrean
P. Earle
Doug. Co. Surveyors Office
Sept. 1, 1976
C.S. 59/24

Dennis Gaylord, U.S. F.S.
Deputy, Doug. Co.
Surveyors Office
Bland Simshauser
Sec. 8, 1977
C.S. 59/42

William Ruppert (Umpqua Research Company)
For: U. S. Forest Service
November, 1977
M 65 - 50