

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

168

Section Corner for Secs. 8, 9, 17 and 16.
Found - 1923 GLO Brass cap, properly marked, on a 1" I.P.
12" D. Fir, N.09°46'E., 119.8 ft. good face. Ren. # 162
23" Oak snag, S.10°02'W., 18.5 ft.
18" D. Fir, N.36°13'W., 29.9 ft. Good face. Ren. #30.
Set - 6 ft. steel post, S.19°15'E., 60.4 ft.
6 ft. steel post, S.21°W., 67.7 ft.

William Ruppert
For: U.S. Forest
Service
November, 1977
M 65 - 50

11/77

169

1/4 Corner for Secs. 6 and 7.
Bronze disk set in June, 1967 per M 34 - 23. See Ren. #34
Bearing trees changed Jan. 4, 1978 per G. Baughman as follows:
21" D. Fir bears N.23°45'E., 22.5 ft. scribed 1/4 Cor.
S6 & 7 BT.
17" D. Fir bears S.45°15'E., 19.3 ft. scribed 1/4 Cor.
S 6 & 7 BT.

See M 34 - 23
County Surveyor
Map files.

FD. 10/7/80
L. HEDSTROM
U.S.F.S.
C.S. 6/1/77

2002-03
- See BLM
Resurvey - VOL 54 pg 20786 - 1/4/78
VOL 54 pg 20788-9

170

Center 1/4 Corner for Section 7.
Set - Brass cap stamped: T31S R1W C 1/4 S7 PLS 866 1977.
BT's - 24" Cedar bears S.85°00'W., 94.0 ft. scribed "C 1/4 S7 BT"
12" Fir bears S.01°45'E., 43.4 ft. scribed "C 1/4 S7 BT"
Note: All monuments set on survey are set on 2"x30" Galv. I.P. with
2 1/2" Brass cap. All BT dimensions indicate the diameter
of the tree at scribed area. All BT distances & bearing are
from the center of the monument to the center of the tree.
Scribed BT's have a brass washer stamped LS 866 nailed in
lower blaze.

William Rupper
For: U.S. Forest
Service
December 1977
M 65 - 60

12/77

171

Center 1/4 Corner for Section 19.
Set - A 2" Pipe with 3" brass cap stamped: T31S R1W C 1/4 S19
PLS 944 1978"
From which:
A 8" Cedar bears N.66°W., 63.0 ft. scribed C 1/4 S19 BT
A 14" Fir bears N.22°E., 19.6 ft. scribed C 1/4 S19 BT.

Loyd R. Moffit
For: Umpqua National
Forest
June 1978
M 70 - 23

RE-RENEWED, SEE CORNER NO. #202

6/78

172

Section corner for Secs. 16, 17, 20 and 21
Found - 1968 County Surveyors Brass cap. Ren. #89
12" Yew bears S.88°E., 1.2 ft.
15" Maple bears N.5°E., 68.5 ft.
18" D. Fir snag (5' high) bears S.48°30'W., 40.0 ft.
22" D. Fir stump bears N.54°W., 36.2 ft.
New BT's-36" D. Fir bears S.6°W., 43.0 ft. scribed T31S R1W S20 BT.
20" D. Fir bears N.85°W., 65.3 ft. scribed T31S R1W S17 BT.

7/78

173

1/4 Corner for Secs. 16 and 21.
Found - Orig. 36" D. Fir snag bears N.30°E., 9.2 ft. (Orig. 24")
Set - 2" x 30" I.P. with brass cap stamped T31S R1W 1/4 S16 S21
OLS 536 1978.
New BT's-21" D. Fir bears S.65°E., 20.2 ft. scribed 1/4 S21 BT.
13" D. Fir bears N.18°W., 46.8 ft. scribed 1/4 S16 BT.

7/78

174

Center 1/4 Corner for Sec. 21.
Set - 2" x 30" I.P. with brass cap stamped T31S R1W WM C1/4 C $\frac{C}{C}$
1978 OLS 536.
BT's - 16" D. Fir bears S.45°W., 9.4 ft. scribed C 1/4 S21 BT.
8" D. Fir bears N.34°E., 8.9 ft. scribed C 1/4 S21 BT.

L-77

Glenn S. Baughman
For: U.S. Forest Service
July 1978
M 70 - 28