

Douglas County Surveyor's Record of
Government Corners Renewed

T 31

T. S.

R 1

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97101

Glenn Baughman
For: U.S. Forest
Serv.
April 1979
C.S. 58/176

North 1/16 corner to Sec. 6, T131-1 and Sec. 1, T31-2. 175
Found - 2" Iron pipe with Baughman 1967 brass cap . Ren. #36
18" Douglas Fir, S.22°W., 12.0 ft.
36" Pine stump, N.1 1/2°W., 46.5 ft.
Marked: 8" Douglas Fir, N.9°W., 19.2 ft. "N. 1/16 S - 1" bearing tree
and fastened brass washer stamped Land Surveyor 536 in lower
part of blaze.

April, 1979

Section corner for Secs. 5 and 6; and Sec. 31, 32 of T.30-1 176
Found - A 1" iron pipe projecting 16" above the ground with a 2 1/2" brass
cap marked: County Surveyors Office Ren. #13

From which:

A 11" D. fir with partially healed blaze, bears S.35°W., 9.2 ft.
A 28" D. fir, wind thrown stump, bears N.20°W., 15.2 ft.
A 24" D. fir stump, bears N.2°E., 21.8 ft.
A 12" D. fir with healed blaze, bears N.80°E., 40.8 ft.
A 18" D. fir with healed blaze, bears S.52°E., 51.3 ft.
A 26" D. fir with scribe marks visible on a partially healed blaze,
bears S.72°W., 21.2 ft.
New BT - A 16" W. fir bears N.56°W., 140.1 ft., I marked "T30S R1W S31 BT"
on a double blaze and nailed a brass washer stamped "LS 536"
into lower blaze.

7/79

Angle Point for 1/4 corner for Secs. 30 and 31 177
Found - 40" D. Fir, I opened and found scribe marks visible on a burnt face,
From which:

a root hole with 4" - 8" Laurels growing out bears S.40°E., 13.2 ft.
a root hole with 4" - 8" Laurels growing out bears N.35°W., 23.8 ft.
Set - A 2" x 30" iron pipe, 18" in the ground in a 3 foot diameter mound
of stone with a 3" brass cap marked: T31S R1W AP S30 S31
1979 PLS 536
Monument set 2.50 feet east of center of corner tree, from which brass cap:
A 6" D. fir bears N.64°E., 34.4 ft. marked: "AP S30 BT" on a
double blaze and nailed a brass washer stamped "LS 536" into
lower blaze.
A 10" D. Fir bears S.4°E., 102.7 ft., marked: "AP S31 BT" on a
double blaze and nailed a brass washer stamped "LS 536" into
lower blaze.

7/79

1/4 Corner for Secs. 9 and 16 178
Found - 1" Iron pipe with a 2 1/2" brass cap set 8" above the ground and mar
marked: 1/4 S9 S16 1923 from which: Ren. #84
a 10" Yew, down and burnt, bears S.81°W., 23.8 ft.
A 13" D. Fir snag bears N.18°W., 15.2 ft.
a 42" D. fir stump bears N.65°E., 44.0 ft.
a 10" Hemlock bears S.5°W., 95.0 ft.
New BT - 14" D. fir bears N.32 1/2°W., 114.6 ft. I marked "1/4 S9 BT" on a
double blaze and nailed a brass washer stamped "LS 536" into a
lower blaze.

7/79

Glenn Baughman
For: U.S. Forest Service
July 1979
C.S. 58/176

Center 1/4 Corner for Sec. 32 179

Set - 2" x 30" Iron pipe with 2 1/2" brass cap.
BT's - 10" W. Oak bears N.23°W., 21.8 ft.
12" W. Oak bears N.85°13'E. 73.5 ft.

South 1/4 Corner Sec. 32 only, T. 31 S. R. 1 W. 180
Found - Brass cap at corner. Ren. #10
D. Fir stump 12" dia. bears N.48°01'W, 57.3 ft. (Rec. N.48°W.
58.0 ft.)
W. Fir 13" dia. bears N.79°03'E., 54.0 ft. (Rec. N.78°E.,
54.9 ft.)
Stump hole with dead and down W. Fir bears N.8°47'W., 16.5 ft.
(Rec. N.10°W., 16.5 ft.)

(continued on next page)