Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Kurt Weaver
For: U.S. Forest Service
Dec. 1979
M 81 - 58

South 1/4 Corner Sec. 32, T. 31 S. R. 1 W. continued - **180**

New BT's - 6" diameter Yew Wood bears N.52°05'W., 47.1 ft.
7" diameter D. Fir bears N.57°45'E., 44.6 ft.
13" diameter W. Fir bears N.16°22'W., 62.5 ft.
Note - This corner lies 165 ft. east of the C.C. of Sections 5 and 6, of T. 32 S. R. 1 W.

Kurt Weaver
For: U.S. Forest Service
Dec. 1979
M 81 - 59

1/4 Corner to Sections 29 and 28 **181**
Found - Brass Cap at corner. Ren. #71 ~~#208~~
A P. Pine 24" diameter bears S.89°06'E., 20.5 ft.
(Rec. S.88 1/2°E., 20.2 ft.)
New BT - A W. Oak 6" diameter bears N.25°04'W., 51.8 ft.
Note - B.T.'s to the S.W. were removed by road construction.

RE-RENEWED SEE CORNER NO. #208

FD. BK 12/92 BY KAISER M116-30

Kurt Weaver LS #1679
For: U.S. Forest Service
January 1980
M 82 - 75 A&B
CS 58/216N

S.W. Sec. Corner to Sec. 33, T. 31 S. R. 1 W. REN. #8 **182**
Found - W. Fir Stump 26" dia. bears N.84°56'W., 38.0 ft.
(Rec. N.84°W., 37.6 ft.)
D. Fir Stump 24" dia. bears N.34°48'E., 28.7 ft.
(Rec. N.30°E., 27.8 ft.)
D. Fir 11" dia. bears N.40°30'W., 21.1 ft.
(Rec. N.41°W., 20.7 ft.)
W. Fir 16" dia. bears S.87°21'W., 39.7 ft.
(Rec. S.86°W. 39.6 ft.)
D. Fir 10" dia. bears S.40°06'W. 15.2 ft.
(Rec. S.39°W., 15.5 ft.)
Set - 2" x 30" Galv. Iron Pipe with 2 1/2" Brass Cap
New BT - D. Fir 11" dia. bears N.27°30'E., 16.6 ft.

Center 1/4 Corner for Section 33, T. 31 S. R. 1 W. **183**

Set - 2" x 30" Galv. Iron Pipe with 2 1/2" Brass Cap.
BT's - D. Fir 11" dia. bears S.76°52'E., 13.0 ft.
D. Fir 13" dia. bears S.15°08'W., 35.5 ft.
Note - 5/8" Iron Pin bears S.65°42'25"W. 45.90 ft. from corner.

Kurt Weaver #1679
For: U.S. Forest Service
Feb. 1980
C.S. 58/176

North 1/4 Corner for Sec. 5 only of T.32-1. **184**
Found - the 3/4" G.I.P. as set by Lovejoy,
from which-
A 8" W. Fir bears S.39°03'W., 18.0 ft. (Rec.S.38°W., 16.6 ft.)
A 8" G. Fir bears S.31°00'E., 19.0 ft. (Rec. W. Fir S.28°E., 19.4 ft.) Ren. #51
A 2" G.I.P. with a 2 1/2" B.C. at the section corner for Secs. 32 and 33, T.31S., R.1W., bears S.89°52'48"E., 158.37 ft.
Set - I set a 2" x 30" G.I.P. with a 2 1/2" brass cap over found pipe exposed 16" in a mound of stone and marked:
T31S R1W 1/4——— T32S R1W LS 1679 1980
S5

Kurt Weaver #1679
For: U.S. Forest Service
March 1980
M 83 - 4 ABCD

Center 1/4 corner to Sec. 34. **185**
Set- 2" x 30" galvanized iron pipe with 2 1/2" brass cap.
BT's- 9" dia. D. Fir bears S.72°16'E., 28.0 ft.
14"dia. D. Fir bears S.9°45'W., 25.3 ft.

Bruce A. Shaner
For: U.S. Forest Service
March 1980
RM 3 - 29

Section corner to Sections 34 and 35, T.30S. R.1W. REN. #48 **186**
Fd- G.L.O. brass cap at corner properly marked in 1923.
14" Original Oak BT snag bears N.49°E., 34.5 ft.
(Record N.45°E., 33.7 ft.) Scribes visable.
34" Original Douglas Fir BT bears S.40°E., 4.0 ft.
with face visable.
14" Douglas Fir scribed by Douglas County Surveyor's office bears N.2 1/2°W., 15.6 ft.
New BT's- 20" Douglas Fir bears N.76°E., 35.5 ft. and scribed "T30S R1W S35 BT".

CONTINUED