

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 31 S T. S. R 1 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gerald V. Nygren
LS #1035
For: Umpqua Nat'l
Forest
1980
9 - 53
58/158N

Leonard Herzstein, Deputy, Doug. Co. Surveyors Office
U.S. Forest Service
Witnesses - Art Arciniega; Joe Richey
October, 1980
C.S. 61/11

187

1/4 Corner to Sec. 2, T.32S. R.1W. only
Set - 2 1/2" x 30" Alum. pipe with alum. cap mkd. "T32S R1W WM
1/4 S2 1980 PLS 1035", exposed 20" above ground in large
mound of stone.
BT's - 60" D. Fir bears S.36°E., 31.1 ft.
26" D. Fir bears S.24°W., 13.0 ft.
Bearing trees have brass washer stamped "RS 1035" nailed to lower blaze.

188

Center West 1/16 Corner Section 6-
Found - 2" I.P. with brass cap properly marked, set by Baughman in 1967,
facing east projecting 20" above ground. leaning Northerly. #41
7" I. Cedar, N.62°18'E., 15.4 ft. (Rec. 15.1 ft.) with scribe
marks visible on partly healed blaze, facing North.
7" I. Cedar, S.70°42'E., 22.6 ft. (Rec. 22.7 ft.) with scribe
marks "CW 1/16 S6 BT" visible on partly healed blaze with blaze
Reset - Reset I.P. facing North, projecting 6" above ground, firmly set.
10/22/80

189

S 1/16 Corner for Sec. 6; and Sec. 1 of T.31-2
Found - 2" I.P. with brass cap properly marked, facing east and leaning
easterly, firmly set, projecting 20" above ground set by
Baughman in 1967. Ren. #35
W. Oak, 10", bears S.9°-4'W., 35.1 ft. (Rec. 32.3 ft.) with
healed blaze.
W. Oak clump with 2 trunks, the easterly trunk, 8", N.24°14'W.,
32.3 ft. (Rec. 35.3 ft.) with healed blaze.
Reset - Reset I.P. facing North, firmly set, projecting 8" above 2 ft.
diam. mound of stone.

10/23/80

190

Center North 1/16 Section 6.
Found - 2 1/2" D. I.P. projecting 18" above ground loosely set with
properly marked brass cap set by Baughman in 1967. Ren. #38
3" Willow snag, S.15°E., 50.5 ft. (Rec. S.17°01'E) with scribe
marks "CN 1/16 S6 BT" visible on partly healed blaze.
4" Willow, S.34°30'W., 68.7ft. (Rec. S.32°45'W., 89.5 ft.) with
scribe marks "CN 1/16 S6 BT" visible on partly healed blaze.
5/8" Rebar, projecting 1" above ground, N.54°01'W., 27.4 ft.
(M 81-28)
Reset- Reset I.P. projecting 12" above 3 ft. diam. mound of stone
firmly set.
New BT - 6" D. Fir, S.9°E., 59.3 ft. scribed "CN 1/16 S6 CS BT".
10/9/80

191

1/4 Corner for Sec. 7; and Sec. 12 of T.31-2
Found - 9" Diam. Maple marked by Boyer in 1950 as a corner tree by
proportionate measurement, with healed blazes on east and west
sides with an 8" alum. nail in center of base of tree. Ren. #3
now bears S.6°E., 7.5 ft. from orig. corner position as det-
ermined by record bearing & distance from orig. BTs.
A 1 1/2" I.P. projecting 14" above ground firmly set alongside
corner tree, set in 1966 by Powell, with brass cap properly
marked, now bears S.10°E., 7.9 ft. I REMOVE marks from brass cap.
Ren. #24
Orig. D. Fir, 36", N.57°E., 20.5 ft. with scribe mark "S" on
bark blaze.
Orig. D. Fir, 30", N.12°W., 23.1 ft. with no marks visible. (both
trees of sufficent age by growth ring count)
D. Fir, 12" now N.81 3/4°E., 11.3 ft. (Rec. N.48 1/2°E., 15.0 ft.
to corner tree) with healed blaze facing N.48 1/2°E. Ren. #3
9" Maple, now N.85°W., 7.4 ft. (Rec. N.51 1/2°W., 15.0 ft. to
corner tree) with healed blaze facing N.51 1/2°W.
22" D. Fir now N.0 1/4°E., 18.6 ft. (Rec. N.5°W., 26.7 ft. to cor-
ner tree) with healed double blaze. Ren. #24
Set - At record bearing and distance from orig. BTs, SET I.P. 2" diam.
30" long, 24" in ground within a 2 ft. mound of stone with
brass cap marked "Douglas County Surveyor T31S R2W S12 1/4
S7 R1W 1980".
10/20/80