

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 31                      T. S.                      R 1                      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

192

Bruce Shaner  
For: U.S. Forest  
Service  
Oct. 1980  
RM 3 - 36

1/4 Corner for Section 4 only - T.32-1  
Set - Brass cap marked T31S R1W. W.M. R.L.S. 430 1980  
BTs- 8" D. Fir BT, I scribed "1/4 S4 BT" bears S.86°W., 8.7 ft.  
8" W. Fir BT, I scribed "1/4 S4 BT" bears S.11°E., 20.7 ft.

10/80

Bruce Shaner  
For: U.S. Forest Serv.  
October 1980  
RM 3 - 37  
FO. OK BY R. WYTCHELEY  
MAY 2004 - M 144-50

Closing Corner for Sections 5 and 6 of T.32-1 only.  
Found - 1964 County Brass cap. Ren. #11  
8" Oak, bears N, 55.6 ft. Scribes visible  
8" Maple, dead, scribes visible, bears S.1°E., 106.9 ft.  
(Rec. S.2°W)

193

New BT's - 12" D. Fir, I scribed "T32S R1W S5 CC BT" bears S.19°E., 138.0 ft  
8" D. Fir, I scribed "T32S R1W S6 CC BT" bears S.34°W., 143.2 ft

10/80

Kurt Weaver  
For: U.S. Forest Serv.  
Nov. 9, 1979  
M 81 - 28  
C.S. 58/216

1/4 Corner for 5 and 6.  
Found - Douglas County brass cap. 1966. Ren. #17  
D + D D. Fir, 9" bears N.44°33'E., 13.5 ft. (Rec. N.50°E., 13.0')  
(Rec. per Ren. #17 is N.48°E.)  
D + D D. Fir, 15" bears N.37°58'W., 12.4 ft. (Rec. N.40°W., 13.2')  
(Rec. per Ren. #17 N.43°W.)  
P. Pine stump, 22" bears S.82°39'W., 10.5 ft. (Rec. S.79°W., 9.0')

194

New BT's- D. Fir 6" bears N.77°34'W., 20.4 ft.  
D. Fir 8" bears N.39°35'E., 17.2 ft.

11/79

NW 1/16 corner for Sec. 29.

Found - 2" I.P., firmly set, projecting 4" above ground, with a  
Brass Cap marked: T 31 S R 1 W NW 1/16 S29 ORE LIC 222  
1972, set by J.A. Hoffbuhr in 1972. M 42 - 70.  
14" D. Fir stump bears N.46 1/4°E., 45.5-ft., with scribe mark  
visible on partly healed double blaze.  
24" D. Fir bears N.57°W., 45.1-ft. with scribe marks visible  
on partly healed double blaze.

195

New BT - 9" I. Cedar bears S.14 1/2°E., 32.3-ft., scribed NW 1/16  
S29 CS BT on double blaze.

6/18/81

NE 1/16 corner of Sec. 29.

Found - 2" I.P. set in concrete, projecting 6", with Brass Cap  
marked COR T31S R1W NE 1/16 S29 ORE LIC 222 1972,  
set by J.A. Hoffbuhr in 1972. M 42 - 70.  
15" D. Fir snag bears S.52 3/4°W., 48.1-ft., with a  
partly healed blaze.  
19" D. Fir snag bears N.40 1/4°W., 26.5-ft., with a  
partly healed blaze.

196

New BT's- 15" P. Pine bears S.66°W., 52.9-ft., scribed :  
NE 1/16 S29 CS BT, on a double blaze.  
15" P. Pine bears N 66 1/2 °W., 63.2-ft., scribed:  
NE 1/16 S29 CS BT, on a double blaze.

\* NOTE - Corner lies 20-ft. North of Centerline of USFS Rd.# 3131.  
6/17/81

Center 1/4 corner of Sec. 30.

Found - 2" I.P. with Brass Cap marked T31S R1W C 1/4 S30 1972 PE 2128  
set by William Barnes in 1972, firmly set, projecting 6"  
above a 2' diameter mound of stone. M 42 - 74.  
14" D. Fir stump bears S.10°W., 63.4-ft., with scribe marks  
visible on partly healed double blaze.  
14" D. Fir bears N.49 1/2°W., 22.7-ft., with scribe marks  
visible on partly healed double blaze.

197

New BT - 11" W. Fir bears N.24 3/4 °E., 27.2-ft., scribed:  
C 1/4 S30 CS BT on a double blaze.

6/18/81

Leonard Herzstein  
U.S. Forest Service  
Deputy, Douglas County Surveyor  
Witnesses: Jim Landrum  
Tom Wolford  
June, 1981  
C.S. 61 / 27 Compass Decl.=19 1/4 °

REN. # 152