

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORR. 21881

201

Section corner for Secs. 7 and 18; and Secs. 12 & 13 of T31-2
Found - 8" W. Oak corner tree with 4 healed blazes and a 4" x 6" x 13" sandstone projecting 1" above ground on north side of corner tree with "+" on top, both marked by Ben Irving in 1931. See Ren. #12 in T31-2. Corner tree is actual corner position per Irving in 1931.

1" dia. iron pipe 6" long, 12" below ground, north of corner tree, which is the remains of I.P. and brass cap set by John Powell, County Surveyors Office in 1966. Ren. #19

Found remaining original bearing trees:

A roothole, bears S.07°W., 72.6 ft.

A 9" W. oak snag, N.37°W., 12.7 ft. (Rec. N.12°W., 10.6 ft. with rotted healed blaze visible on inside of tree.

And found BTs marked by Irving in 1931:

A 7" W. Oak stump, N.28°E., 12.2 ft. (Rec. 11.9 ft.) with healed blaze.

A 7" W. Oak, S.42°W., 8.0 ft. (Rec. 8.6 ft.) with healed double blaze.

And found BTs marked by Jim Landrum, LS 2024 in 1983: Ren. #199

A 9" D. fir, N.43°E., 64.2 ft. with scribe marks "T31S R1W S7 BT" visible on double blaze.

A 7" D. fir, S.63°E., 78.2 ft. with scribe marks "T31S R1W S18 BT" visible on single blaze.

A 7" W. Oak, N.89°W., 9.4 ft. with scribe marks "T31S R2W S12 BT" visible on single blaze.

Set - A reference monument: a 2 1/4" dia. iron pipe. 32" long, set 28" in ground with brass cap mkd. T31S RM R2W S12 S13 S7 S18 R1W LS 1181 1984. A 2 ft. dia. mound of stone is flush to top of brass cap. Ref. monument is north, 0.6 ft. from corner position. Remains of previous I.P. placed inside of new I.P. Buried stone alongside.

New Accessory:

Set 6 ft. steel fence post east, 2.1 ft. with USFS sign #54-4. Corner is S.10°W., 50 ft. from junction of USFS Roads #3131-860 and -865.

202

Center 1/4 Corner for Section 19

Found - 2 1/2" outside dia. I.P. firmly set, projecting 2" above a 3 ft. dia. mound of stone, with brass cap, properly marked, set by Loyd Moffit, LS. 944 in 1978. Ren. #171

14" D. fir, N.22°E., 19.2 ft. (rec. 19.6 ft.) with scribe marks "C 1/4 S19 BT" visible on partially healed double blaze.

8" I. Cedar, N.66°W., 63.0 ft. with scribe marks "C 1/4 S19 BT" visible on partially healed double blaze with brass washer stamped "LS 944" nailed flush to lower blaze. Tree has been cut off 12 ft. above the ground by the Power company so it wouldn't interfere with the power lines.

A steel fence post East, 3.8 ft. with USFS signs #54-2 and 54-9 attached as a guard post.

New BT - I mark a new BT outside power line clearing to replace NW BT:
A 16" P. Pine, S.73 1/2°E., 32.0 ft. scribed "C 1/4 S19 BT" on a single blaze with a brass washer stamped "LS 1181" nailed flush to base of blaze.

Corner is 900 ft. + , N.15°E. from the junction of USFS Rd. #1613-100 a State Highway 227, and 17 ft. north of east-west barbwire fence under high tension power lines.

fd OK, R. Brown, 1994-0036, 2/94

12/10/84

203

Section corner for Sections 5 and 4; and Secs. 32 and 33 of T.30-1

Found - A 2 1/2" brass cap on a 1 1/2" iron pipe. Ren. #44

A 32" fir bears N.42°E., 10.8 ft. scar visible.

A 20" madrone bears S.74°E., 10.6 ft. scar visible.

A 17" pine bears S.01°E., 16.9 ft. scribe visible. (no record)

A fir stump bears S.88°W., 9.7 ft. scar visible.

A 15" fir bears N.56°W., 36.5 ft. scribe visible.

New BT - An 8" fir which bears S.43°W., 35.6 ft. marked T31S R1W S5 BT.

Maurice E. Farr, L.S. 1181.
U.S. Forest Service
Leonard Herzstein; Randy Lopez Witnesses
June 5, 1984
C.S. 62/15

Maurice E. Farr
LS #1181
Leonard Herzstein
Randy Lopez
For: U.S.F.S.
Dec. 10, 1984
C.S. 62/15

Loyd R. Moffit
L.S. #944
For: U.S. Forest
Service
C.S. 63/8