

Douglas County Surveyor's Record of
Government Corners Renewed

T 31

T. S.

R 1

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 91881

204

1/4 Corner for Sections 9 and 16

- Found - 3/4" iron pipe with 2 1/2" brass cap. (1923 GLO)
- 36" fir stump bears N.65°E., 44.0 ft. scar visible. Ren. #84
- 9" hemlock bears S.05°W., 95.0 ft. scribe visible.
- Cedar snag (down) bears S.81°W., 23.8 ft. Has open face. (Rec. Yew)
- 14" fir (dead) bears N.32°30'W., 114.6 ft. scribe visible. #178
- New BT - I marked a 3" fir BT which bears N.46°W., 5.5 ft. scribed "X"
- BT. Nailed brass washer stamped L.S. 944 to BT scribe.

205

Section corner for sections 16 and 21 only.

- Found - A 2 1/2" brass cap on a 1 1/4" iron pipe in small rock mound. (1922 GLO)
- 32" fir bears N.40°E., 27.6 ft. scribe visible. Ren. #81
- 16" fir stump with 5/8" rebar in top bears S.05°W., 29.6 ft. scar visible.
- 40" fir stump with 5/8" rebar in top bears N.45°W., 2.6 ft. scar visible.

- Note: No live trees for BTs available in N.W. quad.
- New BT - Since there are no live trees available in the northwest quadrant, I marked a 8" Pine BT which bears S.24°W., 7.1 ft. from the corner, scribed T31S R1W S21 BT. Nailed L.S. 944 brass washer to BT scribe.

206

1/4 Corner for Sections 27 and 28.

- Found - 16" fir as corner tree.
- 2 1/2" Doug. County Surveyors Office brass cap on 1" iron pipe exposed 12" set on south side of tree. Ren. #126
- 14" fir bears S.05°E., 36.5 ft. scar visible.
- 7" fir (dead & down) bears S.30°W., 6.1 ft. scar visible.
- New BT - I marked a 9" fir BT which bears S.16°30'W., 29.4 ft. from the corner, scribed 1/4 S28 BT. Nailed L.S. 944 brass washer to BT scribe.

207

Section Corner for Secs. 6 and 5; and Secs. 31 and 32 of T.30-1

- Found - A 1966 County Surveyors 2 1/2" brass cap on a 1" iron pipe. Ren.#13
- 24" rotted fir stump which bears N.02°E., 21.8 ft.
- 12" Fir which bears N.80°E., 40.8 ft. Scar visible.
- 18" Dead Fir which bears S.52°E., 51.3 ft. Scribe visible.
- 14" Fir which bears S.35°W., 9.2 ft. Scar visible.
- 20" dead Fir which bears S.72°W., 21.2 ft. Scribe visible.
- 16" Fir which bears N.56°W., 140.1 ft. Scribe visible. Ren.#176
- 27" uprooted Fir which bears N.20°W., 15.2 ft.
- 24" Fir which bears N.89°W., 23.0 ft. Scar visible. (origin unknown).
- New BT - 7" Cedar which bears S.40°E., 62.8 ft. from the corner, scribed T31S R1W S5 BT, with L.S. Washer #944 nailed to BT scribe. 12/86

208

1/4 Corner for Sections 28 and 29

- Found - A 1 1/4" Iron pipe by Powell in 1986, firmly set, projecting 14" above ground in a mound of stone with a 2 1/2" brass cap properly marked. Ren. No. 71
- A 21" S.Pine snag bears S.89°E., 20.5 ft. with scribe marks visible
- A 7" W.Oak bears N.25°W., 51.8 ft. with scribe marks visible. Ren. No. 181
- Set - I built a 36" dia. x 12" high mound of stone around monument.
- New BTs - A 20" P.Pine bears S.21 1/2°W., 37.6 ft. scribed "1/4 S29 BT"
- A 11" W.Oak bears S.26°E., 10.6 ft. scribed "1/4 S28 BT".

All bearing trees have a 6" red band painted around the tree and the blazed face painted red. U.S.F.S. sign 54-3, BEARING TREE, and sign 54-9, LAND SURVEYING MONUMENT, are nailed to all bearing trees. All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown, and distances are measured to the root crown at the side and center of the tree. Bearings and distances were measured with a staff compass (Decl. 20°E) and steel tape.

12/12/91

Loyd R. Moffit
For: U.S.F.S.
Jan. 1986
C.S. 62/30

Loyd Moffit
For; U.S.F.S.
Dec. 1986
C.S. 62/30

Christian DeGroot
LS #1941
For: U.S.F.S.
Dec. 12, 1991
C.S. File 63/138