

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 1 W R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 31881

209

$\frac{1}{4}$  cor to sec. 24 & 19  
Monuments FD.

blazes 30" now 42" dia., 30 ft. high D.Fir snag with single healed  
on east and west side of corner tree (orig. cor. tree)  
out of  $2\frac{1}{2}$ " dia. DCSO Brass Cap on  $1\frac{1}{4}$ " O.D. by 36" long I.P. is fd.  
ground along south side of corner tree (Ren #21)

County Surveyors Office

R	$\frac{1}{4}$	R
2	S24 S19	1
W	T 31 S	W
1966		

Accessories FD.

Brg's & distances taken from center of Orig. Cor. tree  
18" now 30" dia. 5' high D.Fir stump with fully healed  
single blaze & bark scribing " $\frac{1}{4}$ S" bears N.77 $\frac{1}{2}$ °W., 21.5 ft. (rec.  
N.74°W., 20.5 ft. dist is a possible face to face measurement)  
Orig. BT.

30" now 42" dia. 15' high D.Fir snag with a previously  
opened blaze, scribing visible "BT" bears N.10°E., 34 ft. (orig.  
rec. N.10°E., 30.4 ft.) Orig BT.

Brg's & Dist. taken from reset position of 1966

9" now 12" dia.  $1\frac{1}{2}$  ft. high rotted W.Fir stump scribing fd.  
"BT" bears N.27°W., 34.2 ft. (rec. N.29°W., 34.6 ft. distance  
is a possible slope distance) Ren. #21.

12" now 21" dia. W.Fir with a fully healed double blaze  
bears S.61°E., 12.7 ft. (rec. S.59°E., 13 ft.) Ren. #21.

Monuments set

We investigated numerous position to reset 1966 BC/IP. None  
of which fit well on ground (BC/IP would fall inside cor. tree or lie  
on top of large undisturbed roots) We reset DCSO BC/IP at most  
probable 1966 position between two large roots on southerly side of  
corner tree. Loose dirt was found between roots down to a depth that  
ground marks showed on BC/IP. BC/IP protrudes 18" above ground and  
is surrounded by a  $2\frac{1}{2}$ " ft. dia., 15" high mound of stone.

County Surveyor Office

	N15E	$\frac{1}{4}$	2.6ft
R	to		cor R
2	S24 S19		1
W	Reset 1993		W
T31S			
1966			

New Accessories

BRG's & Dist. taken from center of orig. cor. tree  
DCSO BC/IP bears S.15°W., 2.6 ft.  
21" dia. W.Fir (1966 ren tree) with a fully healed double  
blaze bears S.49 $\frac{1}{2}$ °E., 13 ft.  
6" dia., W.Fir, double blazed and scribed " $\frac{1}{4}$  S19 CS BT "  
bears S.14 $\frac{1}{2}$ °E., 20.2 ft.  
8" dia., D.Fir, double blazed and scribed " $\frac{1}{4}$  S24 CS BT "  
bears S.79°W., 12.9 ft.  
8" dia., Maple, double blazed and scribed " $\frac{1}{4}$  S19 CS BT "  
bears N.19°E., 19.5 ft.

The corner is the Orig. corner tree. all new accessories are in  
reference to the corner tree. The DCSO BC/IP should be used as a  
reference to the corner tree.

*Fd OK, 1994-0036, R Brown, 2/94*

210

Next PG for

210

Douglas Co. Surv  
Randall Smith  
Stephen Flauser  
Nov. 4, 93  
C.S.64/47