

Douglas County Surveyor's Record of
Government Corners Renewed

T31 S.T.S. RIW R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

1/4 Cor. Secs. 5 & 8

210

Found - 2½" dia. brass cap, properly mkd., firmly set, flush w/3 ft. mound of stone established by Ruppert in 1977 (Ren. #166) from which 36" dia., D.Fir, bears N.29°19'E., 97.9 ft. w/healed double blaze.
16" dia., D.Fir, bears S.12°31'W., 70.0 ft. (rec. S.32°55'E., 66.4 ft.) w/healed double blaze. This is the bearing & dist. reported to the Forest Service on the corner card signed by Wm. Ruppert in 1977 & etched on the BT tag I found on the ground beside the tree. I checked within ½ minute in bearing & 0.2 ft. in distance & I accept the information from Ruppert's corner card.

Leonard Herzstein
USDA Forest Service
Witness:
Erica Barth
Jan. 4, 2001
C.S. File 65/36-1

21" dia., D.Fir, bears N.64°19'W., 91.8 ft. with a healed double blaze.

New - A steel fence post bears N.89°W., 3.9 ft., projecting 4.0 ft. out of the ground w/Forest Service signs "Property Boundary" (#54-2) and "Attention" (#54-4) attached.

Note - At the corner point, I used a magnetic declination of 17°E. in the staff compass to obtain a back sight bearing of S.89½°E., on a boundary post established by Ruppert in 1977, approx. 200 ft. away. I used my bearings & distances to confirm Ruppert's work. Trees are measured at the center of the root crown. Tree diameters are at breast height.

To reach the corner, take an old logging road, which is gated at Forest Service Road No. 1610 (Devil's Knob Road), northward ¾ miles through sec. 8. At the curve at the end of the road, walk approx. 1000 ft. west on the section line to the corner.

Cor. Secs. 7, 8, 17, & 18

211

Condition Report

Found - 1" galv. iron pipe exposed 12" above ground in a 36" dia. stone mound with a 2½" dia. brass cap firmly affixed to the top stamped as per rec.

Les Fanning
2/2001
C.S. File
65/36-10

From which OBT:

Was 18" now 26" B.Oak snag bears S.55°W., (Rec.) 65.3 ft. (Rec.) with a good face scar.

BTs mkd. by Powell:

Was 13" now 20" D.Fir bears N.47°E. (Rec.) 26.31 ft. (Rec.) with healed face.

Was 14" now 20" Laurel bears N.59°W. (Rec. N.62°W.) 17.0 ft. (Rec.) with healed face.

Was 12" now 16" D.Fir bears S.37°W., (Rec.) 28.1 ft. (Rec.) with healed face.

Was 13" now 13" high stumped D.Fir bears S.50°E. (Rec.) 52.0 ft. (Rec.) with good face scar.

No suitable trees available in Sec. 17

All BTs were painted with a red 6" band & faces.

F.S. sign 54-9 attached to the back of each tree. BT tags were updated or replaced.

Magnetic decl. 20°E.

continued next page