

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Cl. Corner to Sections 18 and 19 only, T31-2W. 36

Found - 24" Fir, now 30", N. 70° E. 7.3 ft., shows good scar.  
24", now 30" Fir S. 31° E. 13.2 ft., shows good scar.  
Squared Stake at Cl. Corner N. face scribed S18, 3 notches.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R  
Office, 1966 3 S 24 S 18 2  
W S 19 W

Both Bearing Trees in good condition.

Corner to Sections 13 and 24 only, T31-3W. 37

Found - 10", now 22" Fir N. 71½° E. 16.5 ft., shows good scar.  
7", now 10" Laurel S. 29° E. 18.5 ft., opened & found rotten.  
48", now 54" Pine S. 41½° W. 16.5 ft., shows good scar.  
8" Chinq. N. 15½° W. 27.1 ft., This tree down with scribing visible, "R3W S13".

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R #228  
Office, 1966 3 S 13 S 19 2  
W S 24 S 19 W

New BT's: 8" Hemlock S. 32° E. 34.4 ft. scribed T31S R2W S19 CS BT.  
7" Laurel N. 66° W. 27.1 ft. scribed T31S R3W S13 CS BT.

Sec. Cor. To Secs. 30 & 31, T31-2W. 38

Found - Stone at Sec. Cor. Mkd: C.C. on E. face.  
36" D. Fir, now 40", N. 40° E. 11.2 ft., shows good scar.  
12" Fir, now snag, S. 48° E. 23.8 ft., opened for scribing.  
(This BT. bearing S.B. S.40°E.)

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's R T 31 S R  
Office 1966 3 S 30 2  
W S 31 W

New BT: 24" D. Fir S. 10° W. 34.0 ft. scribed T31S R3W S25 CS BT.

Sec. Cor. to Secs. 25 & 36 only, T31-3W. 39

Found - 30" Fir, N. 35° W. 28.0 ft., shows scribe marks.  
16" Fir, now down, N. 45° E. 1.0 ft.  
Orig. 30" Fir, now stump, S. 18° W. 53.0 ft.  
Orig. 30" Fir, now down, S. 30° E. 23.0 ft., shows scar.  
No trace of Iron Pipe, See Ren. #35, T31-3W.

Set - Brass Cap Mkd: County Surveyor's R T 31 S R  
Office 1966 3 S 25 2  
W S 36 W

New BT: 8" Chinquapin bears S. 60° W. 31.3 ft. mkd: T31S R3W S36 CS BT.

Township Corner: 40

Found - 15" Fir, now 36" Corner Tree, had been opened, scribing.  
18" Fir, now stump, S. 70° W. 18.5 ft., shows good scar.  
15" Fir, now stump, N. 66° W. 79.9 ft., shows scar.  
48" Fir, now 49", N. 48° E. 19.8 ft., very old bark scribe.  
15" Fir, now 34", S. 40° E. 13.2 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R  
(N-W Side of Office 2 S 36 S 31 1  
Corner Tree) 1966 W S 1 S 6 W  
T 31 S

New BT's: 12" D. Fir N. 19° W. 81.3 ft. scribed T30S R2W S36 CS BT.  
11" D. Fir S. 12° W. 109.3 ft. mkd: T31S R2W S 1 CS BT.  
Distances to center of corner tree.

Note - Corner lies on top of main ridge, running East & West.  
June 6, 1966

John M. Powell  
Frank Jones & Joe Brady  
Jan. 28, 1966  
C. S. File No. 52/63

John M. Powell  
Frank Jones & Joe Brady  
April 15, 1966  
C. S. File No. 52/63

John M. Powell  
Frank Jones & Joe Brady  
June 1966  
C. S. File No. 53/15