

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

John M.
Powell &
Crew
C. S. File
No. 54/28

1/4 Corner to Sec. 1, T31-2W. & Sec. 6, T31-1W.
Found - 18" Oak, now 24", N. 60° W. 15.2 ft., rotten face.
20" Oak, now 22", S. 80° E. 9.9 ft., Dead Snag, Tree had
been opened for scribe "BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S
Office, 1966 R2W 1/4 S 1/S 6 RLW
New BT's: 12" D. Fir S. 55 1/2° W. 10.8 ft. scribed 1/4 S 1 CS BT.
10" D. Fir N. 55 1/2° E. 19.6 ft. scribed 1/4 S 6 CS BT.

June 6, 1966

41

Sec. Cor. to Secs. 12 & 13, T31-2W. & Secs. 7 & 18, T31-1W.
Found - Corner Tree & Sandstone at Cor. See Ren. #223
Orig. 20" W. Oak, now 18", S. 57° E. 57.1 ft. scribe visible "18".
8" W. Oak, now 7", S. 42° W. 8.6 ft. shows good scar.
10" Pine, now 14", N. 55° W. 41.0 ft., Tree had been opened,
corner scribe pitched over, scribing visible.
6" W. Oak, now 7", N. 28° E. 11.9 ft., shows good scar.
Set - Brass Cap on E. Side of 6" Corner Tree mkd: R T 31 S R
County Surveyor's 2 S 12 S 7 1
Office, 1966 W S 13 S 18 W
No New BT's. marked as all trees in good condition.

42

Sec. Cor. to Secs. 13 & 24, T31-2W. & Secs. 18 & 19, T31-1W.
Found - Stone at Sec. Cor. 16x10x8, See Ren. #11
20" E. Oak N. 65 1/2° W. 44.2 ft. Opened for scribe "3BT". Rotten.
(Bearing should be N. 75 1/2° W.)
No trace of N.E. - S. E. - BT's.
20" Laurel, now 24", S. 56° W. 17.8 ft., no scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
Office 2 S 13 S 18 1
1966 W S 24 S 19 W
New BT's: 24" Cedar N. 45 1/2° W. 41.9 ft. scribed T31S R2W S13 CS BT.
14" D. Fir N. 25° W. 22.9 ft. scribed T31S R2W
10" D. Fir S. 45° E. 39.4 ft. scribed T31S RLW S19 CS BT.
Reblzd. & Rescrbd: 24" Laurel S. 56° W. 17.8 ft. scribed T31S R2W S24 CS BT.

43

1/4 Corner to Sec. 24, T31-2W. & Sec. 19 T31-1W.
Found - 30" Corner, now dead snag.
18" D. Fir, now stump, N. 74° W. 20.5 ft., bark scribed "1/4 S".
30" D. Fir, now dead snag; N. 10° E. 30.4 ft., shows good scribe.
Opened tree for scribe "BT" find dist. to be 34.0 ft.
Set - Brass Cap S. Side Corner Tree Mkd: R T 31 S R
County Surveyor's 1/4 2 S 24 / S 19 1
Office, 1966 W W
New BT's: 9" W. Fir N. 29° W. 34.6 ft. scribed 1/4 S24 CS BT.
12" W. Fir S. 59° E. 13.0 ft. scribed 1/4 S19 CS BT.

44

Sec. Cor. to Secs. 19 & 30, T31-1W. & Secs. 24 & 25, T31-2W. Fd. OK. 7-7-81
Found - GLO Brass cap mkd. incorrectly: S 25 S 30
1922 S 36 S 31 L. HERZSTEIN CS. 6/27
Orig. 18" D. Fir, now snag, N. 5° E. 13.2 ft., opened for scribe "BT".
Orig. 20" D. Fir, now down, N. 60° W. 4.0 ft., opened for scribe, "BT".
Orig. 18" D. Fir, now 27", S. 89 1/2° E. 91.1 ft., shows scar (Rescribed)
Orig. 18" D. Fir, now stump, S. 50° W. 21.8 ft. (dist. S.B. 17.3 ft.)
No scribing on stump, but part of old burned face.
1922 BT's: 11" D. Fir N. 79° W. 9.4 ft., opened for scribe "R2W".
13" D. Fir S. 49° W. 30.3 ft., shows good scar.
27" D. Fir S. 89 1/2° E. 91.1 ft., rescribed on bark T30SRLW S30.
Set - Brass Cap alongside 1922 B.C. & Mkd: R T 31 S R
County Surveyor's 2 S 24 S 19 1
Office, 1966 W S 25 S 30 W
New BT's: 12" D. Fir S. 76° E. 9.5 ft. scribed T31S RLW S30 CS BT.
11" D. Fir N. 19° E. 27.9 ft. scribed T31S RLW S19 CS BT.
10" D. Fir N. 67° W. 23.4 ft. scribed T31S R2W S24 CS BT.
11" D. Fir S. 42° W. 18.7 ft. scribed T31S R2W S25 CS BT.

45

John M. Powell
Frank. Jones & Terry Connell
June and July 1966
C. S. File No. 54/28