Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

46

¼ Corner to Sections 18, T31-1W. & Section 13, T31-2W.
Found - Sandstone a t ¼ Corner, no marks visible. Ren. #13.
10" Fir, now 17", N. 32° E. 60.1 ft., bark scribed "¼S" BT".
14" Fir, now 23", N. 32° W. 48.8 ft., bark scribed ¼ S13 CS BT.
Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1966 R ¼ 2W T 31 S S 13/S R 18 1W
Reblazed & Rescribed: 17" D.Fir N. 32°E. 60.1 ft. mkd. ¼ S18 CS BT.
23" D.Fir N. 32° W. 48.8 ft. mkd. ¼ S13 CS BT.
Note - This corner lies about 150 ft. south of high, rock bluffs, that drop off to the west and north.

- - - - - -

47

¼ Corner to Sec. 7, T31-1W. & Sec. 12, T31-2W.
Found - 6" Maple Corner Tree, See Ren. #3, T31-1W.
4" Maple, now 6", N. 51½° W. 15.0 ft., scribe marks visible.
12" D. Fir, N. 48½° E. 15.0 ft., shows good scar.
Set - Brass Cap alongside Maple mkd: County Surveyor's Office, 1966 R ¼ 2W T 31 S S12/S R 7 1W
New BT: 21" D. Fir N. 5° W. 26.7 ft. scribed ¼ S12 CS BT.
Note - This corner lies 30.0 ft. west of 60.0 ft. high vertical bluff.

RE-RENEWED, SEE CORNER NO. #213

- - - - - - -

48

Sec. Cor. to Secs. 30 & 31, T31-1W. & Secs. 25 & 36, T31-2W.
Found - Stone at Sec. Corner, no marks visible.
Orig. 28" Cedar N. 5° E. 5.9 ft. scribe visible "31S R1W S30".
16" Pine, now snag, N. 22° W. 22.4 ft. scribe visible "R2S25BT".
30" Pine S. 66°E. 87.1 ft. scribe visible "R S", pitched over.
14" Laurel, now 19", S. 74½° W. 97.7 ft., scribe visible "36BT".
Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1966 R 2 W T 31 S S 25 | S 30 S 36 | S 31 R 1 W
New BT's: 6" D. Fir S. 41° W. 7.5 ft. scribed T31S R2W S36 CS BT.
7" Laurel N. 66° W. 22.6 ft. scribed T31S R2W S25 CS BT.
Note - This corner lies west of trail, tag on Pine Tree N. 66° W. 87.1 ft. to section corner.
FD. OK 7/78 G. BAUGHMAN #536 C.S. 58/173

49

¼ Corner to Sec. 30, T31-1W. & Sec. 25, T31-2W.
Found - 12", now 20" Laurel N. 70° E. 18.5 ft. Opened for "BT" scribe.
15" Oak N. 57° W. 25.7 ft. No trace of this tree.
Reset - 1922 GLO Brass Cap from 20" Laurel, see above.
Reblazed & Rescribed: 20" Laurel N. 70° E. 18.5 ft. mkd: ¼ S30 CS BT.
New BT: 24" D. Fir S. 81° W. 20.0 ft. mkd: ¼ S25 CS BT.

- - - - - - -

50

¼ Corner to Sec. 31, T31-1W. & Sec. 36, T31-2W.
Found - Stone at ¼ Corner, marked "¼".
18" Cedar, down & rotten, N. 10° E. 9.9 ft., found scribing "BT"
28" Cedar, now burned stump, S. 47° W. 14.5 ft.
Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1966 R 2W T 31 S ¼ S 36/S R 31 1W
New BT's: 6" D. Fir N. 15° E. 17.9 ft. mkd. ¼ S31 CS BT.
8" D.Fir S. 60° W. 17.0 ft. mkd. ¼ S36 CS BT.
Note - This corner lies 50 ft. north of trail. Location tag on trail.
FD. OK 7/78 G. BAUGHMAN #536 C.S. 58/173

51

¼ Corner to Sections 14 and 13.
Found - Unrecorded 1½" I. Pipe at Corner. No trace of stone. Ren. #8
26" Fir, now stump, N. 62° W. 16.6 ft., opened for scribing.
(This stump is out of place but renewed by using stump hole)
No trace of N. E. BT.
Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1966 T 31 S R 2 W ¼ S 14/S 13
New BT's: 11" W. Oak S. 77° E. 125.0 ft. scribed ¼ S13 CS BT.
12" Cedar N. 42° W. 218.7 ft. scribed ¼ S14 CS BT.

- - - - - - -

John M. Powell
Frank Jones & Terry Connell
June and July 1966
C. S. File No. 54/28