

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

58

$\frac{1}{4}$ Corner to Sections 23 ~~ONLY~~ - SEE REN.# 140
Found - Orig. Stone at corner with $\frac{1}{4}$ " on north face.
Orig. 12" D. Fir, now rotten snag, N. 5° W. 12.5 ft., opened for "BT".
16" W. Fir, now 27", S. 32° E. 25.1 ft., scribe visible "S 26 BT"
16" Laurel N. 28° E. 25.1 ft., now hole in ground, good bear. & dist.
Set - Brass Cap alongside Stone Mkd: County Surveyor's Office T 31 S R 2 W
1966 S 23
S 26
New BT: 11" Cedar N. 48° E. 14.3 ft. scribed $\frac{1}{4}$ S23 CS BT. 140
July, 1966

59

Section Corner to Secs. 23 - 24 - 25 - 26.
Found - 30" Pine, now stump, N. 67° W. 49.5 ft., scribe visible.
36" Pine, now stump, S. 32° W. 77.9 ft., scribe visible.
15" Laurel, now 22", S. 45° E. 23.1 ft., faint scribe visible
on old rotten face.
6" Laure, now 15"; N. 88° E. 37.6 ft., face rotten.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R 2 W
1966 S 23 S 24
S 26 S 25
New BT's: 10" D. Fir S. 62° E. 41.4 ft. scribed T31S R2W S25 CS BT.
14" Laurel N. 76° E. 29.5 ft. mkd. T31S R2W S24 CS BT.
6" D. Fir N. 33° W. 13.8 ft. mkd. T31S R2W S23 CS BT.
10" D. Fir S. 76° W. 34.3 ft. mkd. T31S R2W S26 CS BT.
Note - This corner lies in East & South fence corner.

60

$\frac{1}{4}$ Corner to Sections 27 and 26.
Found - No Stone at Corner.
Orig. 20" Fir, now 21", S. 23° E. 4.0 ft., tree had been opened
for scribe.
Orig. 24", now 25" Fir, N. 67° W. 4.6 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R2W
1966 S 27 / S 26
Reblzd. & Rescrbd: 21" D. Fir S. 23° E. 4.0 ft. scribed $\frac{1}{4}$ S27 CS BT.

61

$\frac{1}{4}$ Corner to Sections 25 and 26.
Found - No trace of Corner Stone.
Orig. 10" W. Fir, now 15", S. 86° E. 13.2 ft. Tree Dead.
Orig. 12" W. Fir, now 18", S. 70° W. 13.2 ft. opened for
scribing. This tree is dying.
Set - Brass Cap at Cor Mkd: County Surveyor's Office T 31 S R 2 W
1966 $\frac{1}{4}$ S 26/S 25
New BT's: 10" W. Fir N. 11° E. 25.1 ft. scribed $\frac{1}{4}$ S25 CS BT.
13" D. Fir N. 88° W. 55.0 ft. scribed $\frac{1}{4}$ S26 CS BT.
Note - This corner lies in cut unit about 140 ft. south of old
logging road.

62

$\frac{1}{4}$ Corner to Sections 27 and 34.
Found - Iron Stone at $\frac{1}{4}$ Corner with $\frac{1}{4}$ " on North face.
15" Fir, now dead, N. 31° W. 11.9 ft., opened for scribe. #212
18" Fir, now dead, South 16.5 ft., shows good scar.
Set - Brass Cap alongside Stone Mkd: County Surveyor's Office T 31 S R 2 W
1966 $\frac{1}{4}$ S 27
S 34
New BT's: 15" D. Fir S. 71° E. 34.3 ft. mkd. $\frac{1}{4}$ S34 CS BT.
19" D. Fir N. 76° W. 3.0 ft. mkd. $\frac{1}{4}$ S27 CS BT.

63

$\frac{1}{4}$ Section Corner to Sections 24 and 25.
Found - Orig. 12" Laurel N. 65° E. 18.5 ft., opened for scribing "BT".
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office T 31 S R2W
1966 S 24
S 25
New BT's: 12" D. Fir N. 15° E. 21.0 ft. scribed $\frac{1}{4}$ S24 CS BT.
18" E. Fir S. 58° E. 37.3 ft. scribed $\frac{1}{4}$ S25 CS BT.

Hohn M. Powell
Frank Jones & Terry Connell
June and July 1966
C. S. File No. 54/28

RE-RENEWED, SEE CORNER NO. #212

RE-RENEWED, SEE CORNER NO. 217