

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

64

Section Corner to Sections 26 - 27 - 34 - 35.  
Found - Pieces of Corner Stone.  
Orig. 12" Pine, now snag, N. 23° E. 70.0 ft. (Bearing S. B. N. 13° E.)  
Scribe visible, "1S 26 T".  
Orig. 18" Fir, now stump, S. 79° E. 60.1 ft., opened for scribe "2".  
Orig. 15" Laurel, now 20", S. 38° W. 54.8 ft., rotten face.  
Orig. 40", now 44" Pine, N. 65° W. 10.6 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
S 27 | S 26  
S 34 | S 35  
New BT's: 9" Laurel S. 29½° E. 7.2 ft. mkd. T31S R2W S35 CS BT.  
10" D. Fir S. 31° W. 31.0 ft. mkd. T31S R2W S34 CS BT.  
8" D. Fir N. 86° E. 15.5 ft. mkd. T31S R2W S26 CS BT.

¼ Corner to Sections 34 and 35.  
Found - Iron Stone at ¼ Corner mkd: "¼" on north face.  
18" Cedar, now 24", S. 87° W. 9.9 ft., scribe visible "S".  
20" Fir, now stump, N. 38° E. 11.2 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
S 34 | S 35  
New BT's: 42" D. Fir N. 26° W. 18.6 ft. scribed 34 CS BT.  
No trees available in Sec. 35.  
Note - This corner lies about 60.0 ft. on north side of draw.  
FD. OK L. HERZSTEIN 6-4-81 CS-6/27 #218

65

Sec. Cor. to Sections 34 and 35 only, T31-2W.  
Found - 15x6x6 Basalt Stone mkd. with notches & CC on North face.  
36" D. Fir, now stump, N. 10° E. 33.0 ft. (Dist. S. Be 47.2 ft., scribe visible "2 W".  
16" D. Fir, now 24", N. 48° W. 21.8 ft. Had been opened but patched over.  
Set corner with 2 correct bearings & 1 distance which fall at Corner Stone.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
S 34/S 35  
S 3 T32-2W  
New BT: 28" Cedar N. 1½° W. 32.6 ft. mkd. T31S R2W S35 CS BT.  
Note - 12" Yew Post at Fence Corner N. 31° W. 21.3 ft.

66

Sec. Corner to Sec. 31, T31-1W. & Sec. 36, T31-2W.  
Found - Orig. 30" Fir N. 30° E. 38.3 ft., shows good scar.  
Orig. 14" Fir, now down, N. 33° W. 19.1 ft., scribe visible "R2W BT".  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
R T 31 S R  
2 S 36/S 31 1  
W S 1 W T32S  
New BT: 24" D. Fir N. 19° W. 34.6 ft. mkd. T31S R2W S36 CS BT.  
FD. OK 7/18 G. BAUGHMAN #536 C.S. 58/173

67

¼ Corner to Sections 26 and 35.  
Found - Iron Stone at ¼ Corner.  
Orig. 60" Cedar, now stump N. 45° W. 12.5 ft. Opened stump for scribing.  
Orig. 12" Cedar, now dead, S. 32° E. 6.6 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
S 26  
S 35  
New BT's: 15" D. Fir S. 38½° E. 32.1 ft. mkd. ¼ S 35 CS BT.  
15" Cedar N. 6° E. 47.3 ft. mkd. ¼ S26 CS BT.

68

Sec. Corner to Sections 25 - 26 - 35 - 36.  
Found - No trace of W. Oak Corner Tree.  
10" Cedar, now 20", S. 60° E. 13.9 ft., opened for scribe "BT".  
20" W. Oak, now 26", S. 30° W. 5.3 ft., shows good scar.  
30" D. Fir, now down, N. 35° E. 5.7 ft., shows scar.  
20" W. Oak, now snag, N. 45° W. 15.2 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
S 26 | S 25  
S 35 | S 36  
New BT's: 7" D. Fir N. 52° W. 39.3 ft. mkd. T31S R2W S26 CS BT.  
8" D. Fir N. 29° E. 27.0 ft. mkd. T31S R2W S25 CS BT.

69

John M. Powell  
Frank Jones & Terry Connell  
June and July 1966  
C. S. File No. 54/28

RE-RENEWED, SEE CORNER NO. #189