

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

70

1/4 Corner to Sections 14 and 23.
Found - 30" Pine, now stump, S. 50° E. 24 chs. Find bearing to be
S. 40° E. & dist. to be 2 1/2 lks., 15.9 ft. Open stump for scribe.

8" Fir, now snag, N. 88° E. 9 chains, find dist. to be 9 lks.,
5.9 ft., Tree had been opened "BT" visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's
Office 1966 T 31 S R 2 W
S 14 S 23

New BT's: 16" Ash S. 15° E. 48.0 ft. mkd. 1/4 S 23 CS BT.
9" W. Fir S. 77° W. 30.1 ft. mkd. 1/4 S 23 CS BT.
13" Laurel N. 35° W. 77.0 ft. mkd. 1/4 S 14 CS BT.

Note - This corner is in fence corner, running south & east.

RE-RENEWED TREE CORNER NO #153; 154

71

1/4 Corner to Sections 13 and 24.
Found - No trace of Corner Stone as recorded in Ren. #10.
Orig. 24" Fir, now snag, S. 70° E. 13.2 ft., rotten, nothing visible.
Orig. 20", now 34" Fir, N. 40° W. 26.4 ft., bark scribe visible.

Set - Brass Cap in Mound of Stone 5' x 2.5' & Mkd: County T 31 S R 2 W
Surveyor's 1/4 S 13
Office, 1966 S 24

New BT's: 20" D. Fir S. 75 1/2° W. 32.9 ft. mkd. 1/4 S 24 CS BT.
Reblzd. & Rescrbd: 34" D. Fir N. 40° W. 26.4 ft. mkd. 1/4 S 13 CS BT.

72

1/4 Corner to Section 36 only, T31-2W.
Found - 16" Fir Stump N. 55° E. 35.6 ft., faint scribe visible.
(I find this bearing to be N. 50° E.)
14" D. Fir, now 24", N. 75° W. 16.5 ft., shows good scar,
No trace of corner stone.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office 1966 1/4 S 36 T32S

New BT: 4" D. Fir N. 27 1/2° E. 14.9 ft. mkd. 1/4 S 36 CS BT.

73

1/4 Corner to Section 35 only, T31-2W.
Found - 12", now 24" D. Fir N. 50° W. 31.7 ft. Opened for scribe.
No trace of N, E. BT. nor Stone, ground very steep.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office 1966 1/4 S 35 T32S

New BT: 5" D. Fir N. 15 1/2° E. 27.8 ft. scribed 1/4 S 35 CS BT.

FO. OK 7/28 G. BAUGHMAN #536 C.S. 58/73

Sec. Corner to Sections 35 and 36 only, T31-2W.
Found - Stone at Sec. Corner, no marks legible.
30" D. Fir, now 38", N. 45° W. 3.3 ft., shows good bear.
16" D. Fir N. 30° E. 19.8 ft., Tree down with burned face,
scribe marks visible. (Find bearing to be N. 65° E. 19.8 ft.)

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office 1966 S 35 S 36 T32S

New BT: 30" D. Fir N. 27° E. 55.0 ft. mkd. T31S R2W S36 CS BT.

FO. OK 7/18 G. BAUGHMAN #536 C.S. 58/73

RE-RENEWED TREE CORNER NO #231

75

1/4 Corner to Sections 35 and 36.
Found - No Trace of Stone.
18" D. Fir, now 24", N. 73° E. 27.7 ft. Opened tree for scribe.
18" D. Fir, now 24", S. 40° W. 27.7 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office, 1966 1/4 S 35/S 36 T32S

Reblzed & Rescrbd: 24" D. Fir N. 73° E. 27.7 ft. mkd. 1/4 S 36 CS BT.

Note - Bluff bears N. 40° W. about 80.0 feet.

FOOK 7/78 G. B. C.S. 58/73

John M. Powell
Frank Jones & Terry Connell
June and July 1966
C. S. File No. 54/28