

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

76

$\frac{1}{4}$ Corner to Sections 8 and 17.
Found - 12" Pine, now 31", S. 63° W. 62.7 ft. Opened for scribing "S".
No trace of N.E. BT. nor Stone, 8" x 60" x 15".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 8
S 17
New BT's: 7" Cedar S. 61 $\frac{1}{2}$ ° W. 43.9 ft. mkd. $\frac{1}{4}$ S 17 CS BT.
11" Cedar N. 41 $\frac{1}{2}$ ° W. 22.4 ft. mkd. $\frac{1}{4}$ S 8 CS BT.
Note - This corner lies in fill slope of old Rock Pit.

$\frac{1}{4}$ Corner to Sections 23 and 24.
Found - 24" Fir, now snag, N. 14° E. 29.7 ft. scribe visible " $\frac{1}{4}$ S BT".
(find this to be N. 33° E. 19.8 ft.)
14", now 32" Fir N. 15° W. 19.8 ft. (find this to be 29.7 ft.)
I opened this tree for "BT" & by ring count place it at about 1857. (Orig. Surv)
Direction of faces are very good for reversing distances.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 23/S 24
Set $\frac{1}{4}$ Corner by using 2 Orig. distances reversed & 1 Orig. Bearing.
New BT's: 13" Laurel N. 22° E. 14.2 ft. mkd. $\frac{1}{4}$ S 24 CS BT.
7" Laurel N. 49° W. 17.3 ft. mkd. $\frac{1}{4}$ S 23 CS BT.

77

~~$\frac{1}{4}$ Corner to Sections 22 and 23.
Found - 12" Corner Tree, Laurel, Opened for scribe "27".
16" Laurel, now 30", N. 30° W. 5.8 ft. found pieces of scribing.
16" Laurel, now 22", S. 70° W. 66.0 ft. Tree burned but still alive.
Set - Brass Cap at Cor. on ~~REN~~ of Corner Tree mkd: County Surveyor's Office 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 22
S 27
Reblzd. & Rescrbd: 30" Laurel N. 30° W. 15.8 ft. mkd. $\frac{1}{4}$ S 22 CS BT.
New BT: 12" D. Fir S. 25° W. 30.5 ft. mkd. $\frac{1}{4}$ S 27 CS BT.~~

78

$\frac{1}{4}$ Corner to Sections 29 & 28.
Found - No trace of Corner Stone.
10" Fir, now 12", S. 87° W. 9.2 ft. Opened for scribe "S29".
30" Laurel, down, N. 57 $\frac{1}{2}$ ° E. 9.2 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 29/S 28
New BT's: 16" D. Fir N. 86° W. 19.5 ft. mkd; $\frac{1}{4}$ S 29 CS BT.
26" D. Fir N. 40° E. 21.4 ft. mkd: $\frac{1}{4}$ S 28 CS BT.

Aug. 1966

79

~~$\frac{1}{4}$ Corner to Sections 21 only. SEE REN. # 139
Found - Stone mkd. " $\frac{1}{4}$ " on North face.
18" Fir, now stump, N. 65° E. 47.5 ft., opened for scribe "BT".
40" Cedar, now 43", S. 42° E. 20.5 ft. Had been opened & face burnt.
1" Iron Pipe, also.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 21
S 28 #139
New BT's: 9" W. Fir S. 17° W. 17.6 ft. mkd: $\frac{1}{4}$ S 28 CS BT.
6" W. Fir N. 88° W. 12.1 ft. mkd: $\frac{1}{4}$
Note - 1" Iron Pipe 1.4 ft. west of Brass Cap.~~

80

$\frac{1}{4}$ Corner to Sections 9 and 16.
Found - 15" Cedar, now 33", S. 25° E. 33.0 ft., shows good scar.
30" Fir, now down, N. 35° E. 21.8 ft., faint bark scribe "S".
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 9
S 16
New BT: 6" Cedar N. 38° W. 22.2 ft. mkd: $\frac{1}{4}$ S 9 CS BT.
Note - This corner lies on west slope about half way between bottom of draw and top of ridge.

81

John M. Powell
Frank Jones & Terry Connell
July 1966
C. S. File No. 54/28