

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

82

Section Corner to Sections 9 - 10 - 15 - 16.

Found - 30" Pine, now down, N. $2\frac{1}{2}^\circ$ W. 949.1 ft. scribe visible.
(fd. dist. to be 960.0 ft.)

30" Pine, now stump, S. $73\frac{1}{2}^\circ$ E. 468.6 ft. Stump had part
old face, lower face rotten.

No trace of N.E. Pine.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S R 2 W
S 9 S 10
S 16 S 15

New BT's: 23" Pine N. $\frac{1}{2}^\circ$ W. 98.3 ft. mkd. T31S R2W S9 CS BT.

24" Pine N. $65\frac{1}{2}^\circ$ W. 64.2 ft. mkd. T31S R2W S9 CS BT.

10" Cedar S. 6° E. 29.5 ft. mkd. S15 CS BT.

12" Cedar S. 61° W. 1101.5' mkd. T31S R2W S16 CS BT.

RE-RENEWED, SEE CORNER NO. #200

83

$\frac{1}{4}$ Corner to Sections 14 and 15.

Found - Good $\frac{1}{2}$ " Iron Pipe at $\frac{1}{4}$ Corner, See Ren. #11.
18" Fir, now stump, N. $68\frac{1}{2}^\circ$ W. 5.3 ft., BT scribe visible.

No trace of Orig. BT's.

New BT's: 8" Cedar S. 71° W. 8.0 ft. mkd. $\frac{1}{4}$ S14 CS BT.

9" Cedar S. 54° E. 25.0 ft. mkd. $\frac{1}{4}$ S15 CS BT.

Note - This corner lies by East & West Fence Line, 14" South
of fence line.

RE-RENEWED, SEE CORNER NO. #222

84

$\frac{1}{4}$ Corner to Sections 11 and 14.

Found - Orig. 18" Fir, now stump, S. 88° W. 8.6 ft. Partly opened,
"BT" visible.

No trace of other trees, cat trail & logged. Ren. #6

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966

T 31 S R2W
$\frac{1}{4}$ S 11
S 14

New BT's: 6" W. Fir N. 9° W. 27.7 ft. mkd. $\frac{1}{4}$ S11 CS BT.

18" W. Fir S. 61° E. 44.3 ft. mkd. $\frac{1}{4}$ S14 CS BT.

RE-RENEWED, SEE CORNER NO. #216

85

$\frac{1}{4}$ Corner to Sections 10 and 15.

Found - 10" W. Oak, now 17", N. 31° E. 62.7 ft., tree partly opened.
8" Oak Stump S. 79° E. 39.6 ft., Opened stump for scribing, "BT".

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966

T 31 S R 2 W
$\frac{1}{4}$ S 10
S 15

New BT's: 18" D. Fir S. 18° E. 26.6 ft. mkd. $\frac{1}{4}$ S15 CS BT.

23" D. Fir N. 27° W. 8.4 ft. mkd. $\frac{1}{4}$ S10 CS BT.

Note - This corner lies in North-South Fence - Fence Corner is
North 39.0 ft.

RE-RENEWED, SEE CORNER NO. #216

86

$\frac{1}{4}$ Corner to Sections 15 and 16.

Found - $\frac{1}{2}$ " I. Pipe (unrecorded)

12" Oak, now 29", S. 13° E. 39.6 ft., shows good scar.
(find dist. to be 41.0 ft.)

12" Oak, now 30", N. 1° W. 50.2 ft. (fd. dist. to be 51.2 ft.)
(Opened for scribing " $\frac{1}{4}$ S".)

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966

T 31 S R2W
$\frac{1}{4}$ S 16/S 15

New BT: 12" D. Fir N. 21° W. 28.0 ft. mkd. $\frac{1}{4}$ S16 CS BT.

RE-RENEWED, SEE CORNER NO. #216

87

$\frac{1}{4}$ Section Corner to Sections 15 and 22.

Found - 24" Pine, now 36", S. 40° E. 48.8 ft., scribe visible " $\frac{1}{4}$ S".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S R 2 W
$\frac{1}{4}$ S 15
S 22

New BT: 12" Pine N. 76° W. 11.2 ft. mkd. $\frac{1}{4}$ S15 CS BT.

Note - This corner lies on very steep, west slope, east of
Drew Creek.

RE-RENEWED, SEE CORNER NO. #216

John M. Powell
Frank Jones & Terry Connell
July & August 1966
C. S. File No. 54/28