

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21681

Section Corner to Sections 15 - 16 - 21 - 22. w.c. see #156 + 157 88
 Found - 18" Fir, down, S. 10° E. 44.8 ft., shows good scar.
 24" Cedar Stub N. 43° W. 20.5 ft., opened tree for scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S	R 2 W
S 16	S 15
S 21	S 22

 New BT's: 9" Cedar N. 4° E. 12.0 ft. mkd. T31S R2W S15 CS BT.
 11" Cedar N. 48° W. 14.4 ft. mkd. T31S R2W S16 CS BT.
 12" Cedar S. 32° W. 26.6 ft. mkd. T31S R2W S21 CS BT.
 8" Cedar S. 15° E. 14.6 ft. mkd. T31S R2W S22 CS BT.

Section Cor. to Sections 14 - 15 - 22 - 23. 89
 Found - I. Pipe at Sec. Cor., See Ren. #17.
 Orig. 15" Fir, now stump, S. 75° W. 4.0 ft.
 11" Cedar N. 42° E. 40.0 ft. "S14" scribe visible.
 No other trees found. Logged.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S	R 2 W
S 15	S 14
S 22	S 23

 New BT's: 12" Cedar N. 2° W. 27.3 ft. mkd. T31S R2W S15 CS BT.
 15" Cedar S. 31° W. 58.9 ft. mkd. T31S R2W S22 CS BT.
 As noted creek bears East 150.0 ft.

Sec. Corner to Sections 13 - 14 - 23 - 24. 90
 Found - 18" D. Fir, now Snag 30", S. 1° W. 260.0 ft. Opened for scribnd. "2".
 (found dist. to be 265.0 ft.)
 12" D. Fir, now 30", S. 83° W. 149.8 ft., shows good scar.
 (found dist. to be 143.7 ft.)
 No trace of NW-SE nor NE BT's.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S	R 2 W
S 14	S 13
S 23	S 24

 New BT's: 27" Cedar S. 3½° E. 252.3 ft. mkd. T31S R2W S24 CS BT.
 9" Laurel N. 24° W. 87.5 ft. mkd. T31S R2W S14 CS BT.
 19" D. Fir N. 55½° E. 223.2 ft. mkd. T31S R2W S13 CS BT.
 Note - This corner lies on open south slope.

Sec. Corner to Sections 17 - 18 - 19 - 20. 91
 Found - 30" Fir, now down, N. 50° E. 124.7 ft.
 30" Fir, now snag, N. 28½° W. 37.0 ft. Opened for scribing "R2".
 6" Fir S. 20° W. 44.9 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

T 31 S	R 2 W
S 18	S 17
S 19	S 20

 New BT's: 12" Cedar N. 5° E. 28.6 ft. mkd. T31S R2W S17 CS BT.
 21" D. Fir N. 62° E. 19.6 ft. mkd. T31S R2W S17 CS BT.
 12" D. Fir S. 33° E. 12.5 ft. mkd. T31S R2W S20 CS BT.
 No good trees in N.W. Quad.

¼ Corner to Sections 4 and 3. 92
 Found - 15x10x6 Basalt Stone ¼" on W. face.
 12" W. Oak, now 21", N. 3° E. 182.8 ft. (Bear S. Be N. 2° E.)
 Opened for scribing, found scribe marks, none legible.
 24" B. Oak, now 36", N. 2° W. 264.7 ft., shows good scar.
 (Bearing should be N. 3° W.)
 Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R 2 W
¼ S	4/S 3

 New BT: 23" W. Oak N. 15° E. 137.9 ft. mkd. ¼ S 3 CS BT.

¼ Corner to Sections 9 and 10. 93
 Found - Stone at ¼ Corner
 12" Pine, down, S. 65° W. 31.0 ft., fd. scribing "S9 BT".
 12" Cedar, now 30", S. 13½° E. 21.1 ft., shows old scar.
 Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966

T 31 S	R 2 W
¼ S	9/S 10

 (continued over)

John M. Powell
Frank Jones & Terry Connell
July & August 1966
C. S. File No. 54/28