

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T.S. R. 2 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

($\frac{1}{4}$ Corner Secs. 9 & 10 continued)

Reblzd. & Rescrbd: 30" Cedar S. $13\frac{1}{2}^{\circ}$ E. 21.1 ft. scribed $\frac{1}{4}$ S10 CS BT.
New BT: 13" Cedar N. 39° W. 31.7 ft. mkd. $\frac{1}{4}$ S 9 CS BT.

94

Sec. Corner to Sections 3 - 4 - 9 - 10.

Found - 36" Y. Pine, now 53", N. $41\frac{1}{2}^{\circ}$ W. 99.7 ft., shows scar.
30" Y. Pine, now dead, S. 76° W. 149.2 ft., scribe vis. "S9".
30" Y. Pine, now 38", S. 44° E. 332.0 ft., shows good scar.
30" Y. Pine, down & rotten, N. 34° E. 239.6 ft., "BT" scribe.

Set - Brass Cap at Cor. Mk'd: County Surveyor's Office 1966

S 4	S 3
S 9	S 10

New BT's: 30" Pine N. 30° E. 281.0 ft. mkd. T31S R2W S3 CS BT.
14" Dbl. Pine S. $39\frac{1}{2}^{\circ}$ W. 220.4 ft. mkd. T31S R2W S9 CS BT.

#179

95

$\frac{1}{4}$ Corner to Section 25 only, T31-3W.

Found - 18x8x5 Ironstone at $\frac{1}{4}$ Corner.
10" Yew, now 14" N. $17\frac{1}{2}^{\circ}$ W. 13.9 ft., fd. two old, rotten faces, but no scribe marks visible.
6" Hemlock S. 73° W. 38.3 ft., No trace of this tree.
Good call on creek. 78.5 ft. (1.19 chs.) from creek.

Set - Brass Cap at Cor. Mk'd: County Surveyor's Office, 1966

R $\frac{1}{4}$ T 31 S	R
3W $\frac{1}{4}$ S 25	2W

New BT's: 6" Hemlock N. $57\frac{1}{2}^{\circ}$ W. 30.3 ft. mkd: $\frac{1}{4}$ S25 CS BT.
15" Yew S. 23° W. 23.4 ft. mkd. $\frac{1}{4}$ S 25 CS BT.

96

$\frac{1}{4}$ Corner to Sec. 2, T31-2W. & Sec. 35, T30-2W.

Found - 30", now 34" Pine N. 80° E. (posted N. 75° E.) 56.1 ft., scribed " $\frac{1}{4}$ S" visible.

18", now 32" Oak, S. 30° E. 87.1 ft. scribe visible " $\frac{1}{4}$ S".
Set - Brass Cap at Cor. Mk'd: County Surveyor's Office, 1966

$\frac{1}{4}$ S 35	T30S
S 2	T31S R2W

Reblazed & Rescrbd: 32" Oak S. 30° E. 87.1 ft. scribed $\frac{1}{4}$ S 2 CS BT.

97

Sec. Cor. to Secs. 1 & 2, T31-2W. & Secs. 35 & 36, T30-2W.

Found - 10" Oak, now stob, N. 85° W. 31.4 ft., shows good scar.
10", now 15" Oak, S. 12° W. 44.2 ft., shows good scar.
15" Oak, now stob, S. 25° E. 42.2 ft., scribe visible "2W".
15", now 26" Oak N. 77° E. 25.1 ft., shows good scar.

Set - Brass Cap at Cor. Mk'd: County Surveyor's Office, 1966

T30S	R2W	S 35	S 36
T31S		S 2	S 1

New BT's: 17" W. Oak N. 30° W. 39.3 ft. mkd. T30S R2W S35 CS BT.
15" W. Oak S. 22° E. 45.4 ft. mkd. T31S R2W S1 CS BT.

98

$\frac{1}{4}$ Corner to Sections 3 and 2.

Found - 18", now 26" Bl. Oak N. 64° E. 63.4 ft., rotted out.
20", now 28" W. Oak S. 20° W. 50.2 ft., rotten face, but found scribing "BT".

Set - Brass Cap at Cor. Mk'd: County Surveyor's Office, 1966

T31S	R2W
$\frac{1}{4}$ S 3	S 2

New BT's: 12" D. Fir S. 27° W. 43.6 ft. mkd. $\frac{1}{4}$ S 3 CS BT.
11" W. Oak N. 83° E. 41.3 ft. mkd. $\frac{1}{4}$ S 2 CS BT.

Note - Very old fence line bears West about 10.0 ft.

99

Sec. Cor. to Sections 2 - 3 - 10 - 11.

Found - 20" Fir, now stump, N. 15° W. 58.1 ft.
12" Fir, now stump, S. 79° E. 53.5 ft. Opened Stump "BT".
15", now 21" Fir S. 31° W. 87.8 ft., shows good scar.
5", now 10", Oak N. 38° E. 29.7 ft., scribe visible "2 CS", (en. #3)

Set - Brass Cap at Cor. Mk'd: County Surveyor's office 1966

T31S	R2W
S 3	S 2
S 10	S 11

New BT's: 7" D. Fir S. 45° E. 31.0 ft. mkd. T31S R2W S11 CS BT.
16" Laurel N. 52° W. 38.0 ft. mkd. T31S R3W S3 CS BT.
16" D. Fir S. 51° W. 17.8 ft. mkd. T31S R2W S10 CS BT.

John M. Powell
Frank Jones & Terry Connell
August 1966
C. S. File No. 54/28