

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

John M. Powell
Frank Jones & Terry Connell
August, 1966
C. S. File No. 54/28

100
 $\frac{1}{4}$ Corner to Sections 2 and 11.
 Found - 24", now 31" Fir N. 71° W. 15.8 ft. Opened for scribing "1 S". #184
 10" Fir, now stump, S. 36° E. 29.0 ft., no scribing found. Ren. #5
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R 2 W
 1966 S 2
 S 11
 New BT: 9" D. Fir S. 27° W. 25.4 ft. mkd. $\frac{1}{4}$ S11 CS BT.
 Note - This corner lies 2.0 ft. north of E - W fence line and 12.0 ft.
 E. of fence corner.

101
 $\frac{1}{4}$ Corner to Sections 10 and 11.
 Found - 14", now 21", Fir S. 35° E. 55.0 ft., shows good scars.
 14", now 17" Cedar S. 33° W. 38.0 ft., scribe marks visible.
 Mound of Stones destroyed. Ren. #1.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 10/S 11
 Bearing Trees in good condition. Fence Corner running N. & E. bears
 S. 45° E. 4.4 ft.

102
 Section Corner to Sections 27 - 28 - 33 - 34.
 Found - 14", now 21" W. Fir Corner Tree.
 14", now 18" W. Fir N. 40° E. 22.4 ft., shows good scar.
 12", now 27" W. Fir N. 68° W. 41.6 ft., shows good scar.
 7", now 13" D. Fir, S. 50° E. 36.6 ft., opened for scribing "B".
 No trace of S.W. BT.
 Set - Brass Cap at Sec. Cor. on West side of Corner Tree mkd:
 County Surveyor's Office 1966 T 31 S R 2 W
 S 28 | S 27
 S 33 | S 34
 New BT: 14" W. Fir S. 31° W. 31.0 ft. mkd. T31S R2W S33 CS BT.

103
 Section Corner to Sections 28 - 29 - 32 - 33.
 Found - Slate Stone at Section Corner.
 12", now 15" Fir N. 82° E. 34.3 ft., shows good scar.
 20", now 27" Fir S. 18° E. 26.4 ft., shows good scar.
 8", now 13" Laurel N. 22° W. 19.1 ft.,
 8" Laurel, now dead, S. 76 $\frac{1}{2}$ ° W. 9.2 ft., faint scribe visible,
 "2" "B", other marks not legible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 31 S R 2 W
 S 29 | S 28
 S 32 | S 33
 New BT: 7" D. Fir S. 34° W. 30.5 ft. mkd. T31S R2W S32 CS BT.

104
 $\frac{1}{4}$ Corner to Sections 27 and 28.
 Found - Stone 8 x 24 x 18" above ground, $\frac{1}{4}$ W. face.
 8", now 12" Laurel S. 18 $\frac{1}{2}$ ° E. 11.9 ft., rotten center, faint
 scribe marks visible.
 12" Laurel, now dead, N. 52° W. 46.2 ft.
 Set - Brass Cap on East edge of Corner Stone Mkd:
 County Surveyor's Office, 1966 T 31 S R 2 W
 $\frac{1}{4}$ S 28/S 27
 New BT's: 17" D. Fir N. 75° W. 23.2 ft. mkd. $\frac{1}{4}$ S28 CS BT.
 11" D. Fir N. 41° E. 24.7 ft. mkd. $\frac{1}{4}$ S27 CS BT.

105
 Corner to Sections 21 and 22 only.
 Found - No sign of corner stone.
 10", now 14" Pine N. 20° E. 41.6 ft., scribe visible "T31SR2W S22 BT".
 36" Pine, now snag, N. 67° W. 54.1 ft. Tree opened, scribe visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 31 S R 2 W
 S 21/ S 22
 S 28
 New BT: 13" Cedar N. 7 $\frac{1}{2}$ ° W. 28.8 ft. mkd. T31S R2W S21 CS BT.
 Sec. Cor. to Sections 27 and 28 bears East 110.0 ft.
 Also Cedar S. 2° E. about 130.0 ft. scribed $\frac{1}{4}$ S 27.