

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

106

~~CLOSING~~
Section Corner to Sections 27 and 28, only.
Found - 12" x 24" x 16" Stone, "CC" on South Face, Out of ground.
10", now 14" Pine S. 4° E. 74.6 ft. Opened for scribe "31S2"27".
10" Cedar S. 62° W. 25.1 ft. Opened old scar to blaze, no scribe.
Set - Along East Side of Corner Stone, Brass Cap Mkd:
County Surveyor's T 31 S R 2 W
Office S 22
1966 S 28 / S 27
New BT's: 14" Cedar S. 21° E. 26.1 ft. mkd. T31S R2W S27 CS BT.
12" D. Fir S. 29° W. 19.1 ft. mkd. T31S R2W S28 CS BT.

107

1/4 Corner to Sections 21 and 22.
Found - 10" Fir, now snag, N. 45° W. 5.9 ft., shows good scar.
Orig. 40" Pine Stump S. 2° E. 64.0 ft. Opened for scribe "1/4".
No trace of N. E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office, 1966 1/4 S 21 / S 22
New BT's: 22" D. Fir S. 80 1/2° E. 8.4 ft. mkd. 1/4 S22 CS BT.
8" D. Fir N. 8° W. 45.0 ft. mkd. 1/4 S21 CS BT.
Aug. 9, 1966

108

Sec. Corner to Sections 7 - 8 - 17 - 18.
Found - Stone at Sec. Corner. No marks.
9" D. Fir, now 17", N. 60° W. 29.7 ft., shows scar.
12" Laurel, now 15", S. 38° E. 30.4 ft., tree with rotten face.
9" Fir, now burnt stump, N. 50° E. 33.0 ft.
15" Laurel, now 19", S. 48° W. 23.8 ft., opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office S 7 | S 8
1966 S 18 | S 17
New BT's: 6" D. Fir N. 20° E. 7.4 ft. mkd. T31S R2W S8 CS BT.
7" D. Fir S. 49° E. 19.0 ft. mkd. T31S R2W S17 CS BT.
Reblzd. & Rescrbd: 19" Laurel S. 48° W. 23.8 ft. mkd. T31S R2W S18 CS BT.
Note - Yellow location tag on top of ridge about 370 ft. S. of corner.
Sept. 8, 1966

109

1/4 Corner to Sections 17 and 18.
Found - Stone at 1/4 corner with faint "1/4" on W. face.
15" Cedar, now 32", N. 11° E. 28.3 ft., shows good scar.
24", now 33" Cedar S. 41 1/2° W. 17.8 ft., opnd. for scribe "T".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office, 1966 1/4 S 18/S 17
New BT's: 7" Laurel N. 37° W. 11.8 ft. mkd. 1/4 S18 CS BT.

110

1/4 Corner to Sections 30 and 31.
Found - No trace of Stone.
6" Cedar, now down, N. 70° W. 19.8 ft. mkd. "1/4 S30 BT" visible.
12" Hemlock, now 18", S. 37° W. 28.4 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office 1/4 S 30
1966 S 31
New BT's: 11" D. Fir N. 63° E. 29.0 ft. mkd. 1/4 S30 CS BT.
Note - This corner lies on steep bank 13.0 ft. north of creek.

111

1/4 Corner to Sections 18 and 19.
Found - 40" Fir, now down, N. 70° W. 25.1 ft.
18", now 33" Fir S. 41 1/2° W. 13.2 ft., shows good scar.
15X10X4 Stone mkd. "1/4" on N. face at 1/4 corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 2 W
Office S 18
1966 S 19
New BT: 15" D. Fir N. 2 1/2° W. 32.7 ft. mkd. 1/4 S18 CS BT.
Note - This corner lies 25.0 ft. west of ravine.

John M. Powell
Frank Jones & Terry Conneil
August & Sept., 1966
C. S. File No. 54/28