

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO. EUGENE, ORE. 97301

112

1/4 Corner to Sections 19 and 30.  
Found - 15 X 8 X 8 Stone, "1/4" on N. face.  
36" D. Fir, now snag, N. 62 1/2° W. 19.1 ft., scribe visible "S19".  
5" Hemlock, now dead, S. 7 1/2° W. 15.2 ft., badly rotten face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
1/4 S 19  
1/4 S 30  
New BT's: 9" W. Fir S. 18° E. 12.2 ft. mkd. 1/4 S30 CS BT.  
9" W. Fir N. 60° E. 13.4 ft. mkd. 1/4 S19 CS BT.  
Note - This corner lies 16.0 ft. west of ravine.

113

1/4 Corner to Section 9 ONLY - SEE REN. #136  
Found - 20" Pine, now Snag, S. 60° E. 17.1 ft. scribe visible "S9 BT".  
30" Cedar S. 40° W. 54.1 ft., shows scar. Almost Dead.  
30 X 18 X 15 Stone mkd. with "X 1/4" on W. face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966  
T 31 S R 2 W  
1/4 S 8/S 9 136  
New BT's: 17" Cedar S. 74° E. 76.2 ft. mkd. 1/4 S9 CS BT.  
14" Cedar S. 85° W. 72.0 ft. mkd. 1/4 S8 CS BT.  
Note - This corner lies on rocky, east slope next to edge of timber, running about E. & W. AUG. 1966

114

S. East Corner Section 36 only, T31S R3W.  
Found - 2" I. Pipe bent over under small log. (See Ren. #41, T31-3W)  
40" W. Fir N. 55° W. 60.5 ft., shows good scar.  
11", now 14" Cedar N. 40° E. 68.5 ft., scribe visible "S 1 BT" #208  
15" W. Fir, now stump, S. 16° W. 28.4 ft. Opened for scribe "T32".  
24" D. Fir, now down, S. 14° E. 7.9 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
R T 31 S R  
3 S 36/S 1 2  
W T 32 S W  
Reblazed & Rescribed: 14" Cedar N. 40° E. 68.5 ft. mkd. T32SR3W S 1 CS BT.  
No other trees available. This corner lies just on south side of small ridge, running E - W.

115

1/4 Corner to Section 31 only, T31-2W.  
Found - 1" I. Pipe at Corner, See Ren. #19.  
5" Hemlock, now 11" S. 51° E. 7.0 ft., scribe visible "BT".  
13", now 14" Fir N. 75° E. 21.5 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
R T 31 S R  
3 1/4 S 31 2  
W W  
Bearing Trees O. K. This corner is north of rock pit in small draw.  
1/4 Corner of S36 only is gone. It lies in Rock Pit 435.0 ft. south of S 31 only.

116

1/4 Corner to Sections 5 and 8.  
Found - 15" Live Oak, now stump, N. 44° W. 34.9 ft. Opened for scribe "S BT".  
10" Laurel S. 32° E. 15.8 ft. No trace of this tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966  
T 31 S R 2 W  
1/4 S 5  
1/4 S 8  
New BT's: 19" Laurel N. 63° W. 112.4 ft. mkd. 1/4 S 5 CS BT.  
18" D. Fir Stump 2" high, south 5.4 ft. mkd. 1/4 S 8 CS BT.  
Note - This corner lies in cut unit about 350.0 ft. west of road and 100.0 ft. north of ravine. Yellow location tag on Road.

117

1/4 Corner to Sections 4. SEE REN. #138  
Found - 18" D. Fir, now 25", S. 25° E. 20.4 ft. Tree had been opened, "BT S4" visible.  
No trace of 4" Laurel.  
Stone with "1/4" mark, out of ground.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966  
T 31 S R 2 W #138  
1/4 S 5/S 4  
New BT: 8" D. Fir S. 22° W. 10.6 ft. mkd. 1/4 S 5 CS BT.

John M. Powell  
Franklin Jones & Terry Connell  
August & Sept., 1966  
C. S. File No. 54/28

RE-RENEWED SEE CORNER NO. #208  
RE-RENEWED SEE CORNER NO. #229