

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKS-CHAPMAN CO., EUGENE, ORE. 21881

118

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Slate Stone at Sec. Cor.

40", now 48" D. Fir, N. 34° E. 17.8 ft., shows good scar.

12", now 15" Hemlock, S. 64° W. 17.8 ft., scribe visible "3 2 T".

7", now 17" W. Fir, N. 11° W. 19.8 ft., shows good scar.

12" Maple, now down, S. 64° W. 13.2 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's

T 31 S	R 2 W
S 6	S 5
S 7	S 8

Office

1966

New BT's: 9" Hemlock S. 82° E. 34.9 ft. mkd. T31S R2W S8 CS BT.

Rescribed: 20" Hemlock S. 64° W. 17.8 ft. mkd. T31S R2W S7 CS BT.

Note - This corner lies 100 ft. west of Hatchet Creek.

119

Sec. Cor. to Sections 31 and 32 only, T31-2W.

Found - 14 x 10 x 6 Stone, "CC" on N. face.

20", now 31" D. Fir, N. 30° E. 50.8 ft., shows good scar.

12", now 17" Laurel, N. 52½° W. 35.6 ft., rotten face,
scribe visible, "31 R2W S31 BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's

T 31 S	R
S 31 / S 32	2
S 6	W

Office

1966

T 32 S

New BT: 11" Laurel N. 32° W. 27.6 ft. mkd. T31S R2W S31 CS BT.

Note - Best way to corner is on old trail from Neuman Gap, location tag on trail.

120

S. W. Corner Section 31 only, T31S R2W.

Found - 1" Iron Pipe at Corner. See Ren. #20.

Orig. 36" D. Fir, now 40", N. 43° E. 23.0 ft.

8" Hemlock S. 44° E. 28.0 ft., Tree dead, scribe visible "S1 32S".

16" D. Fir, now Snag, S. 6½° E. 15.4 ft., bark scribed.

13", now 15" W. Fir N. 49° E. 45.0 ft., scribe visible.

New BT: 27" D. Fir S. 32½° E. 34.7 ft. mkd. T32S R2W S1 CS BT.

Note - I. Pipe in good shape. Road bears east 75.0 ft., however, it lies in an old unit & grown over with small alder. Best way to reach corner is by walking down same from main road.

121

¼ Corner to Sections 31 only, T31-2W.

Found - 1" Iron Pipe at ¼ Cor., Ren. #21.

12" Alder, now 15" Snag, S. 55° W. 3.0 ft., scribe visible "¼S".

10" Hemlock, now down, N. 27° W. 8.2 ft.

New BT's: 19" W. Fir N. 74° E. 104.4 ft. mkd. ¼ S31 CS BT. (In old Road)

52" Fir Stump N. 42° W. 73.3 ft. mkd. ¼ S31 CS BT.

Note - This corner lies in creek which runs S.14°W-N.14°E., in cut unit.

122

Sec. Cor. to Sections 5 and 6, T32-2W only.

Found - 14" D. Fir, now 20" Stump 6.6' high, S. 44° E. 27.1 ft., Tree had been opened & burnt. Faint scribe marks visible.

20" D. Fir, now stump, S. 31½° W. 10.6 ft. opened for scribing.

Set - Brass Cap at Cor. Mkd: County Surveyor's

T 31 S	R 2 W
S 32	
S 6 / S 5	

Office

1966

No new trees to scribe so tagged Orig. Stumps on top & T 32 S top & sides.

Reblzd. & Rescribed: 20" D. Fir Stump S. 44° E. 27.1 ft. mkd. T32S R2W S5 CS BT.

Note - This corner lies in clear cut unit. BT Stumps are cut high.

Corner lies on top of small ridge about 250.0 ft. south & west of cutting lines, & about 300.0 ft. N. of badly eroded area.

John M. Powell
Frank Jones & Terry Connell
August & Sept., 1966
C.S. File No. 54/28

RE-RENEWED SEE CORNER NO. #210

RE-RENEWED SEE CORNER NO. #207