

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

123

Sec. Cor. to Sections 4 and 3 only, T32-2W.
Found - 16 x 12 x 10 Stone at corner with "CC" on S. face;
3 notches on E. face; 2 notches on W. face., Firmly set in ground.
Orig. 24", now 31" D. Fir, S. 66° E. 25.1 ft., (I find to be
S. 33° E.), Tree opened for scribe.
Orig. 12" D. Fir S. 36° W. 19.1 ft., (I find to be S. 60° W. 19.1')
Tree opened for scribe "4BT". Tree in good condition.
Set Corner by using Stone and two distances. T 31 S R 2 W
Set - Brass Cap at Cor. Mkd: County Surveyor's Office S 34
1966 S 4/S 3
T 32 S

124

1/4 Corner to Sections 32 only, T31-2W.
Found - No trace of Corner Stone.
20" D. Fir, now stump, N. 30° E. 50.8 ft. (find this N. 30° W. 50.8')
Scribe visible "1/4 S32 BT", by ring count this was done
about 1900. (Orig. 1908)
Parts of Laurel N. 57 1/2° W. 35.6 ft. (find this to be N. 57 1/2° E.)
Also by chaining btwn. the 1/4 Cor. Sec. 32 only & Sec. Cor. 5 & 6, T32-2W.,
I find dist. to be 292.8 ft. Orig. Notes call for 274.6 ft.
Difference of 18.2 ft.
This corner lies in clear cut unit. Not having anything to scribe,
I tag Orig. Stump N. 30° W. 50.8 ft. Also C. C. of
Sec. 5 & 6, T32-2W bears East 292.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 31 S R 2 W
1966 1/4 S 32 T 32 S

125

Sec. Cor. to Secs. 3 & 2, T31-2W. & Secs. 34 & 35, T30-2W.
Found - 24", now 32" D. Fir, S. 80° W. 16.5 ft., faint bark scribe & scar vis.
24", now 28" D. Fir N. 30° E. 11.9 ft., bark scribe "T30S" Visible.
6", now 15" Cedar N. 36° W. 22.4 ft., scribe visible "S3".
No trace of S. E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 30 S R 2 W
1966 S 34 | S 35
S 3 | S 2
T 31 S

Reblazed & Rescribed:
32" D. Fir S. 80° W. 16.5 ft. mkd. T31S R2W S 3 CS BT.
28" D. Fir N. 30° E. 11.9 ft. mkd. T30S R2W S 35 CS BT.
New BT: 6" D. Fir S. 38° E. 18.3 ft. mkd. S 2 CS BT.
Note - This corner lies about 60.0 ft. south of small draw.

126

Found Corner - 1/4 Corner to Section 34 only, T31-2W.
Found - 3" Brass Cap on 1/2" Iron pipe mkd: 34 31-2 1/4 &
Tag on tree set by Williams 7-14-65.
No trace of Original Corner
Bearing Trees found - 17" Laurel N. 5 1/2° W. 31.8 ft. mkd. T31S R2W S34 1/4 BT.
39" D. Fir S. 70° E. 23.0 ft. mkd. 1/4 BT, other
scribing not legible.

Sept. 14, 1966

127

1/4 Corner to Section 32 only, T30-2W.
Found - Scribed Stake at 1/4 Cor. Mkd: "1/4 S32 CS", See Ren. #11, T30-2W.
Orig. 12", now 18" Laurel N. 65° E. 44.8 ft., shows scar.
Orig. 8" Cedar Stump N. 60° W. 8.5 ft., scribe visible "4 S3".
10" D. Fir N. 37° W. 17.5 ft., scribe visible "4".
17" Cedar N. 69 1/2° E. 46.4 ft. scribe visible "1/4 S32 CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 30 S R
1966 1/4 S 32 2W
T31S
Bearing Trees are in good condition.

John M. Powell
Frank Jones & C. Stone
August & Sept. 1966
C. S. File No. 54/28

FD OK 7-95
B. Shaner
1119-64
CS 63/161-36
A