

Douglas County Surveyor's Record of
Government Corners Renewed

T.31 S. T. S. R. 2 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

128
Sec. Cor. to Secs. 3 & 4, T31-2 and Secs. 33 & 34, T30-2.
Found - 15" ^{CEDAR} Corner Tree, scribe visible T30S S 33 - 34.
10", now 14" D. Fir N. 62° E. 54.0 ft., shows good scar.
18", now 22" D. Fir S. 70° W. 8.6 ft., shows good scar.
40" D. Fir N. 70° W. 11.2 ft., scribe visible, "T30SR2WS33".
18" Fir, now stub, S. 20° E. 7.9 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 30 S R
(Set on S. Side of Office S 33 | S 34 2
Corner Tree) 1966 S 4 | S 3 W
New BT's: 20" D. Fir S. 10° E. 14.8 ft. mkd. T31S R2WTS33 ST. T 31 S
8" Cedar N. 35° W. 15.2 ft. mkd. T30S R2W S33 CS BT.

129
1/4 Corner to Sec. 4, T31-2W and Sec. 33, T30-2W.
Found - 24", now 30" Cedar, N. 20° W. 11.9 ft., poor condition, but
scribe visible "1/4 S".
18" D. Fir, now 25", South 6.6 ft., shows faint scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 30 S R #166
(Set on S. Side of Office S 33 | S 34 2
Corner Tree) 1966 S 4 | S 4 W
Reblazed & Rescribed: T 31 S
25" D. Fir South 6.6 ft. scribed 1/4 S 4 CS BT.
New BT: 4" Hemlock N. 30° E. 28.9 ft. scribed 1/4 CS BT.

130
Sec. Corner to Sections 4 and 5 only, T31-2W.
Found - 36" Corner Tree, now 42" ^{FIR} Fir, opened west side for scribing "5".
12", now 23" Fir S. 33° E. 34.3 ft., shows good scar.
20", now 25" Laurel, S. 1° W. 19.1 ft., shows good scar.
Set - Brass Cap on S. Side of Corner Tree Mkd: T 30 S R
County Surveyor's Office, S 32 | S 34 2
1966 S 5 | S 4 W
Reblazed & Rescribed: T 31 S
25" Laurel S. 1° W. 19.1 ft. mkd. T31S R2W S 5 CS BT.

131
Sec. Corner to Sections 32 and 33, only, T30-2W.
Found - 10", now 18", D. Fir N. 50° E. 38.2 ft., shows good scar.
36" D. Fir, now down, N. 3° W. 26.4 ft., scribe marks
visible, but not legible. T 30 S R
Set - Brass Cap at Cor. Mkd: County Surveyor's Office S 32 | S 33 2 #165
(Set on S. Side of Office S 4 | S 4 W
Corner Tree) 1966 T 31 S
New BT: 22" D. Fir N. 26° W. 33.5 ft. scribed T30S R2W S32 CS BT.

132
Section Corner to Secs. 1 & 12, T31-2W. & Secs. 6 & 7, T31-1W.
Set - 2 1/2" Bronze Disk set by single proper. method, from which:
BT's: 8" D. Fir bears N. 14° 30' E. 51.7 ft. scribed T31S RLW S6 BT.
10" D. Fir bears S. 86° E. 35.6 ft. mkd. T31S RLW S7 BT.
16" Sugar Pine bears N. 54° W. 1.7 ft. scribed T31-2W S1 BT.
10" Cedar bears S. 34° 30' W. 15.9 ft. scribed T31S R2W S12 BT.

133
South 1/16 corner btwn. Secs. 6, T31-1W. & Sec. 1, T31-2W.
Set - 2 1/2" Bronze Disk set by single proper. method, from which:
BT's: 6" Oak bears N. 31° 30' W. 32.3 ft. scribed S 1/16 S1 BT. #217
12" Oak bears S. 12° W. 35.1 ft. scribed S 1/16 S1 CS BT.

134
North 1/16 Corner btwn. Secs. 6, T31-1W. & Sec. 1, T31-2W.
Set - 2 1/2" Bronze Disk set by single proper. method, from which:
BT's: 16" D. Fir bears S. 22° W. 12.0 ft. scribed N 1/16 S1 BT. #201
36" Sugar Pine bears N. 1° 30' W. 46.5 ft. scribed N 1/16 S1 BT.

John M. Powell
Frank Jones & F. Connell
August, 1966
C. S. File No. 54/28

Glenn S. Baughman
Filler Ranger Dist.
June 20, 1967
C.S. 55/41 M 34 - 23