Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)
Found - 7" Chinquapin, now 10" N.66°E. 10.4 ft., scribe visible.
6" Hemlock, now 8" S.33°W. 8.5 ft., scribe visible.
9" Chinquapin, now 12", N.55°W. 15.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 — R 3 W — T 31 S | S 1 / S 12 | S 7 — R 2 W
This corner lies 215.2 ft. S. of Closing Corner Secs. 6 & 7, T31-2W.
3/25/70

142

Closing Corner to Secs. 6 & 7 only, T31-2W.
Found - 14x10x6 Stone at Corner, no marks visible.
30" Cedar, now stump, N.49°E. 48.8 ft., scribe visible.
24",now 36" Fir, S.69°E. 22.4 ft., shows scar.
Set - Brass Cap at Cl.Cor.Mkd: County Surveyor's Office 1970 — R 3 W — T 31 S | S 6 / S 7 — R 2 W
New BT: 12" W.Fir N. 7° E. 40.3 ft. mkd: "T31S R2W S 6 CC CS BT.
Reblzd.& Rescrbd: 36" D.Fir S.69°E. 22.4 ft. mkd: T31S R2W S7 CC CS BT.
This cor. lies 215.2 ft. N. of Sec.Cor. to 1 & 12, T31-3W.
3/25/70

143

¼ Corner to Section 1 only, T31-3W.
Found - Unrecorded 1" I.Pipe N.48°W. 2.8 ft.
30" D.Fir, now snag, S.50°W. 17.8 ft., tree opened, burnt face.
8",now 12" Laurel, N.41½°W. 27.1 ft., opened for scribe,
"S" & other marks, rotted face.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 — R 3 W — T 31 S ¼ S 1 — R 2 W
New BT's: 12" D.Fir N.12°W. 52.0 ft. mkd: "¼ S 1 CS BT.
16" Laurel N.87°W. 17.0 ft.mkd: "¼ S 1 CS BT.
3/25/70

144

Closing Corner to Sections 2 and 1, T32-2W.
Found - Original Corner Stone.
12" Orig.Fir BT.,decayed stub,scribe vis. bears S. 3°W. 18.5 ft.
10" Orig.Fir BT decayed stub, scribe vis., bears S.70½°E. 26.4 ft.
Set - Brass Cap Mkd: T31S, T32S, R2W.
C C S2/S1
1970 O.P.E. 4906
Mkd: 16" Fir BT. bears S.27°W. 78.5 ft.
10" Fir BT. bears S.79°E. 63.4 ft.
FD. OR 7/74 G. BACKMAN #536 C.S. 58/173 **Oct.31, 1970**

145

Center 1/4 Corner to Section 26.
Set - 2" Iron Pipe with 3" Brass Cap stamped:
T 31 S R 2 W
C 1/4 S 26
1972
RE 2128
From which: 12" D.Fir N.32°W. 21.5 ft. scribed:
"C1/4 S26 BT RE 2128"
12" D.Fir S.18 1/2° E. 10.6 ft. scribed:
"C1/4 S26 BT RE2128".
Aug. 1972

146

North 1/4 Corner to Section 26 only.
Set - 2" Iron Pipe with 3" Brass Cap stampd, as shown.
T 31 S R 2 W
1/4
S 26
1972 RE2128
from which: 17" Inc. Cedar South 39.0 ft. scribed:
"1/4 S26 BT RE2128.
12" D.Fir N.50°E. 18.5 ft. scribed:
"1/4 S26 BT RE2128.

John M. Powell
Fr. Jones & W. Penley
March, 1970
C.S.File No. 54/28

Bruce A. Shaner
Ump.Nat'l.Forest
Tiller Ranger Dist.
RM 2 = 21
MARCH 71

Barnes, Wm.
For:
Ump.Nat'l.
Forest
Map File:
M 42 - 69

See
Above:
M
4
2
-
6
9