

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 71881

Barnes, Wm. S.
For: Umpqua Nat'l.
Forest
Map M 42 - 72

Center 1/4 Corner Section 35. 147
Set - 2" Iron Pipe with 3" Brass Cap stamped as shown:
T31S R2W
C 1/4 S 35
1972
PE2128 from which bears:
A 20" D.Fir S.48°E. 20.8 ft. scribed C 1/4 S35 BT PE 2128
A 24" D.Fir N.73 1/2°W. 4.9 ft. scribed C 1/4 S35 BT PE 2128.
9/72

B
A
R
N
E
S,
W.M.
For:
Umpqua Nat'l.
Forest

1/4 Corner between Sections 25 and 36. 148
Set 2" I.P. with 3" B.C., stamped as shown:
T31S R2W
S 25
1/4 S 36
1972
PE2128 from which bears:
A 12" D.Fir N.89°E. 5.5 ft. scribed 1/4 S25 BT PE2128.
A 18" D.Fir S.82°W. 13.8 ft. scribed 1/4 S36 BT PE2128.
10/72

Oct.,
1972
Map
M

Center 1/4 Corner Section 25. 149
Set - 2" I.P. with 3" Brass Cap stamped as shown:
T31S R2W
C 1/4 S 25
1972
PE2128 from which bears:
A 8" W.Fir S.57 1/2°E. 20.0 ft. scribed C 1/4 S25 BT PE2128
A 12" W.Fir S.61°W. 38.2 ft., scribed C 1/4 S25 BT PE2128.
10/72

Glenn S. Baughman
for: U.S. Forest Service
M 56-2 C.S. 58/28
January, 1975

Witness Corner for C 1/4 Cor. of Sec. 15. 150
Set - 30" long, 2 1/2" Diameter galv. iron pipe 24" in the ground,
in a mound of stones, with a 4" Brass cap marked:
T31S R2W WC 238 ft C 1/4 S 15 1974 RLS 536.
New BT's - A Pine, 10", bears N.20.5°E., 133.1 ft. scribed WC C1/4 S15 (BT)
brass washer stamped RLS 536.
A Pine, 7", bears S.2.5°W., 59.2 ft. scribed WC C1/4 S15 (BT)
with brass washer stamped RLS 536.
Note: Bearing trees have a 6" band of red painted around tree.
Corner is set on centerline of Section 15 N.89°51'44" E., 238.50 ft.
from center 1/4, S 15 and lies in an open field 150 ft. West of road.
1/75

Witness Corner for C 1/4 Cor. of Sec. 15 151
Set - 30" Long, 2 1/2" Galv. I. P. 26" in the ground, in a mound of stones
with a 4" Brass cap marked: T31S R2W WC 127 ft C1/4 S15 RLS 536 1974.
BT's - A Cedar, 14", Bears S.2°E., 147.0 ft. scribed WC C1/4 S15 (BT) with
brass washer stamped RLS 536.
A Fir, 7", bears S.19°W., 151.2 ft. scribed WC C1/4 S15 (BT) with brass
washer stamped RLS 536.
Note: Bearing trees have a 6 inch band of red painted around tree.
Corner is set on centerline of Section 15, S.0°18'12" W of true C1/4
and lies in open field approximately 150 ft. West of road and approx.
110 ft. North of timber line to South of corner.
1/75

Glenn Baughman
for: U.S. Forest
Service
Jan. 1975
M 56-5
C.S. 58/30

Center 1/4 Corner for Sec. 23 152
Set - 30" long, 2 1/2" Diameter galv. iron pipe 26" in the ground, in a
mound of stones, with a 3" brass cap marked: T31S R2W C 1/4 S23
OLS 536, 1975
BT's - A Cedar, 9" bears N.29°30'W., 19.5 ft. scribed C 1/4 S23 (BT) with a
brass washer stamped LS 536 nailed at bt.
A Cedar, 8" bears N.53°E., 28.9 ft. scribed C 1/4 S23 (BT) with a brass
washer stamped LS 536 nailed at bt.
Note: Both trees have a 6" red band painted around tree.
Corner is set between a 36" Cedar stump and a 26" Fir log, 100 ft. south
to edge of logged over unit..
Jan. 1975