Douglas County Surveyor's Record of Government Corners Renewed

T 31 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

153

Witness Corner to 1/4 Corner for Secs. 14 and 23.
Found - 1" gal. I. P. with brass cap set 8" above ground marked T31S R2W 1/4 S14 S23. County Surveyors Office 1966. Ren. #70
16" Madrone, bears N.34°W., 73.7 ft. (1/4 CS BT) visible
Orig. 15" Fir stump east 6.5 ft. (B) visible.
Orig. 48" Pine stump S.38°E., 17.5 ft. (BT) visible
I find corner lies in active slide area. I used single proportion method and corner moved downhill; which is impractical. I then established the true position (leaving the County Surveyors Corner out of position) by using call distance and bearing from 16" Madrone, which lies outside the recent slide area. By this method the new Corner position moves S.56°13'43"E., 3.55 ft. from County Surveyors Corner. I then established Witness Corners on the North line of Sec. 23 to the East.
Set - 30" long, 2 1/2" Galv. I.P. 26" in the ground, in a mound of stones, with a 3" brass cap marked: T31S R2W

WC
← 295.85
1/4 S14
S23
RLS 536 1975

New BT's - An Oak, 14" bears N.10°W., 71.4 ft. scribed WC 1/4 S14 (BT) with a brass washer stamped LS 536 nailed at base.
A Madrone 12", bears S.32°30'E., 135.6 ft. scribed WC 1/4 S23 (BT) with a brass washer nailed at base marked LS 536.
Note: Corner lies 1 foot south of East-West fence in logged over unit.

Jan. 1975

Glenn Baughman
For: U.S. Forest Service
Jan. 1975
M 56- 5
C.S. 58/30

154

Witness Corner to 1/4 Corner for Secs. 14 and 23.
Found - 1" Gal. I.P. with brass cap set 8" above ground marked T31S R2W 1/4 S14 S23 County Surveyers Office 1966.
16" Madrone, bears N.34°W., 73.7 ft. (1/4 CS bT) visible.
Orig. 15" Fir stump, east 6.5 ft. (B) visible
Orig. 48" Pine stump, S.38°E., 17.5 ft. (BT) visible.
16" Ash, bears S.12°E., 48.6 ft. (S23 CS BT) visible
I find corner lies in active slide area. I use single proportion method, and corner moves downhill; which is impractical. I then establish the true position, (leaving the County Surveyors Corner out of position) by using call distance and bearing from 16" Madrona, which lies outside the recent slide area. By this method the new corner position moves S.56°13'43"E., 3.55 ft. from County Surveyors Corner. I then establish Witness Corners on the North line of Section 23 to the East.
Set - 30" long 2 1/2" Galv. I.P. 26" in the ground, in a mound of rock, with a 3 inch brass cap marked: T31S R2W

WC
← 526.76
S14
S23
RLS 536 1975

New BT's - A Madrone 8", bears N.26°E., 138.0 ft. scribed WC 1/4 S14 (BT) with a brass washer stamped LS 536, nailed at BT.
A Madrone, 12", bears S.53°E., 84.0f t. scribed WC 1/4 S23 (BT) with a brass washer stamped LS 536, nailed at BT.
Note: Both trees have a 6" red band painted around tree.
Corner lies 4 ft. South of East-West fence in logged over unit.

155

Center 1/4 of Sec. 22
Set - 30" long, 2 1/2" Gal. I. P. 25" in the ground, with mound of rock, with a 3" brass cap stamped: T31S R2W
C 1/4 S22
RLS 536 1975

Glenn Baughman
for: U.S. Forest Service
Jan. 1975
M 56 - 6
C.S. 58/32

BT's - A Cedar, 11", bears S.19°E., 16.2 ft. scribed C 1/4 S22 (BT) with brass washer stamped LS 536 nailed at BT. blaze.
A white Fir, 7", bears S.78°W., 13.1 ft. with brass washer stamped LS 536 nailed at BT blaze.
Note: Both trees have a 6" red band painted around trees. Corner lies in edge of fir and cedar thicket, Corner bears N.51°W., 196 ft. from northwest corner of partially collapsed building, and 3 ft. south of old blaze line.

Jan. 1975