

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

156

Witness Corner to Sec. Corners 16, 15, 21 and 22.

Found - 1966 County Surveyors Office Brass cap for 1/4 Corner. Ren. # 88  
A 7" Cedar, bears N.2°W., 12.0 ft. scribed T31S R2W S 16 CS BT.  
A 8" Cedar, bears N.47°W., 15.5 ft. scribed T31S R2W S 16 CS BT.  
A 6" Cedar, bears S.21°W., 15.2 ft. scribed T31S R2W visible.  
A 12" Cedar, bears S.44°W., 33.1 ft. @ 18° 30' scribed T31S R2W  
S 21 CS BT.

The corner lies in recent slide. I leave the County brass cap out of position. I reestablish corner position by County Surveyors bearing trees which lie outside of the slide area, a 6" and 12" cedar. Then I set the witness corner on South line of S 21 S 22 outside of slide area.

Set - 30" long 2 1/2" Gal. I. P. 24" in the ground, in a mound of stone with a 3" brass cap stamped: T31S R2W WC S16 S15 S21 S22 OLS 536 1975. (247.03 ft. south of corner)

BT's - A Cedar, 7", bears S.56°E., 9.8 ft. scribed WC T31S R2W S22 BT with brass washer stamped CS 536 nailed at B.T. blaze.  
A D. Fir, 9", bears N.12°W., 9.0 ft. scribed WC T31S R2W S21 BT with brass washer stamped CS 536 nailed at B.T. blaze.

Note: Both trees have 6" red band painted around the tree corner. It lies on steep East slope approx. 100 ft. East of ridge top and 247 ft. South of draw.

Jan. 1975

157

Witness Corner to Secs. 16, 15, 21 and 22.

Found - 1" Gal. I.P. with 1966 County Surveyors Brass cap for 1/4 Cor.  
7" Cedar, bears N.2°W., 12.0 ft. scribed T31S R2W S16 CS BT. Ren.#88  
8" Cedar, bears N.47°W., 15.5 ft. scribed T31S R2W S16 CS. BT.  
6" Cedar, bears S.21°W., 15.2 ft. scribed T31S R2W visible  
12" Cedar, bears S.44°W., 33.1 ft. at @ 18°30', scribed T31S R2W  
S21 CS BT.

Corner lies in recent slide: I leave the County Brass cap out of position. I reestablish corner position by County Surveyors bearing trees, using the 6" and 12" Cedars, which lie outside slide area; I then set witness corner on the South line between secs. 21/22 outside of active slide area.

Set - 30" long, 2 1/2 " Gal. I.P. 26" in the ground, in a mound of stone with a 3" brass cap stamped: T31S R2W WC 121.54 ft. S16 S15 S21 S22 OLS 536 1975.

BT's - A Cedar 10", bears S.79°E., 32.6 ft. scribed WC T31S R2W S21 BT with brass washer stamped LS 536 nailed at BT blaze.  
A cedar 8", bears S.32°W., 29.3 ft. scribed WC T31S R2W S22 BT with brass washer stamped LS 536 nailed at BT. Blaze.

Note: Both trees have a 6" red band painted around tree. Corner lies 121 ft. South of draw and slide area.

Jan. 1975

158

1/4 Corner between Secs. 16 and 21.

Set - 2" Iron pipe with 3" brass cap stamped T31S R2W 1/4 16 and 21, 1975, OLS 536.

From which bears:

A 13" Pine, N.22°W., 47.5 ft. scribed 1/4 S16 BT.  
A 10" Pine, S.59°W., 36.2 ft. scribed 1/4 S21 BT.

Jan. 1975

Sec. Cor. Common to Sec. 20 & 29

Found: Original 40" Fir now 48" stump with open blaze and visible scribe "S20 BT". Orig. S.W. BT completely gone leaving only a hole where it stood.

Set: A brass cap on a 1" IP stamped DOUGLAS CO. SURVEYOR 1975

From which: A 48" Fir stump OBT  
bears N86°W., 27.1 ft.)

T31S R2W  
S20  
S29 S28

A 14" Yew scribed "T31S R2W S29 CSBT" in a double blaze bears S8W., 93.3ft.

The section corner for sections 21&28 bears N2°W., 108.6 ft.  
(Call: N0°03'W108.2) Compass Declination 20°

159

Glenn Baughman for  
U.S. Forest Service  
Jan. 1975  
M 56 - 6  
C.S. 58/32

Glenn Baughman for:  
U.S. Forest Service  
Jan. 1975  
C.S. 58/33  
M 56 - 7

Clell Goodwin  
Gary Langlitz  
Vic Cangie  
Lenora Ladig  
7/2/75  
C.S. 57/34