

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 2 R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

Closing Cor. to Sec. 21 and 28
Found: Original 36" Fir now 42" stump with opened blaze and
scribed 25 visible
Original 7" now 15" Madrone alive and well healed
Set: Brass cap on 1" IP stamped

DOUGLAS CO. SURVEYOR
1975

T 31 S R2W	
S 20	$\frac{S21}{S28}$ CC

160

Clell Goowin
Gary Langlitz
Vic Cangie
Lenora Ladig
7/2/75
C.S. 57/34

From which: A 15" Madrone OBT bears N 3 1/2° E., 19.8 ft.
A 42" Fir stump OBT bears S56° E., 25.1 ft.
A 8" Chinquapin scribed "T 31S R2W S21 CC CS BT" in
double blaze bears N88° E., 38.3 ft.
Section corner for sections 20 & 29 bears S 2° E., 108.6 ft.
(Call So° 03' E 108.2 ft) Compass Declination 20°

West 1/4 Cor. Sec. 21

Found- A rotted fir stump approx 12" dia. bears N 38 1/2° E., 11.9 ft. Stump
has been opened and is scribed " 1/4 S21 BT"
Note: Orig. call to a creek north, 53.1 ft. course W., Checks good. Other
BT and orig. corner monument not found.

Set-Brass cap at west 1/4 corner sec. 21 stamped: T31S, R2W
"COUNTY SURVEYORS OFFICE"
1975

Set spike in 36" dia. fir stump, bears N 19 1/2° E., 122.4 ft. Spike stamped
"B0 1 "

Set spike in 48" dia. fir stump bears N 19° W, 108.8 ft. Spike stamped "B0 2"
Note: the east 1/4 corner of section 20 bears S2° E, 163.9 ft., (Rec., S 0.0 3' E,
144.9 feet) Mag. Dec. 20° E 12/15/75

161

L.E. Monrean
P.L. E.
J.H.C.
C.S. 57/39
12/15/75

East 1/4 cor. to Sec. 20

Found-A rotted Hemlock, 12" Dia. broken off approx. 1' above ground, stump
firmly in place bears S 50° W., 14.5 ft. Downed tree is scribed "1/4 S20 BT"
Rotted, Burned remains of a fir, dia. indeterminate, bears N27° W., 16.5 ft.
SET- brass cap at east 1/4 corner of Sec. 20 Stamped:

COUNTY SURVEYORS OFFICE
1975

T31S R2W	
	1/4 S20

SET- spike in 36" dia. fir stump, bears N27° W., 40.3 ft. Spike stamped "BO 1"
SET- spike in 42" dia. stump, bears N73° W., 57.9 ft. Spike stamped "BO 2"
Note- the west 1/4 corner of sec. 21 bears N2° W, 163.9 ft., (Rec. N 0° 3' W., 144.9 ft.)
Mag. Dec. 20° E 12/15/75

162

1/4 Corner Sec. 28. & Sec. 33

Found-not of record- A bronze cap, 2 1/2 " dia. on a 1 1/2 dia. pipe cap is
is stamped

T31S	R2W
1/4	28
	33
30	10

SEE ALSO
#173

163

L.E. Monrean
P.L. Earle
J.H. Cook
CS 57/39

An oak stump, 18" dia. bears N 15° E, 20.0 ft. to center (record 19.1 ft)
Stump is burned and rotted, has a scar, no scribing found.

D. Fir (not of record) 25" dia. bears S 13° E., 12.1 ft. Tree is blazed, I
opened blaze and found scribed "1/4 S33", scribe on lower blaze not
legible., ----Did not renew corner as I could not find scribing in
oak stump. Mag. Dec. 20° E 12/17/75

North 1/4 Corner for Sec. 1 and South 1/4 Cor. Sec. 36, T30-2.

Found - Remains of an orig. BT, a 50" Pine, now a hollow, burnt & rotting
stump. After a diligent search, we find a well-preserved piece
of wood with good scribing "BT" visible. This piece of wood was
fd. at the base of the stump.

We also find a hollow oak snag at the proper location for the orig.
NW BT, however we find no evidence of cor. markings.

At the true cor. point as determined by the record bearing and distance from
the aforementioned remains of the orig. SE BT, an orig. 50" Pine now a
badly deteriorated stump, bearing S. 55° E., 19.8 ft. from the cor. point

We Set - A 1"x30" I.P. 25" in the ground with brass cap attached marked:

Douglas County Surveyor
1976

T30 S R2W	
1/4	$\frac{S36}{S1}$
	T31S R2W

164

Co. Surveyor Off.
G. L. Langlitz
A. Cangie
D. Stewart
April 22, 1976
C.S. 59/8