

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31681

C O N T.

G.L. Langlitz
A. Cangie
D. Stewart
April 22, 1976
C.S. 59/8

We find no trace of the orig. corner monument. 164
New BT's - A 9" D. Fir bears N.75°W., 60.9 ft. scribed "1/4 S36 CS BT" on
a double blaze.
A 15" D. Fir bears S.2 1/2°E., 50.7 ft. scribed "1/4 S1 CS BT" on a
double blaze.
We deposit the found scribing at the base of the Pine stump.
Note: A fence corner of nearly new fences running south and east bears
S.36°W., 58 ft.
Compass declination setting: 20° east.

4/22/76

Section Corner for Secs. 32 and 33 only, T30-2 165
Found - 22" Fir, S.26°E., 33.5 ft. County Ren. #131
18" Fir, N.50°E., 38.2 ft. Down OBT.
36" Fir, N.3°W., 26.4 ft. Down OBT.
Reset Corner S.26°E., 33.5 ft. from 22" Fir.
New BT - 7" Fir, N.88°E., 71.9 ft.

1/4 Corner Sec. 33 only, T30-2 166
Found - County Surveyor 1966 BCIP mkd. 33 Ren. #129

BT's - 30" Cedar N.19°W., 12.2 ft. OBT
5" Hemlock N.31 1/2°E., 26.3 ft. County BT
28" Fir S.2 1/2°W., 6.5 ft. OBT
Changed cap to read "Sec. 33 only".

RE-NEWED, SEE CORNER NO. #225

1/4 Corner For Sec. 4 only. 167
Set - 5/8" x 30" Iron Rod & Alum. Cap.
BT's - 32" Fir, S.8 1/4°W., 21.0 ft.
5" Oak, S.56 1/2°W., 20.4 ft.

Center 1/4 Corner for Sec. 4 168
Set - 5/8" x 30" Iron Rod & Alum. Cap
BT's - 38" Pine N.11 1/2°W., 223.6 ft.
Rock Mound, S.38 1/2°W., 25.5 ft.
Pickett Butte L.O., N.62 1/2°E.
Diamond Rock, S.14 1/2°E.

7/15/76

1/4 Corner for Secs. 4 and 9. 169
Set - 5/8" x 54" Iron Rod & Alum Cap.
BT's - 10" Cedar, S.37°W., 8.2 ft.
12" Cedar, N.40°E., 23.3 ft.

Center 1/4 Corner for SEC. 21 170
Set - Brass cap on 2" Gal. I.P. Piled rock around brass cap set 6" above groun
mkd. T31S R2W C 1/4 S21 RLS 866 1977.
BT's - 10" Black Oak scribed T.31S R2W C1/4 S21 BT, disk LS 866 attached.
bears N.53°42'E., 27.3 ft.
6" Ponderosa Pine scribed as above, bears N.20°14'W., 43.4 ft.
BT's tagged W-53
Iron Guard post bears N.4.0 ft. 54-4 sign attached.

1/17/77

East 1/4 Corner for Sec. 21. 171
Found - 1966 Douglas County Brass cap properly marked. Ren. #107
14" D. Fir, scribe visible, bears N.9°W., 45.0 ft.
20" D. Fir stump, scribe visible, bears S.77 3/4°E., 8.2 ft.
10" Snag. Scar visible. bears N.43 3/4°W., 5.9 ft.
36" Stump, deteriorated, bears S. 02 3/4°E., 65.0 ft.
New BT - 14" Cedar, scribed T31S R2W 1/4 S22 BT, LS 866 disk attached,
bears S.52°E., 74.1 ft.

12/2/76

Howard w. Johnstone, Ore. #498
For: Roseburg Lumber Company
July 15, 1976
M 56 - 49

William Ruppert
For: U. S. Forest Service
Dec. 1976 and Jan. 1977
M 65 - 1 C.S. 58/136