

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 31      T. S.      R 2      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

**172**

Center 1/4 Corner for Sec. 28  
 Found - a 1" Gal. I.P. not of record at their intersection of 2 new fences, which bears N.79°17'W., 79.82 ft. from true C 1/4 S.28.  
 Set - a 2" x 30" Gal. I.P. with brass cap marked T31S R2W C 1/4 S28 RLS 866 1977. 24" of pipe buried  
 New BO's - A steel post set 5' North with signs 54-2 & 9 facing East  
 A treated wood post set 51' West with signs 54-2 & 5 facing South.  
 BT's - 16" White Fir bears N.17°11'E., 79.8 ft.  
 12" Cedar bears S.52°21'E., 70.6 ft.  
 Both trees scribed T31S R2W C 1/4 S28 BT. LS 866 Disk attached.

1/27/77

**173**

1/4 Corner for Secs. 28 and 33.  
 Found - Brass cap on 1" Gal. I.P. not of record bearing & distance to true corner is S.44°43'E., 11.2 ft.  
 BT's - An Oak stump found with county surveyor's tag, no scribing. # <sup>see also</sup> 163 bears S.14°20'W., 19.5 ft. Stump is burnt & rotted, no scar is discernible. Not of record  
 24" D. Fir found tagged & recently cut open shows scribing 1/4 S33 and bears N.15°02'W., 11.9 ft. to brass cap. No record  
 Set - 2" x 30" Gal. I.P. with brass cap mkd. T31S R2W 1/4 S28 S33 RLS 866 1977. 24" of pipe buried. Cairn to cap.  
 BO's - Steel fence post 4.0 ft. North with signs 54-2 & 54-4 facing West.  
 BT's - 14" D. Fir bears N.82°26'E., 38.8 ft. scribed T31S R2W 1/4 S28 BT.  
 14" Cedar bears S.42°41'E., 21.9 ft. scribed T31S R2W 1/4 S33 BT.  
 LS 866 disk attached.

William Ruppert  
 For: U. S. Forest Service  
 Jan. & Feb. 1977  
 M 65 - 2 C.S. 58/137

1/77

**174**

North 1/4 Corner for Sec. 28.  
 Set - 2" x 30" Gal. I.P. with brass cap mkd. T31S R2W N 1/4 S28, RLS 866 1977. 24" of pipe buried in base of stump cutaway, cairn to cap.  
 BT's - 10" D. Fir scribed T.31S R2W N 1/4 S28 BT tagged & painted, brass disk LS 866 attached, bears S.54°14'W., 64.8 ft.  
 11" W. Fir, scribed T.31S., R. 2 W N. 1/4 S 21 BT, tagged & painted, brass disk LS 866 attached, bears S.29°46'E., 83.3 ft.

1/27/77

**175**

Center 1/4 Corner for Sec. 13  
 Found - 1 1/2" Steel auto axle solidly set with top flush to ground. Corner is in a 3 way fence corner. Ren. #15A  
 A 20" Orig. 16" D. Fir stump bears S.7°E., 13.2 ft. Has a double healed blazes. (Rec. S.2°E.)  
 A 22" Orig. 14", D. Fir bears N.7°E., 7.5 ft. (Rec. N.2°E.) to center of tree. (Rec. Dist. of 6.6 ft. is to face) Has a single healed blaze.  
 Set - 2 1/2" Brass cap on a 1 1/2" G. Iron Pipe. Referencing the axle I remove the axle and place the brass cap in the exact same location. I bury the axle alongside the brass cap. Brass cap stamped: County Surveyor's Office T31S R2W C 1/4 S13 1977.  
 New BT's - A 13" D. Fir bears N.68°W., 56.7 ft. scribed "C 1/4 S13 CS BT" on a double blaze. Placed County BT signs on the orig. BT and the new BT.

Dennis Gaylord  
 U.S.F.S.  
 Deputy, Doug. Co. Surveyors Office  
 Witness: Roland Simshauser  
 Nov. 10, 1977  
 C.S. 59/42

Note: Some local attraction may be caused by fence wires.

**176**

1/4 Corner for Sec. 6 and 7.  
 Found - A stone, 16" x 8" x 6" firmly set in the ground. No markings visible on the stone.  
 A 44", Orig. 36", D. Fir nearly dead, bears S.70°W., 11.22 ft. Has a healed scar.  
 A 31" Orig. 30", D. Fir stump bears N.67°W., 16.0 ft. (Rec. 16.5 ft.) Has a healed scar.  
 Placed County BT signs on both trees.  
 Set - Referencing the stone monument, I remove stone & set 9n its place a 2 1/2" Brass cap on a 1" Galv. I. P. marked County Surveyors Office T 31 S R 2 W 1/4 S6 S7 1977.  
 I bury the orig. corner stone alongside the brass cap.  
 New BT's - A 25" D. Fir bears S.53°W., 57.5 ft. scribed "1/4 S7 CS BT" on a double blaze.  
 A 9" D. Fir bears N.50°30'E., 38.3 ft. scribed "1/4 S6 CS BT" on a double blaze. Placed County BT signs on both trees.

Dennis Gaylord U.S.F.  
 Deputy, Co. Surveyors Office  
 Roland Simshauser  
 Dec 8, 1977  
 C S 59/42

12/8/77

File on 5/91  
 J. NEWMAN M113-61