

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 31 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Glenn Baughman
For: U.S. Forest
Service
March 1978
M 65 - 68

1/4 Corner for Secs. 2 and 1.
Set - 2" x 30" I.P. with brass cap stamped T31S R2W WM 1/4 S2 S1 1978
OLS 536.
BT's- 6" D. Fir bears S.33°W., 47.0 ft. scribed 1/4 S2 BT.
9" D. Fir bears S.32°E., 35.4 ft. scribed 1/4 S1 BT.

185

- 3/78 -

Glenn Baughman
For: U.S. Forest
Service
April 1978
M 65 - 9

Center 1/4 for Sec. 1
Set - 2" x 30" I.P. with brass cap stamped "T31S R2W WM
C 1/4 S1 1978 OLS 536.
BT's - 9" D. Fir bears S.2°W., 9.5 ft. scribed C 1/4 S1 BT.
14" D. Fir bears N.86°E., 49.3 ft. scribed C 1/4 S1 BT.

186

- 4/78 -

187

1/4 Corner for Secs. 1 and 12.
Set - 2" x 30" I.P. with brass cap stamped T31S R2W WM 1/4 S1 S12
1978 OLS 536.
BT's - 12" W. Fir bears N.9°E., 59.0 ft. scribed 1/4 S1 BT.
9" W. Fir bears S.79°E., 24.6 ft. scribed 1/4 S12 BT.

- 4/78 -

188

Howard Johnstone
For: Roseburg Lbr.
Company
June 13, 1978
M 70 - 20

Center 1/4 for Section 24
Set - 5/8" x 36" Iron rod with aluminum cap.
BT's - 6" Fir bears N.15° W., 11.0 ft.
4" Cedar bears S.36°E., 12.5 ft.

- 6/13/78 -

189

Glenn Baughman #536
For: U.S. Forest
Service
July 1978
C.S. 58/173

Section Corner for Secs. 26, 25 35 and 36.
Found - 1" I.P. with 2" Brass cap 14" above ground. Ren. #69
A cedar, 22" bears S.60°E., 13.9. ft. good blazed face.
A white oak, 26" bears S.30°W., 5.3 ft. good blazed face.
A Douglas fir, 36" bears N.35°E., 5.7 ft. (now down) good blaz
face.
A white oak snag, 20" bears N.45°W., 15.2 ft. ~~no~~ face visible.
A Douglas fir, 10" bears N.29°W., 26.7 ft. good blazed face.
(Rec. N.52°W., 39.3 ft.)
A Douglas fir, 10" bears N.62°E., 39.0 ft. good blazed face.
(now down). (Rec. N.29°E., 27.0 ft.)
A white fir, 8" bears N.85°E., 35.9 ft.
Scribed: I scribed "T 31 S R 2 W S25 BT" on double blazed face of White
fir, 8" bears N.85°E., 35.9 ft.

- 7/78 -

190

Loyd R. Moffit
For: Umpqua National
Forest
July, 1976
M 70 - 26

Center 1/4 Corner for Section 12
Set - 2" pipe with 3" brass cap stamped T31S R2W C1/4 + S 12
PLS 944 1978.
BT's - A 6" Fir bears S.69°W., 11.0 ft. scribed C 1/4 S 12 BT.
A 20" Fir bears South 3.0 ft. scribed C 1/4 S 12 BT.

- 7/78 -

191

Section corner for Secs. 7 and 18 only. (West side)
Found - 1/2" Pipe and orig. corner stone. Ren. #22
Set - 2" pipe with 3" brass cap stamped: T31S R3W S12 T31S S7 S18 C
R2W PLS 944 1978.
From which:
A 42" Fir bears N.68°E., 42.9 ft. shows scars.
A 36" Cedar bears S.45°E., 3.3 ft. scribe visible.

192

Loyd R. Moffit
Reg. L.S. No. 944
For: Umpqua National Forest
August, 1978
M 72 - 76

1/4 Corner for Sec. 12 only - T31-3
Found - 1/2" Pipe with stone scribed, 1/4, laying beside it. See Ren.
#70 in T31-3
Set - 2" pipe with 3" brass cap stamped T31S R3W R2W 1/4 S12 PLS 944
1978.
From which-A 10" Hemlock bears N.74°E., 16.4 ft. scribe visible.
A 30" Cedar bears S.48°E., (Rec. S.51°E.) 45.21 ft. bark scribe
visible.
A 10" Fir bears S.54°W., 25.8 ft. scribed 1/4 S12 BT.