

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 31 T. S. R 2 R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

Loyd R. Moffit
For: Umpqua National
Forest
August, 1978
72 - 76

Loyd R. Moffit
For: U. S. Forest Service
August, 1978
C.S. 58/176

William J. Ruppert, LS #866
For: U.S. Forest Service
February, 1979
C.S. 58/176

SE corner for Sec. 12 only - T.31-3 193
Found - 3/4" pipe with orig. corner stone laying beside it. See Ren.
#69 in T31-3
Set - 2" pipe with 3" brass cap stamped T31S S12 S13 T31S R2W S18 R3W
PLS 944 1978.
From which:
A 16" Fir bears N.54°E., 25.2 ft. shows scars.
A 7" Fir bears S.80°W., 21.3 ft. scribed T31S R3W S12 BT.
A rotten Fir snag bears S.86°W., 30.03 ft. BT scribe visible.
A 5 ft. Fir bears N.71 1/2°W., 25.41 ft. shows scars.

8/78

1/4 Corner for Secs. 6 and 5. 194
Found - A granite stone 18" x 14" x 4" marking the 1/4 corner
From which: A 20" Fir bears S.51°W., 18.5 ft. shows scars.
A 20" Hemlock bears S.65°E., 15.8 ft. scribe visible.
Set - A 2" pipe with 3" brass cap stamped: T31S R2W 1/4 S6 S5 PLS 944 1978.
New BT's- A 16" Hemlock bears S.10°E., 34.1 ft. scribed 1/4 S5 BT.
Note: The orig. stone is buried along side the 2" pipe. The new bearing
tree has a brass tag #944 nailed at BT scribe.

8/78

Closing corner for Secs. 6 and 5 only. North boundary. 195
Found - A granite stone 15 x 15 x 6 inches marking the closing corner
From which: A 36" Fir bears S.14°W., 13.2 ft. scar healed over.
A 24" Madrone (now dead) bears S.14°E., 49.5 ft. scar visible.
Set - 2" pipe with 3" brass cap stamped: T30S R2W S32 S6 S5 CC T31S R2W
PLS 944 1978.
New BT - A 8" Fir bears S.53°E., 21.8 ft. scribed T31S R2W S5 BT.
Note - The orig. stone is buried along side the 2" pipe. The new BT has a
brass tag #944 nailed at BT scribe.

Section corner for Secs. 31 and 32 only - T30-2 196
Found - A stone 18 x 10 x 9 inches marking the south section corner between
sections 31 and 32, *Fook 7/95 B. Shaner C.S. 63/161-36A*
From which: A 36" Fir bears N.23°E., 124.7 ft. scar visible.
Set - A 2" pipe with a 3" brass cap stamped: T30S R2W S31 S32 T31S R2W
S6 PLS 944 1978.
New BT - A 8" Fir bears N.20°W., 15.4 ft. scribed T30S R2W S31 BT.
Note - The orig. stone is buried along side the 2" pipe. The new BT has a
brass tag #944 nailed at BT scribe.

8/78

Southwest Corner for Sec. 16 only. 197
Found - 1" pipe with 1961 County Brass cap properly marked. Ren. #27
36" Cedar, N.82°W., 3.0 ft. scars.
20" D. Fir, N.81°E., 65.0 ft. good scar.
I Scribed: "T31S, R2W S16 BT" on 16" D. Fir, N.29 1/2°E., 34.5 ft. Attached
brass washer "LS 866" to lower blaze.

2/79

Closing Corner for Secs. 5 and 4 only. North. 198
Found - 42" D. Fir corner tree.
A 1" Iron pipe with 1966 County brass cap attached is next to
south side of tree. Cap properly marked. Ren. #130
24" Madrone, S.5 1/2°W., 18.4 ft. scribe visible.
Set - 6 foot steel fence post approximately 2 feet into the ground and
attached bearing tree sign. Painted top of post red. Post bears
S.70 3/4° E., 17.8 ft. from corner tree.
No suitable bearing trees in Southeast quadrant.

2/79

West 1/4 Corner for Section 4 only. 199
Found - 1" Iron pipe on 2 1/2" brass cap, 1966 County Surveyors cap properl
marked. Stone alongside pipe. Ren. #138
8" D. Fir, N.85 1/2°E., 13.6 ft. good scar.
28" D. Fir uproot S.28°E., 21.4 ft.
12" D. Fir, S.16 3/4°W., 10.5 ft. good scar.
Scribed: "1/4 S4 BT" on 14" D. Fir bears N.29 3/4°E., 27.0 ft. Attached 3/4"
Brass washer "LS 866" to lower blaze.

2/79

RE-RENEWED, SEE CORNER NO. #226