

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

200

Section Corner for Secs. 9, 10, 16 and 15.

Found - A 1"x36" I.P with 1966 County Surveyors brass cap properly marked Ren. #82, protruding 1 ft. above a 2 1/2" x 2' x 1' mound of stone

A 3' x 2' x 1 1/2' serpentine stone not found (1908)

A 30" Pine bears N.2 1/2°W., 960.0 ft. (Rec. 949.1 ft.) partial scribing "9" visible. This BT is down and rotted. (orig.)

An orig. 30" Pine, now a 36" stump, bears S.73 1/2°E., 468.6 ft. partial scribing "BT 1" Fd. in this rotted stump.

I do not find the NE orig. BT.

A 6" Ponderosa Pine, now 26", bears N.74 1/2°E., 178.5 ft. (rec. N.72 1/2°E., 182.8 ft.) with healed over single blaze

A 10" Cedar now a 28" fork (of a 3 fork tree) bears S.11°E., 252.6 ft. (rec. S.23 1/4°E., 259.4 ft.) with well healed single blaze. (1908)

A 12" Incense cedar, now 28" bears S.40°W., 164.1 ft. (Rec. S.32 1/2°W., 163.0 ft. ) with healed single blaze. (1908)

An 8" Cedar now a 24" Fork (of 3 fork tree, 48" diam. at ground level) bears N.21°W., 87.5 ft. (rec. N.16°W., 79.2 ft.) with healed single blaze. (1908)

A 23" Pond. Pine, now 24" bears N.4°E., 98.3 ft. (rec. N. 1/2°W.) with visible scribing "T31S R2W S9" in double blaze. Ren. #82

A 24" Pond. Pine, now 26" bears N.61 1/2°W., 64.2 ft. (Rec. N.65 1/2°W.) with visible scribing "T31S R2W S9 CS" "BT" in double blaze. Ren. #82.

A 10" Cedar, now a 10" For, (2 fork tree, 18" at base) bears S.2°E., 27.9 ft. (Rec. S.6°E., 29.5 ft.) with visible scribing "S15 CS" "BT" in double blaze.

A 12" Cedar bears S.64°W., 101.5 ft. (Rec. S.61°W.) with visible scribing "T31S R2W S16" "BT" in double blaze.

We left brass cap in position. The 1908 retracement does not state conclusive evidence that the retracement corner was set at orig. position. No bearings or distances were stated, does not state finding orig. post. Therefore cap left at orig. brg. & distance from original SW BT and rec. brg. from NW orig. BT.

4/10/79

201

North 1/16 corner for Sec. 6, T.31-1 and Sec. 1, T.31-2.

Found - 2" Iron pipe with 1967 Baughman brass cap. Ren. #134

18" Douglas Fir, S.22°W., 12.0 ft.

36" Pine stump N. 1 1/2° W., 46.5 ft.

Marked - 8" Douglas Fir, N.9°W., 19.2 ft. "N 1/16 S - 1" bearing tree and fastened brass washer stamped Land Surveyor 536 in lower part of blaze.

Section corner for Secs. 4 and 9 only.

202

Found - 1961 County brass cap and 1" pipe. Ren. #33

36" Oak bears S.8 1/2°W., 56.0 ft. good scar.

34" B. Oak, N.60 3/4°W., 57.8 ft. good scar.

10" Cedar, S.23 1/2°E., 16.3 ft. Open.

42" stump, S.72 1/2°E., 142.6 ft. burned.

10" D. Fir, N.26 1/4°E., 10.9 ft. good scar.

New BT - 9" D. Fir, S.8°E., 77.5 ft. scribed "T31S. R2W S9 BT".

203

Center 1/4 Corner for Sec. 9

Set - 2" Pipe and 2 1/2" brass cap marked T31S R2W C 1/4 S9 PLS 866 1979.

BT's - 12" Cedar S.42°37'W., 223.4 ft. scribed "C 1/4 S9 BT".

16" D.Fir, N.21°53'W., 102.4 ft. scribed "C 1/4 S9 BT".

R. R. Spike in asphalt E. 11.68 ft.

6 foot steel fence post W. 12.44 ft.

Jan-Mar. 1979

204

Section corner for Secs. 3 and 4; and 33 & 34 of T.30-2

Found- 20" Cedar corner tree.

1" pipe with 2 1/2" brass cap bears S.45°W., 1.3 ft. 1966 County surveyors cap. Ren. #178

24" stump very rotten S.35°52'E., 8.0 ft.

24" D.Fir good face S.6°22'E., 14.7 ft.

20" D. Fir good face S.68°32'W., 7.3 ft.

40" D. Fir good face N.66°35'W., 10.4 ft.

RE-NEWED CORNER NO. 233 234

Gary L. Langlitz  
Karen Reed  
Douglas County  
Surveyors Office  
April 10, 1979  
C.S. 60/24

Glenn Baughman  
For: U.S. Forest  
Service  
April 1979  
C.S. 58/176

William Ruppert  
For: U.S. Forest Serv.  
Jan.-March 1979  
M 70 - 57

William Ruppert  
LS #866  
For: U.S. Forest Serv.  
April 1979  
M 70 - 61