

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 31      T. S.      R 2      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

C O N T.

William Ruppert #866  
For: U.S. Forest  
Service - April 1979  
70 = 61

10" D. Fir good face, N.9°09'W., 32.6 ft.  
8" Cedar windfall N.36°09'W., 13.8 ft.  
Scribed New BT:  
18" D. Fir N.62°00'E., 43.3 ft. "T30S R2W S34 BT".

204

Bruce Shaner  
For: U.S.  
Forest Serv.  
Jan. 7, 1980  
RM 3 - 27

Center of Section 11  
Set - Brass cap mkd. T31S R2W W.M. C1/4 S11 PLS 430 1979  
From which:  
12" Douglas fir, I scribe "C 1/4 S11 BT: bears N.82°W., 79.0 ft.  
10" Douglas fir, I scribe "C 1/4 S11 BT" bears N.52 1/4°E.,  
227.5 ft.  
Note - 10" Yew post at C 1/4 set by County Surveyor Eppstein in 1928 +  
bears S.38°W., 26.25 ft. Yew post is fence corner post. Fences  
bear E., W., and N. REN. #18

205

Dennis Gaylord  
U.S. Forest Service  
Deputy, Doug. Co.  
Surveyors Office  
Leonard Herzstein,  
Witness  
April 16, 1980  
S. 61/6

1/7/80

Section Corner for Secs. 1, 2, 11 and 12.  
Found - Truck axle set firmly in ground in a mound of stones. Ren. #23  
One stone in the mound of stones could be the orig. corner stone  
but no marks are visible on the stone.  
Orig. BT. is now a 18" Oak, bears N.70°E., 26.7 ft. scribing  
visible "BT" on a previously opened blaze.  
A 12" D. Fir bears N.80°E., 25.6 ft. and has double healed blazes.  
A 17" Cedar bears S.54°30'E., 19.9 ft. to center of tree at  
base. Scribing is visible on a nearly healed upper blaze. Lower  
blaze is healed over. Ren. #52  
A 16" Cedar bears S.56°W., 36.8 ft. scribing visible on double  
blazes.  
A 9" Doug. Fir bears N.66°W., 13.0 ft. has double healed blazes.  
Set - Moving the axle aside, I set in it's place a 1" x 30" iron pipe  
with a 2 1/2" brass cap marked County Surveyor's Office  
T 31 S R 2 W S2 S1 S11 S12 1980. I bury the axle horizontally  
alongside the iron pipe and build a rock mound around the pipe.  
No new accessories established.  
Corner is 40 ft. north of F.S. Road #301.

206

Malcolm Clark  
For: U.S. Forest  
Service  
April 1980  
M 83 - 53 - C.S. 58/227

4/16/80

1/4 Corner for Sec. 31 only. (south)  
Found - 12" x 18" x 8" stone with "1/4" clearly chiseled on N. face.  
52" Fir stump bears N.40°30'W., 75.3 ft. scribing visible. Ren. #121  
19" White Fir bears N.72 15'E., 111.0 ft. scribing visible.  
A 1" iron pipe bears N.33°W., 4.15 ft. See Ren. # 21, C.S. 42/392  
Set - An alum. cap in the position of the stone stamped: T31S R2W  
1/4 S31 T32S R3W 1980 RLS 601".  
New BT - 6" Madrone bears N.26°15'W., 65.3 ft. scribed "T31S R2W 1/4  
S31 BT".

207

William Ruppert  
For: U.S. Forest  
Service  
May 1980

4/80

S.E. section corner for Sec. 36 only of T.31-3  
Found - 1" galv. I.P. with a 1966 County brass cap. Ren. #114  
15" Incense cedar, N.40°20'E., 68.4 ft. "T32S R3W S1 CS BT" visible  
16" rotten stump, S.15°56'W., 28.5 ft., two faces, one face has  
chopped scribing visible.  
31" Fir uproot, N.59°24'W., 60.6 ft. hollow face.  
New BT - 13" Yew, N.64°24'W., 67.6 ft. scribed "T31S R3W S36 BT". Attached  
3/4" brass washer marked "LS 866 to lower blaze.

208

M 84 - 4  
C.S. 58/143 (n)

5/80

Witness corner for the 1/4 corner for Sec. 36 only of T.31-3.  
Set - 2" x 36" galv. I.P. with brass cap marked "T31S R3W WC 1/4 S36  
N.0° 14'E., 122.79 ft. R2W PLS 866 1980".  
Constructed mound of rocks around pipe.  
New BTs - 11" D. Fir, S.25°29'W., 62.8 ft.  
13" D. Fir, S.41°05'W., 54.6 ft.  
Both trees scribed "WC 1/4 S36 BT". Attached brass washer marked  
"LS 866" to lower blaze of both trees.  
1/4 corner bears N.0°14'E., 122.79 ft. from witness corner. (See Ren. #36  
in T.31-3)

209

5/80