

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

210

William Ruppert
For: U.S. Forest
Service

May 1980
M 84 - 4 C.S. 58/143

S.W. corner for Sec. 31 only-
Found - \uparrow 1/2" I.P. Ren. #120
36" D. Fir, N.41°26'E., 23.1 ft. good scars.
14" W. Fir, N.47°42'E., 44.5 ft. scribing partly visible.
10" Hemlock snag, S.42°50'E., 27.5 ft.
31" D. Fir, S.31°30'E., 34.3 ft. Bark scribe 7 1/8" good scar.
18" D. Fir snag, S.4°50'E., 15.3 ft. "S1 T32S R2W BT" visible.
Set - 2" x 30" Galv. I.P. with 2 1/2" brass cap marked "PLS 866 T31S R3W T31S R2W S31 CC S1 T32S R3W 1980".

5/80

Bruce A. Shaner
For: U.S. Forest
Service

July 1980
C.S. 58/229

Center 1/4 Corner to Sec. ³⁴~~35~~
Found - 5/8" Iron rod with a 1 1/4" plastic cap mkd. "Nygren RS1035". See Ren. #177
6" Hemlock (record yew), scribes visible bears N.23°W., 7.2 ft.
6" Hemlock (record yew), scribes visible bears S.89°W., 15.1 ft.
6" Hemlock (record yew), scribes visible bears S.39°E., 5.9 ft.
Set - 2" Iron pipe with 2 1/2" BRASS CAP mkd. "T31S, R2W, W.M. C1/4, S34, RLS 430, 1980".
Reset Nygren's 5/8" iron rod alongside.

211

8/14/80

Bruce A. Shaner
LS# 430
For: U.S. Forest Ser.
July 1980
C.S. 58/229

1/4 Corner to Secs. 27 and 34
Found - 2 1/2" brass cap properly mkd. See Ren. #62.
Original corner stone sets alongside brass cap mkd. "1/4"
18" Douglas Fir stump, original BT, scribes visible, bears N31°W., 11.9 ft.
20" Douglas fir stump, original BT, scribes visible, bears South, 16.5 ft.
15" Douglas fir snag scribes visible bears S.71°E., 34.3 ft.
19" Douglas fir snag scribes visible bears N.76°W., 3.0 ft.
New BT's - 10" Douglas fir scribed "1/4 S34 BT", bears S.69°W., 21.6 ft.

212

1/4 Corner for Sec. 12; and Sec. 7 of T.31-1.
Found - 9" diam. Maple marked by Boyer in 1950 as a corner tree by proportionate measurement, with healed blazes on east and west sides with an 8" alum. nail in center of base of tree. See Ren. #3 of T.31-1, now bears S.6°E., 7.5 ft. from orig. corner position as determined by record bearing and distance from orig. BTs.

213

Leonard Herzstein, U.S.FS.
Deputy, Doug. Co.
Surveyors Office
Witnesses: Art
Arciniega; Joe Richey
October 1980
C.S. 61/11

A 1 1/2" I.P. projecting 14" above ground firmly set alongside corner tree, set in 1966 by Powell, with brass cap properly marked, now bears S.10°E., 7.9 ft. Ren. #47. I REMOVE marks from brass cap.
Orig. D. Fir, 36", N.57°E., 20.5 ft. with scribe mark "S" on bark blaze.
Orig. D. Fir, 30", N.12°W., 23.1 ft. with no marks visible. (both trees of sufficient age by growth ring count).
D. Fir, 12" now N.81 3.4°E., 11.3 ft. (Rec. N.48 1/2°E., 15.0 ft. to corner tree) with healed blaze facing N.48 1/2°E. Ren. #3 T.31-1
9" Maple, now N.85°W., 7.4 ft. (Rec. N.51 1/2°W., 15.0 ft. to corner tree) with healed blaze facing N.51 1/2°W.
22" D. Fir now N.0 1/4°E., 18.6 ft. (Rec. N.5°W., 26.7 ft. to corner tree) with healed double blaze. Ren. #47
Set - At record bearing and distance from orig. BTs, SET I.P. 2" diam. 30" long, 24" in ground within a 2 ft. mound of stone with brass cap marked "Douglas County Surveyor T31S R2W S12 1/4 S7 RLW 1980".

10/20/80